## Hamilton

## making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio 70C1X60 Hartland CFX Gloss White 1 gang 600W Resistive Leading Edge Push On-Off Rotary 2 Way Switching Dimmer Gloss White Item Image Wiring Dimensions Hemilton HARTLAND CFX 1X60 Resistive Leading Edge Push On-Off Rotary 2 Way Switching Dimmer 101: - 86.0 -Primary Range Hartland CFX Insert Type 1 gang 600W Resistive Leading Edge Push On-Off Rotary 2 Way Switching Dimmer Plate Finish Hartland CFX Gloss White Insert Colour Gloss White EAN13 Barcode 5017504008406 Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Wattage 600W Switched Poles Single Current Rating 2.5 Amp 220/250V AC Voltage Maximum Load 600W resistive Min Load 100W 50Hz Mains Frequency IP Rating IP2XD N/A Contact Gap Minimum **Terminal Capacity 1** 2 x 1mm2 **Terminal Capacity 2** 2 x 1.5mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Face plate must be earthed -5° to +40°C Ambient Operating Temperature Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-2-1 Tungsten filament GU10 lamps must be branded with a fuse base. When using mains voltage halogen lamps- dimmers Additional Notes should be de-rated by 25%. When dimming LED lamps de-rated by 75% - please contact our Technical for compatibility. CFX is a Registered Trade Mark No 2398667 Patents and Trademarks Hartland CFX is a Registered Design under Reference Nos. R21 = 3023446 SS2 = 3023445 All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. It is the policy of the company to improve products as part of our development programme. All products listed conform to current British or European standard and the product information is correct at the time of going to press. Therefore, we reserve the right to alter designs and dimensions without prior notice. Illustrations and diagrams are reproduced within Due to manufacturing processes we cannot Correct as at 16 October 2018 12:36 PM the limitations of reproduction and printing guarantee an exact colour match and shadings of E&OE process and are not binding of certain finishes R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ **SECA** Listed in STrimble +44 (0)1747 860088 F: +44 (0)1179 710414 Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB LUCKINS E: info@ milton-litestat.com www.hamilton-litestat.com Registered in London No. 941624 VAT Registration No. 222 6607 84

SL

Hamilton

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio