





70C2J12W

Hartland CFX Gloss White 2 gang RJ12 Outlet - Unshielded White

Item Image	Wiring	Dimensions																																																						
	<p style="text-align: center;">Wiring</p> <div style="display: flex; justify-content: space-around;"> <div style="text-align: center;"> <p>Datacom Module Rear View RJ11 / 12 Socket Rear View</p>  </div> <div style="text-align: center;"> <p>View of Transparent Cover</p>  </div> </div> <p style="text-align: center;">Cable tie anchor</p> <table border="1" style="font-size: 8px; margin: 0 auto;"> <thead> <tr> <th>Pin</th> <th>RJ11</th> <th>RJ12</th> <th>Wiring</th> <th>Colour</th> <th>Socket</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>NOT USED</td> <td>NOT USED</td> <td>NOT USED</td> <td>NOT USED</td> <td>NOT USED</td> </tr> <tr> <td>2</td> <td>GREEN / White</td> <td>BLUE</td> <td>GREEN / White</td> <td>BLUE</td> <td>GREEN / White</td> </tr> <tr> <td>3</td> <td>ORANGE / White</td> <td>YELLOW</td> <td>ORANGE / White</td> <td>YELLOW</td> <td>ORANGE / White</td> </tr> <tr> <td>4</td> <td>WHITE / Blue</td> <td>GREEN</td> <td>WHITE / Blue</td> <td>GREEN</td> <td>WHITE / Blue</td> </tr> <tr> <td>5</td> <td>BLUE / White</td> <td>RED</td> <td>BLUE / White</td> <td>RED</td> <td>BLUE / White</td> </tr> <tr> <td>6</td> <td>WHITE / Orange</td> <td>BLACK</td> <td>WHITE / Orange</td> <td>BLACK</td> <td>WHITE / Orange</td> </tr> <tr> <td>7</td> <td>NOT USED</td> <td>NOT USED</td> <td>NOT USED</td> <td>NOT USED</td> <td>NOT USED</td> </tr> <tr> <td>8</td> <td>NOT USED</td> <td>NOT USED</td> <td>NOT USED</td> <td>NOT USED</td> <td>NOT USED</td> </tr> </tbody> </table>	Pin	RJ11	RJ12	Wiring	Colour	Socket	1	NOT USED	NOT USED	NOT USED	NOT USED	NOT USED	2	GREEN / White	BLUE	GREEN / White	BLUE	GREEN / White	3	ORANGE / White	YELLOW	ORANGE / White	YELLOW	ORANGE / White	4	WHITE / Blue	GREEN	WHITE / Blue	GREEN	WHITE / Blue	5	BLUE / White	RED	BLUE / White	RED	BLUE / White	6	WHITE / Orange	BLACK	WHITE / Orange	BLACK	WHITE / Orange	7	NOT USED	NOT USED	NOT USED	NOT USED	NOT USED	8	NOT USED	NOT USED	NOT USED	NOT USED	NOT USED	<p style="text-align: center;"> Hamilton® HARTLAND CFX 2J12 2 gang RJ12 Outlet Unshielded 6 wire </p> 
Pin	RJ11	RJ12	Wiring	Colour	Socket																																																			
1	NOT USED	NOT USED	NOT USED	NOT USED	NOT USED																																																			
2	GREEN / White	BLUE	GREEN / White	BLUE	GREEN / White																																																			
3	ORANGE / White	YELLOW	ORANGE / White	YELLOW	ORANGE / White																																																			
4	WHITE / Blue	GREEN	WHITE / Blue	GREEN	WHITE / Blue																																																			
5	BLUE / White	RED	BLUE / White	RED	BLUE / White																																																			
6	WHITE / Orange	BLACK	WHITE / Orange	BLACK	WHITE / Orange																																																			
7	NOT USED	NOT USED	NOT USED	NOT USED	NOT USED																																																			
8	NOT USED	NOT USED	NOT USED	NOT USED	NOT USED																																																			

Primary Range	Hartland CFX
Insert Type	2 gang RJ12 Outlet - Unshielded
Plate Finish	Hartland CFX Gloss White
Insert Colour	White
EAN13 Barcode	5017504008420
Dimensions (Nominal)	Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips
Minimum Wall Box Depth	35mm
Switched Poles	N/A
IP Rating	IP2XD
Contact Gap Minimum	N/A
Earth Terminal Capacity 1	5 x 1mm ²
Earth Terminal Capacity 2	4 x 1.5mm ²
Earth Terminal Capacity 3	3 x 2.5mm ²
Earth Terminal Capacity 4	1 x 4mm ² Multi-strand
Earth Terminal Capacity 5	1 x 6mm ²
Product Class 1	Must be earthed (ref BS7671 415.2.1)
Ambient Operating Temperature	-5° to +40°C
Recommended Location	Internal Use Only
Maximum Installation Altitude	2000m
EuroFix Additional Notes	Can be used as either RJ11 (4 wires) or RJ12 (6 wires)
Patents and Trademarks	CFX is a Registered Trade Mark No 2398667 Hartland CFX is a Registered Design under Reference Nos. R21 = 3023446 SS2 = 3023445

<p>All products listed conform to current British or European standard and the product information is correct at the time of going to press.</p>	<p>All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.</p>	<p>It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.</p>
<p>Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.</p>	<p>Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.</p>	<p style="text-align: right;">Correct as at 16 October 2018 12:36 PM E&OE</p>

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ
 T: +44 (0)1747 860088 F: +44 (0)1179 710414
 E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB
 Registered in London No. 941624 VAT Registration No. 222 6607 84



CERT. No. FM1238