

## making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

## **70C3XLEDITR100**

| Hartland CFX Gloss  | 70C3XLEDITB100<br>White 3g 100W LED 2 Way Push On/Off Rota   | ry Dimmer Gloss White  |
|---|--|--|
| Item Image  | Wiring   | Dimensions   |
|   |  | Hamilton HARTLAND CFX 3XLEDITB LEDITB100 2 Way Dimmer  |
|   |  | 145.0  |
| Primary Range   | Hartland CFX   |  |
| Insert Type   | 3 gang 100W LED Trailing/Leading Edge Push On/Off Rotary 2 Way Switching Dimmer  |  |
| Plate Finish  | Hartland CFX Gloss White   |  |
| Insert Colour   | Gloss White  |  |
| EAN13 Barcode   | 5017504079048  |  |
| Dimensions (Nominal)  | Double: Height = 86.0mm Width = 145.0mm Depth = 5.0mm  |  |
| Fixing Hole Centres   | Box Fixing = 120.6mm Grid Fixing = CFX Clips   |  |
| Minimum Wall Box Depth  | 35mm   |  |
| Wattage   | 5-70W Per Gang   |  |
| Switched Poles  | Single   |  |
| Current Rating  | 0.3A Per Gang  |  |
| Voltage   | 230V-240V  |  |
| Maximum Load  | 5-70W Per Gang   |  |
| Mains Frequency   | 50Hz   |  |
| IP Rating   | IP2XD  |  |
| Terminal Capacity 1   | 2X1mm <sup>2</sup>   |  |
| Terminal Capacity 2   | 2X1.5mm²   |  |
| Earth Terminal Capacity 1   | 5X1mm <sup>2</sup>   |  |
| Earth Terminal Capacity 2   | 4X1.5mm <sup>2</sup>   |  |
| Earth Terminal Capacity 3   | 3X2.5mm²   |  |
| Earth Terminal Capacity 4   | 1X4mm² Multi-Strand  |  |
| Earth Terminal Capacity 5   | 1X6mm²   |  |
| Product Class 1   | Face plate muct be earthed   |  |
| Ambient Operating Temperature   | -5°C to +40°C  |  |
| Recommended Location  | Internal Use Only  |  |
| Maximum Installation Altitude   | 2000m  |  |
| Standard/Approval   | BS EN 60669-2-1  |  |
| Additional Notes  | Trailing Edge & Leading Edge Dimmer  |  |
| Patents and Trademarks  | CFX is a Registered Trade Mark No 2398667 Hartland CFX is a Registered Design under Reference Nos. R21 = 3023446 SS2 = 3023445 |  |
| All products listed conform to current British or<br>European standard and the product information is<br>correct at the time of going to press. | All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.                          | It is the policy of the company to improve products as part of our development programme.  Therefore, we reserve the right to alter designs and dimensions without prior notice. |
| Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.                      | Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.                  | Correct as at 16 October 2018 12:36 PM<br>E&Ol   |

T: +44 (0)1747 860088 F: +44 (0)1179 710414
E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84









