## Hamilton

## making connections beautifully

	70CDTVMW	
Hartland	I CFX Gloss White 1 gang Non-Isolated TV (Ma	ale) White
Item Image	Wiring	Dimensions
	EVIC Gasket Conductor Terminal Screw Correct position of conductor, screening braid and cable	HARTLAND CFX DTW Mon-solated TV (male)
Primary Range	Hartland CFX	
nsert Type	1 gang Non-Isolated TV (Male) (DAB Compatible)	
Plate Finish	Hartland CFX Gloss White	
nsert Colour	White	
AN13 Barcode	5017504008628	
Dimensions (Nominal)	Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm	
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips	
Inimum Wall Box Depth	35mm	
Switched Poles	N/A	
P Rating	IP2XD	
Contact Gap Minimum	N/A	
Earth Terminal Capacity 1	5 x 1mm2	
arth Terminal Capacity 2	4 x 1.5mm2	
Earth Terminal Capacity 3	3 x 2.5mm2	
arth Terminal Capacity 4	1 x 4mm2 Multi-strand	
arth Terminal Capacity 5	1 x 6mm2	
Product Class 1	Must be earthed (ref BS7671 415.2.1)	
Ambient Operating Temperature	-5° to +40°C	
Recommended Location	Internal Use Only	
Aximum Installation Altitude	2000m	
EuroFix Additional Notes	TV Outlet (IEC 169-2 male socket) Usually used for FM (DAB) outlet	
Frequencies 1	FM DC=5-2200 MHz	
Patents and Trademarks	CFX is a Registered Trade Mark No 2398667 Hartland CFX is a Registered Design under Reference Nos. R21 = 3023446 SS2 =3023445	
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 16 October 2018 12:36 E&

SL