SL

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

71CSS1USBPB-W

Hartland CFX Polished Brass 1 gang	13A Single Pole Switched Socket with 1 USE	B Outlets 1x2.1A Polished Brass/White
Item Image	Wiring	Dimensions
		Hemilton HARTLAND CFX SSTUSBX1 USB Charger + Switched Socket
		86.0 - 5.0 - 21.2 - 1.0 - 21.2
Primary Range	Hartland CFX	
Insert Type	1 gang 13A Single Pole Switched Socket with 1 USB Outlet 1x2.1A	
Plate Finish	Hartland CFX Polished Brass	
Insert Colour	Polished Brass/White	
EAN13 Barcode	5017504088859	
Dimensions (Nominal)	Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm	
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips	
Minimum Wall Box Depth	35mm	
Switched Poles	Single	
Current Rating	13 Amp, USB = 2.1A	
Voltage	180/250V AC	
Maximum Load	13 Amp, USB = 2.1A	
Mains Frequency	50/60Hz	
IP Rating	IP2XD	
Contact Gap Minimum	3mm	
Terminal Capacity 1	3 x 2.5mm2	
Terminal Capacity 2	3 x 4mm2	
Terminal Capacity 3	2 x 6mm2 Multi-Strand	
Earth Terminal Capacity 1	3 x 2.5mm2	
Earth Terminal Capacity 2	3 x 4mm2	
Earth Terminal Capacity 3	2 x 6mm2 Multi-strand	
Product Class 1	Must be earthed	
Ambient Operating Temperature	-15°C to +40°C	
Recommended Location	Internal Use Only	
Maximum Installation Altitude	2000m	
Standard/Approval	BS1363, BS5733, EN60950-1	
Patents and Trademarks	CFX is a Registered Trade Mark No 2398667 Hartland CFX is a Registered Design under Reference Nos. R21 = 3023446 SS2 = 3023445	
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 16 October 2018 12:37 PM E&OE

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84









