

## making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio


## 71CTPBL-B

Hartland CFX Polished Brass 1 gang 10A Triple Pole Rocker Black/Black




Item Image





## Dimensions



| Primary Range   | Hartland CFX   |   |
|---|--|---|
| Insert Type   | 1 gang 10A Triple Pole Rocker  |   |
| Plate Finish  | Hartland CFX Polished Brass  |   |
| Insert Colour   | Black/Black  |   |
| EAN13 Barcode   | 5017504241506  |   |
| Dimensions (Nominal)  | Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm   |   |
| Fixing Hole Centres   | Box Fixing = 60.3mm Grid Fixing = CFX Clips  |   |
| Minimum Wall Box Depth  | 25mm   |   |
| Switched Poles  | Triple   |   |
| Current Rating  | 10A  |   |
| Voltage   | 220/250V AC  |   |
| Maximum Load  | 10 Amp resistive   |   |
| Mains Frequency   | 50Hz   |   |
| IP Rating   | IP2XD  |   |
| Contact Gap Minimum   | 3mm  |   |
| Terminal Capacity 1   | 5 x 1mm2   |   |
| Terminal Capacity 2   | 4 x 1.5mm2   |   |
| Terminal Capacity 3   | 1 x 2.5mm2   |   |
| Terminal Capacity 4   | 1 x 4mm2 Multi-strand  |   |
| Terminal Capacity 5   | 1 x 6mm2   |   |
| Earth Terminal Capacity 1   | 5 x 1mm2   |   |
| Earth Terminal Capacity 2   | 4 x 1.5mm2   |   |
| Earth Terminal Capacity 3   | 3 x 2.5mm2   |   |
| Earth Terminal Capacity 4   | 1 x 4mm2 Multi-strand  |   |
| Earth Terminal Capacity 5   | 1 x 6mm2   |   |
| Product Class 1   | Must be earthed  |   |
| Ambient Operating Temperature   | -5° to +40°C   |   |
| Recommended Location  | Internal Use Only  |   |
| Maximum Installation Altitude   | 2000m  |   |
| Standard/Approval   | BS EN 60669-1  |   |
| Patents and Trademarks  | CFX is a Registered Trade Mark No 2398667 Hartland CFX is a Registered Design under Reference Nos. R21 = 3023446 SS2 = 3023445 |   |
| All products listed conform to current British or<br>European standard and the product information is<br>correct at the time of going to press. | All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.                          | It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior potice. |

Due to manufacturing processes we cannot guarantee an exact colour match and shadings of

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84







and dimensions without prior notice.



Correct as at 16 October 2018 12:37 PM E&OE



Illustrations and diagrams are reproduced within the limitations of reproduction and printing

process and are not binding.





Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio