SL

## making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio


## 71DPNCWH-W

Hartland Polished Brass 1 gang 20AX Double Pole Rocker and Neon and Cable Outlet White/White

## Item Image







## **Dimensions**



|   |   | 811.0  |
|---|---|--|
| Primary Range   | Hartland  |  |
| Insert Type   | 1 gang 20AX Double Pole Rocker + Neon + Cable Outlet  |  |
| Plate Finish  | Hartland Box Polished Brass   |  |
| Insert Colour   | White/White   |  |
| EAN13 Barcode   | 5017503210855   |  |
| Dimensions (Nominal)  | Single: Height = 88.0mm Width = 88.0mm Depth = 5.0mm  |  |
| Fixing Hole Centres   | Box Fixing = 60.3mm Grid Fixing = N/A   |  |
| Minimum Wall Box Depth  | 35mm  |  |
| Switched Poles  | Double  |  |
| Current Rating  | 20AX  |  |
| Voltage   | 220/250V AC   |  |
| Maximum Load  | 20 Amp inductive  |  |
| Mains Frequency   | 50Hz  |  |
| IP Rating   | IP2XD   |  |
| Contact Gap Minimum   | 3mm   |  |
| Terminal Capacity 1   | 3 x 2.5mm2  |  |
| Terminal Capacity 2   | 2 x 4mm2 Multi Strand   |  |
| Terminal Capacity 3   | 1 x 6mm2  |  |
| Earth Terminal Capacity 1   | 6 x 1mm2  |  |
| Earth Terminal Capacity 2   | 5 x 1.5mm2  |  |
| Earth Terminal Capacity 3   | 3 x 2.5mm2  |  |
| Earth Terminal Capacity 4   | 2 x 4mm2 Multi-strand   |  |
| Earth Terminal Capacity 5   | 1 x 6mm2  |  |
| Product Class 1   | Must be earthed   |  |
| Ambient Operating Temperature   | -5° to +40°C  |  |
| Recommended Location  | Internal Use Only   |  |
| Maximum Installation Altitude   | 2000m   |  |
| Cable Outlet Minimum/Maximum  | Min = 0.75mm <sup>2</sup> Max = 2.5mm <sup>2</sup>  |  |
| Standard/Approval   | BS EN 60669-1   |  |
| Patents and Trademarks  | Hartland is a Registered Trade Mark No. 2344778   |  |
| All products listed conform to current British or<br>European standard and the product information is<br>correct at the time of going to press. | All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.         | It is the policy of the company to improve products<br>as part of our development programme.<br>Therefore, we reserve the right to alter designs<br>and dimensions without prior notice. |
| Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.                      | Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes. | Correct as at 16 October 2018 12:54 PM E&OE  |

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84











