




## 722J12W

### Hartland Satin Brass 2 gang RJ12 Outlet - Unshielded White

| Item Image  | Wiring   | Dimensions  |
|---|--|---|
|    |  <p>RIGHT TO LEFT Wiring colour codes:<br/>No. STRIP/WIRE - SOLE WIRE<br/>1 NOT USED NOT USED<br/>2 GREEN / White BLUE<br/>3 ORANGE / Blue YELLOW<br/>4 BLUE / White GREEN<br/>5 WHITE / Blue RED<br/>6 WHITE / Orange BLACK<br/>7 NOT USED NOT USED<br/>8 NOT USED NOT USED<br/>MIDI WIRE colour shown in CAPITALS</p> |  <p><b>Hamilton</b><br/>HARTLAND<br/>2J12<br/>2 gang RJ12 Outlet Unshielded 6 wire</p>       |
| Primary Range   | Hartland   |   |
| Insert Type   | 2 gang RJ12 Outlet - Unshielded  |   |
| Plate Finish  | Hartland Box Satin Brass   |   |
| Insert Colour   | White  |   |
| EAN13 Barcode   | 5028690220732  |   |
| Dimensions (Nominal)  | Single: Height = 88.0mm Width = 88.0mm Depth = 5.0mm   |   |
| Fixing Hole Centres   | Box Fixing = 60.3mm Grid Fixing = N/A  |   |
| Minimum Wall Box Depth  | 35mm   |   |
| Switched Poles  | N/A  |   |
| IP Rating   | IP2XD  |   |
| Contact Gap Minimum   | N/A  |   |
| Earth Terminal Capacity 1   | 5 x 1mm <sup>2</sup>   |   |
| Earth Terminal Capacity 2   | 4 x 1.5mm <sup>2</sup>   |   |
| Earth Terminal Capacity 3   | 3 x 2.5mm <sup>2</sup>   |   |
| Earth Terminal Capacity 4   | 1 x 4mm <sup>2</sup> Multi-strand  |   |
| Earth Terminal Capacity 5   | 1 x 6mm <sup>2</sup>   |   |
| Product Class 1   | Must be earthed (ref BS7671 415.2.1)   |   |
| Ambient Operating Temperature   | -5° to +40°C   |   |
| Recommended Location  | Internal Use Only  |   |
| Maximum Installation Altitude   | 2000m  |   |
| EuroFix Additional Notes  | Can be used as either RJ11 (4 wires) or RJ12 (6 wires)   |   |
| Patents and Trademarks  | Hartland is a Registered Trade Mark No. 2344778  |   |
| All products listed conform to current British or European standard and the product information is correct at the time of going to press. | All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  | It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. |
| Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.                | Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.  | Correct as at 16 October 2018 12:54 PM E&OE   |

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ  
T: +44 (0)1747 860088 F: +44 (0)1179 710414  
E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB  
Registered in London No. 941624 VAT Registration No. 222 6607 84

