

making connections beautifully


Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

72R22SB-B


Hartland Satin Brass 2 gang 10AX 2 Way Rocker Satin Brass/Black

Item Image

Wiring



Dimensions



Insert Type			
Plate Finish	Primary Range	Hartland	
Insert Colour	Insert Type	2 gang 10AX 2 Way Rocker	
EAN13 Barcode 5017503222223 Dimensions (Nominal) Single: Height = 88.0mm Width = 88.0mm Depth = 5.0mm Weight 119 GR Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = N/A Minimum Wall Box Depth 25mm Switched Poles Single Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 1 x 2.5mm2 Terminal Capacity 4 1 x 4mm2 Multi-strand Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 3 1 x 6 mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6 mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6 mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6 mm2 Earth Terminal Capacity 6 1 x 6 mm2 Earth Terminal Capacity 7 5 x 1 mm2 Earth Terminal Capacity 6 1 x 6 mm2 Earth Terminal Capacity 7 5 x 1 mm2 Earth Terminal Capacity 6 1 x 6 mm2 Earth Terminal Capacity 6 1 x 6 mm2 Earth Terminal Capacity 7 1 x 6 mm2 Earth Terminal Capacity 6 1 x 6 mm2 Earth Terminal Capacity 7 1 x 6 mm2 Earth Terminal Capacity 8 1 x 6 mm2 Earth Terminal Capacity 9 1 x 6 mm2 Earth Terminal Capacity 6 1 x 6 mm2	Plate Finish	Hartland Box Satin Brass	
Dimensions (Nominal) Single: Height = 88.0mm Width = 88.0mm Depth = 5.0mm	Insert Colour	Satin Brass/Black	
Weight 119 GR Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = NVA Minimum Wall Box Depth 25mm Switched Poles Single Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 1 x 2.5mm2 Terminal Capacity 4 1 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 For Outce Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only	EAN13 Barcode	5017503222223	
Fixing Hole Centres	Dimensions (Nominal)	Single: Height = 88.0mm Width = 88.0mm Depth = 5.0mm	
Minimum Wall Box Depth 25mm Switched Poles Single Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 1 x 2.5mm2 Terminal Capacity 4 1 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only	Weight	119 GR	
Switched Poles Single Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 1 x 2.5mm2 Terminal Capacity 4 1 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Forduct Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only	Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = N/A	
Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 1 x 2.5mm2 Terminal Capacity 4 1 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Forduct Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only	Minimum Wall Box Depth	25mm	
Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 1 x 2.5mm2 Terminal Capacity 4 1 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only	Switched Poles	Single	
Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 1 x 2.5mm2 Terminal Capacity 4 1 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only	Current Rating	10AX	
Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 1 x 2.5mm2 Terminal Capacity 4 1 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only	Voltage	220/250V AC	
P Rating	Maximum Load	10 Amp inductive	
Contact Gap Minimum 3mm Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 1 x 2.5mm2 Terminal Capacity 4 1 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only	Mains Frequency	50Hz	
Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 1 x 2.5mm2 Terminal Capacity 4 1 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only	IP Rating	IP2XD	
Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 4 1 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 1 x 4mm2 Multi-strand Earth Terminal Capacity 3 1 x 6mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only	Contact Gap Minimum	3mm	
Terminal Capacity 3 Terminal Capacity 4 Terminal Capacity 5 1 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Forduct Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only	Terminal Capacity 1	5 x 1mm2	
Terminal Capacity 4 1 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only	Terminal Capacity 2	4 x 1.5mm2	
Terminal Capacity 5 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Earth Terminal Capacity 5 I x 6mm2 Product Class 1 Ambient Operating Temperature Recommended Location Internal Use Only	Terminal Capacity 3	1 x 2.5mm2	
Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only	Terminal Capacity 4	1 x 4mm2 Multi-strand	
Earth Terminal Capacity 2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Ambient Operating Temperature 75° to +40°C Recommended Location Recommended Location A x 1.5mm2 1 x 4mm2 Multi-strand 1 x 6mm2 Must be earthed Internal Use Only	Terminal Capacity 5	1 x 6mm2	
Earth Terminal Capacity 3 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only	Earth Terminal Capacity 1	5 x 1mm2	
Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only	Earth Terminal Capacity 2	4 x 1.5mm2	
Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only	Earth Terminal Capacity 3	3 x 2.5mm2	
Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only	Earth Terminal Capacity 4	1 x 4mm2 Multi-strand	
Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only	Earth Terminal Capacity 5	1 x 6mm2	
Recommended Location Internal Use Only	Product Class 1	Must be earthed	
	Ambient Operating Temperature	-5° to +40°C	
Maniform In the Heating Altitude	Recommended Location	Internal Use Only	
Maximum installation Altitude 2000m	Maximum Installation Altitude	2000m	
Standard/Approval BS EN 60669-1	Standard/Approval	BS EN 60669-1	
Patents and Trademarks Hartland is a Registered Trade Mark No. 2344778	Patents and Trademarks	Hartland is a Registered Trade Mark No. 2344778	
All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. BS EN ISO 9001 : 2015 Quality Management System. BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice.	European standard and the product information is		as part of our development programme. Therefore, we reserve the right to alter designs

Due to manufacturing processes we cannot guarantee an exact colour match and shadings of

of certain finishes.

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com

Illustrations and diagrams are reproduced within

the limitations of reproduction and printing process and are not binding.

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84











Correct as at 16 October 2018 12:55 PM







Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio