Dimensions

SL

Item Image

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

731X60

Hartland Bright Steel 1 gang 600W Resistive Leading Edge Push On-Off Rotary 2 Way Switching Dimmer Bright Steel

Wiring

Hamilton HARTLAND 1X60 ading Edge Push On-Off Rotary Way Switching Dimmer Primary Range Hartland Insert Type 1 gang 600W Resistive Leading Edge Push On-Off Rotary 2 Way Switching Dimmer Plate Finish Hartland Box Bright Steel Insert Colour **Bright Steel** EAN13 Barcode 5017503239450 Dimensions (Nominal) Single: Height = 88.0mm Width = 88.0mm Depth = 5.0mm Weight 182 GR Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = N/A Minimum Wall Box Depth 35mm Wattage 600W Switched Poles Single **Current Rating** 2.5 Amp Voltage 220/250V AC Maximum Load 600W resistive Min Load 100W Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum N/A Terminal Capacity 1 2 x 1mm2 Terminal Capacity 2 2 x 1.5mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Face plate must be earthed

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

F: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com

All products listed conform to current British or

European standard and the product information is

correct at the time of going to press.

Illustrations and diagrams are reproduced within

the limitations of reproduction and printing

Ambient Operating Temperature Recommended Location

Maximum Installation Altitude

Patents and Trademarks

Standard/Approval

Additional Notes

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84

Hartland is a Registered Trade Mark No. 2344778

All accessories are manufactured under an accredited

BS EN ISO 9001: 2015 Quality Management System.

Due to manufacturing processes we cannot

guarantee an exact colour match and shadings of

-5° to +40°C

2000m

Internal Use Only

BS EN 60669-2-1



Tungsten filament GU10 lamps must be branded with a fuse base. When using mains voltage halogen lamps- dimmers

should be de-rated by 25%. When dimming LED lamps de-rated by 75% - please contact our Technical for compatibility.







It is the policy of the company to improve products

as part of our development programme.

Therefore, we reserve the right to alter designs

and dimensions without prior notice.



Correct as at 16 October 2018 12:55 PM







Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio