



731XLEDITB100

Hartland Bright Steel 1g 100W LED 2 Way Push On/Off Rotary Dimmer Bright Steel

| Item Image | Wiring | Dimensions |
|---|--------|---|
|  | |  |

| | |
|-------------------------------|---|
| Primary Range | Hartland |
| Insert Type | 1 gang 100W LED Trailing/Leading Edge Push On/Off Rotary 2 Way Switching Dimmer |
| Plate Finish | Hartland Box Bright Steel |
| Insert Colour | Bright Steel |
| EAN13 Barcode | 5017504079260 |
| Dimensions (Nominal) | Single: Height = 88.0mm Width = 88.0mm Depth = 5.0mm |
| Weight | 112 GR |
| Fixing Hole Centres | Box Fixing = 60.3mm Grid Fixing = N/A |
| Minimum Wall Box Depth | 35mm |
| Wattage | 5-100W (10 LED Lamps MAX) |
| Switched Poles | Single |
| Current Rating | 0.4A |
| Voltage | 230V-240V |
| Maximum Load | 5-100W (10 LED Lamps MAX) |
| Mains Frequency | 50Hz |
| IP Rating | IP2XD |
| Terminal Capacity 1 | 2X1mm ² |
| Terminal Capacity 2 | 2X1.5mm ² |
| Earth Terminal Capacity 1 | 5X1mm ² |
| Earth Terminal Capacity 2 | 4X1.5mm ² |
| Earth Terminal Capacity 3 | 3X2.5mm ² |
| Earth Terminal Capacity 4 | 1X4mm ² Multi-Strand |
| Earth Terminal Capacity 5 | 1X6mm ² |
| Product Class 1 | Face plate must be earthed |
| Ambient Operating Temperature | -5°C to +40°C |
| Recommended Location | Internal Use Only |
| Maximum Installation Altitude | 2000m |
| Standard/Approval | BS EN 60669-2-1 |
| Additional Notes | Trailing Edge & Leading Edge Dimmer |
| Patents and Trademarks | Hartland is a Registered Trade Mark No. 2344778 |

| | | |
|---|---|---|
| All products listed conform to current British or European standard and the product information is correct at the time of going to press. | All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. | It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. |
| Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. | Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes. | Correct as at 16 October 2018 12:55 PM E&OE |