Hamilton

making connections beautifully

	Wiring Accessories • Circuit Protection • Si	mart Lighting Control & Multi-room Audio
<u>7345SS1BL-B</u>		
Hartland Bright Steel 45/	Double Pole Rocker + Neon + 13A Switche	d Socket Red+Black/Black
Item Image	Wiring	Dimensions
		Hemilton HARTLAND 45S1 Double Pole Red Rocker & Neon & 13A Switched Socket
Primary Range	Hartland	
Insert Type	45A Double Pole Red Rocker + Neon + 13A Switched Socker	at
Plate Finish	Hartland Box Bright Steel	
Insert Colour	Red+Black/Black	
EAN13 Barcode	5017503231706	
Dimensions (Nominal)	Double: Height = 88.0mm Width = 144.5mm Depth = 5.0mm	
Fixing Hole Centres	Box Fixing = 120.6mm Grid Fixing = N/A	
Minimum Wall Box Depth	35mm	
Switched Poles	Double	
Current Rating	Switch 45 Amp Socket 13 Amp	
Voltage	220/250V AC	
Maximum Load	Switch 45 Amp Socket 13	
Mains Frequency	50Hz	
IP Rating	IP2XD	
Contact Gap Minimum	3mm	
Terminal Capacity 1	3 x 6mm2	
Terminal Capacity 2	2 x 10mm2	
Terminal Capacity 3	1 x 16mm2	
Earth Terminal Capacity 1	3 x 6mm2	
	2 x 10mm2	
Earth Terminal Capacity 2 Earth Terminal Capacity 3	1 x 16mm2	
Product Class 1	Must be earthed	
	-5° to +40°C	
Ambient Operating Temperature Recommended Location	Internal Use Only	
Maximum Installation Altitude	2000m	
Standard/Approval	BS 4177	
Patents and Trademarks	Hartland is a Registered Trade Mark No. 2344778	
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 16 October 2018 12:55 PI E&O
R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville R T: +44 (0)1747 860088 F: +44 (0)1179 710414 Registered (Listed in STrimble Broduct Selector

SL