SL

Item Image

making connections beautifully

Dimensions

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

7345SS1WH-W

Hartland Bright Steel 45A Double Pole Rocker + Neon + 13A Switched Socket Red+White/White

Wiring

Hamilton HARTLAND 45SS1 ole Red Rocker & Neon & Primary Range Hartland Insert Type 45A Double Pole Red Rocker + Neon + 13A Switched Socket Plate Finish Hartland Box Bright Steel Insert Colour Red+White/White EAN13 Barcode 5017503230709 Dimensions (Nominal) Double: Height = 88.0mm Width = 144.5mm Depth = 5.0mm Fixing Hole Centres Box Fixing = 120.6mm Grid Fixing = N/A Minimum Wall Box Depth 35mm Switched Poles Double **Current Rating** Switch 45 Amp Socket 13 Amp Voltage 220/250V AC Switch 45 Amp Socket 13 Maximum Load Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 3 x 6mm2 Terminal Capacity 2 2 x 10mm2 **Terminal Capacity 3** 1 x 16mm2 Earth Terminal Capacity 1 3 x 6mm2 Earth Terminal Capacity 2 2 x 10mm2

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com

All products listed conform to current British or

European standard and the product information is

correct at the time of going to press

Illustrations and diagrams are reproduced within

the limitations of reproduction and printing

process and are not binding.

Earth Terminal Capacity 3

Recommended Location

Maximum Installation Altitude

Patents and Trademarks

Ambient Operating Temperature

Product Class 1

Standard/Approval

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84

Hartland is a Registered Trade Mark No. 2344778

All accessories are manufactured under an accredited

BS EN ISO 9001: 2015 Quality Management System.

Due to manufacturing processes we cannot

guarantee an exact colour match and shadings of

of certain finishes.

1 x 16mm2

-5° to +40°C Internal Use Only

2000m

BS 4177

Must be earthed









It is the policy of the company to improve products

as part of our development programme.

Therefore, we reserve the right to alter designs

and dimensions without prior notice.



Correct as at 16 October 2018 12:55 PM

