## Hamilton

## making connections beautifully

SL

	C	
	Wiring Accessories • Circuit Protection • Sr 73MED1B	nart Lighting Control & Multi-room Audio
Lientien di Euro Ein Dright O		Lineswitch and On alreat Dia als
Hartland EuroFix Bright S	teel Media Plate EURO4 aperture + 2 X13A	Unswitched Socket Black
Item Image	Wiring	Dimensions
		Hemilton HARTLAND MED1 EURO4 Aperture with 2 x 13A Unswitched Socket
Primary Range	EuroFix	
Insert Type	EuroFix Media Plate EURO4 aperture + 2 X13A Unswitched Socket	
Plate Finish	Hartland EuroFix Bright Steel	
Insert Colour	Black	
	5028690231318	
EAN13 Barcode		
Dimensions (Nominal)	150x150: Height = 146.0mm Width = 146.0mm Depth = 5.0mm	
Fixing Hole Centres	Box Fixing = 120.6mm x 2 Grid Fixing = N/A	
Minimum Wall Box Depth	As Per Inserts None	
Switched Poles		
Current Rating	13 Amp 220/250V AC	
Voltage		
Maximum Load	13 Amp (socket)	
Mains Frequency	50Hz IP2XD	
IP Rating	None	
Contact Gap Minimum	None 3 x 2.5mm2	
Terminal Capacity 1		
Terminal Capacity 2	3 x 4mm2	
Terminal Capacity 3	2 x 6mm2 Multi-Strand	
Terminal Capacity 4	1 x 10mm2	
Earth Terminal Capacity 1	3 x 2.5mm2	
Earth Terminal Capacity 2	3 x 4mm2	
Earth Terminal Capacity 3	2 x 6mm2 Multi-strand	
Earth Terminal Capacity 4	1 x 10mm2 Must be cathed (cooket)	
Product Class 1	Must be earthed (socket)	
Ambient Operating Temperature	-5° to +40°C	
Recommended Location	Internal Use Only	
Maximum Installation Altitude	2000m	
Standard/Approval	BS 1363-2 (socket)	
Additional Notes	SPECIAL NOTE : When mains voltage & telecom/data/TV are mixed on the same plate a suitable phase barrier MUST be used in the wall box to shield the mains. Shuttered:Yes	
Patents and Trademarks	EuroFix is a Registered Trade Mark No. 2560270	
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 15 October 2018 09:01 AM E&OE
R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Ro T: +44 (0)1747 860088 F: +44 (0)1179 710414 Registered Of E: info@hamilton-litestat.com www.hamilton-litestat.com Registered in	ad, Brislington, Bristol, BS4 5NZ fice 1 Rushmills, Bedford Road, Northampton NN4 7YB London No. 941624 VAT Registration No. 222 6607 84	Listed in Strimble product Selector CSL 100 CK1128