




73SHSB

Hartland Bright Steel Shaver Dual Voltage Unswitched Socket (Vertically Mounted) Black

Item Image	Wiring	Dimensions
		
Primary Range	Hartland	
Insert Type	Shaver Dual Voltage Unswitched Socket (Vertically Mounted)	
Plate Finish	Hartland Box Vertical Bright Steel	
Insert Colour	Black	
EAN13 Barcode	5017503231034	
Dimensions (Nominal)	Double: Height = 144.5mm Width = 88.0mm Depth = 5.0mm	
Weight	766 GR	
Fixing Hole Centres	Box Fixing = 120.6mm Grid Fixing = N/A	
Minimum Wall Box Depth	47mm	
Switched Poles	None	
Current Rating	20VA	
Voltage	220/250V AC	
Maximum Load	200/250V input; 115/230V 20VA output	
Mains Frequency	50Hz	
IP Rating	IP2XD	
Contact Gap Minimum	None	
Terminal Capacity 1	5 x 1mm ²	
Terminal Capacity 2	4 x 1.5mm ²	
Terminal Capacity 3	3 x 2.5mm ²	
Terminal Capacity 4	2 x 4mm ² Multi-strand	
Terminal Capacity 5	1 x 6mm ²	
Earth Terminal Capacity 1	9 x 1mm ²	
Earth Terminal Capacity 2	6 x 1.5mm ²	
Earth Terminal Capacity 3	4 x 2.5mm ²	
Earth Terminal Capacity 4	2 x 4mm ² Multi-strand	
Earth Terminal Capacity 5	1 x 6mm ²	
Product Class 1	Must be earthed	
Ambient Operating Temperature	-5° to +40°C	
Recommended Location	Internal Use Only	
Maximum Installation Altitude	2000m	
Standard/Approval	BS EN 61558-2-5 - BS 4573	
Additional Notes	Must be mounted vertically. Shuttered :Yes. Box Depth 47mm	

73SHSB

Hartland Bright Steel Shaver Dual Voltage Unswitched Socket (Vertically Mounted) Black

Patents and Trademarks			Hartland is a Registered Trade Mark No. 2344778		
All products listed conform to current British or European standard and the product information is correct at the time of going to press.		All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.		It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.	
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.		Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes.		Correct as at 16 October 2018 12:56 PM E&OE	

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414

E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB

Registered in London No. 941624 VAT Registration No. 222 6607 84



CERT. No. FM11238