SL

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio


73SPNWH-W

Hartland Bright Steel 1 gang 13A Double Pole Fused Spur and Neon White/White


Item Image



Wiring



Dimensions



| | Live | |
|---|---|--|
| | | 1 |
| Primary Range | Hartland | |
| Insert Type | 1 gang 13A Double Pole Fused Spur + Neon | |
| Plate Finish | Hartland Box Bright Steel | |
| Insert Colour | White/White | |
| EAN13 Barcode | 5017503230921 | |
| Dimensions (Nominal) | Single: Height = 88.0mm Width = 88.0mm Depth = 5.0mm | |
| Fixing Hole Centres | Box Fixing = 60.3mm Grid Fixing = N/A | |
| Minimum Wall Box Depth | 35mm | |
| Switched Poles | Double | |
| Current Rating | 13 Amp | |
| Voltage | 220/250V AC | |
| Maximum Load | 13 Amp | |
| Mains Frequency | 50Hz | |
| IP Rating | IP2XD | |
| Contact Gap Minimum | 3mm | |
| Terminal Capacity 1 | 3 x 2.5mm2 | |
| Terminal Capacity 2 | 2 x 4mm2 Multi Strand | |
| Terminal Capacity 3 | 1 x 6mm2 | |
| Earth Terminal Capacity 1 | 6 x 1mm2 | |
| Earth Terminal Capacity 2 | 5 x 1.5mm2 | |
| Earth Terminal Capacity 3 | 3 x 2.5mm2 | |
| Earth Terminal Capacity 4 | 2 x 4mm2 Multi-strand | |
| Earth Terminal Capacity 5 | 1 x 6mm2 | |
| Product Class 1 | Must be earthed | |
| Ambient Operating Temperature | -5° to +40°C | |
| Recommended Location | Internal Use Only | |
| Maximum Installation Altitude | 2000m | |
| Standard/Approval | BS 1363-4 | |
| Patents and Trademarks | Hartland is a Registered Trade Mark No. 2344778 | |
| All products listed conform to current British or European standard and the product information is correct at the time of going to press. | All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. | It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. |
| Illustrations and diagrams are reproduced within | Due to manufacturing processes we cannot | Correct as at 16 October 2018 12:56 PM |

guarantee an exact colour match and shadings of

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414
E: info@hamilton-litestat.com www.hamilton-litestat.com

the limitations of reproduction and printing

process and are not binding.

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84













E&OE