Hamilton

making connections beautifully

	Wiring Accessories • Circuit Protection • Sn	nart Lighting Control & Multi-room Audio	
741GP Hartland Grid-IT Satin Steel 1 gang Grid Fix Aperture Plate with Grid			
			Item Image
•		Hemilton HARTLAND 1GP Single plate with 1 x GRID-IT cutout	
Primary Range	GRID-IT		
Insert Type	1 Gang Grid Fix Aperture Plate with Grid		
Plate Finish	Hartland GRID-IT Satin Steel		
Insert Colour	No Insert Colour		
EAN13 Barcode	5051164749019		
Dimensions (Nominal)	Single: Height = 88.0mm Width = 88.0mm Depth = 5.0mm		
Weight	99 GR		
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = 49.2mm		
Minimum Wall Box Depth	As Per Insert		
Switched Poles	N/A		
IP Rating	N/A		
Contact Gap Minimum	N/A		
Earth Terminal Capacity 1	11mm2		
Product Class 1	Face plate must be earthed		
Recommended Location	Internal Use Only		
Maximum Installation Altitude	2000m		
Additional Notes	See GRID-IT for a full range of inserts. Plates must be Earthed via the Earth Tag.		
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.	
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 15 October 2018 09:51 AN E&Ot	
R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Ro T: +44 (0)1747 860088 F: +44 (0)1179 710414 Registered Off E: info@hamilton-litestat.com www.hamilton-litestat.com Registered in I	ad, Brislington, Bristol, BS4 5NZ ice 1 Rushmills, Bedford Road, Northampton NN4 7YB ondon No. 941624 VAT Registration No. 222 6607 84	Listed in MTimble, product selector	



SL