Hamilto

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio 7<u>41X40</u> Hartland Satin Steel 1x400W Resistive Leading Edge Push On-Off Rotary 2 Way Switching Dimmer Satin Steel Item Image Wiring Dimensions Hamilton HARTLAND 1X40 eading Edge Push On-Off Rotary 88.0 101: 60.3 88.0 ė Primary Range Hartland Insert Type 1 gang 400W Resistive Leading Edge Push On-Off Rotary 2 Way Switching Dimmer Plate Finish Hartland Box Satin Steel Insert Colour Satin Steel EAN13 Barcode 5017503249411 Dimensions (Nominal) Single: Height = 88.0mm Width = 88.0mm Depth = 5.0mm Weight 125 GR **Fixing Hole Centres** Box Fixing = 60.3mm Grid Fixing = N/A Minimum Wall Box Depth 35mm Wattage 400W Switched Poles Single Current Rating 1.66 Amp Voltage 220/250V AC Maximum Load 400W resistive Min Load Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum N/A **Terminal Capacity 1** 2 x 1mm2 Terminal Capacity 2 2 x 1.5mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Face plate must be earthed -5° to +40°C Ambient Operating Temperature Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-2-1 Tungsten filament GU10 lamps must be branded with a fuse base. When using mains voltagehalogen lamps- dimmers Additional Notes should be de-rated by 25%. When dimming LED lamps de-rated by 75% - please contact our Technical for compatibility. Patents and Trademarks Hartland is a Registered Trade Mark No. 2344778 All products listed conform to current British or All accessories are manufactured under an accredited It is the policy of the company to improve products European standard and the product information is BS EN ISO 9001 : 2015 Quality Management System. as part of our development programme. Therefore, we reserve the right to alter designs correct at the time of going to press and dimensions without prior notice. Illustrations and diagrams are reproduced within Due to manufacturing processes we cannot Correct as at 16 October 2018 12:56 PM the limitations of reproduction and printing guarantee an exact colour match and shadings of E&OE process and are not binding. of certain finishes R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ _isted in STrimb **Seca**

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YE Registered in London No. 941624 VAT Registration No. 222 6607 84

SL

Hamilton

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio