SL

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio 743XTSSS-B Hartland Satin Steel 3 gang Multi-Way Touch Slave Controller Satin Steel/Black Item Image Wiring **Dimensions** Hamilton Multi- Way Wiring using Slave module(s) Primary Range Hartland Insert Type 3 gang Multi-Way Touch Slave Controller Plate Finish Hartland GRID-IT Satin Steel Insert Colour Satin Steel/Black EAN13 Barcode 5028690241447 Dimensions (Nominal) Double: Height = 88.0mm Width = 144.5mm Depth = 5.0mm Fixing Hole Centres Box Fixing = 120.6mm Grid Fixing = 106.5mm Minimum Wall Box Depth 35mm Wattage The same as Touch Master or Ceiling Dimmer Switched Poles N/A Current Rating The same as Touch Master or Ceiling Dimmer 220/250V AC Voltage Maximum Load The same as Touch Master 50Hz Mains Frequency IP Rating IP2XD Contact Gap Minimum N/A Terminal Capacity 1 2 x 1mm2 Terminal Capacity 2 2 x 1.5mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Face plate must be earthed -5° to +40°C **Ambient Operating Temperature** Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-2-1 Tungsten filament GU10 lamps must be branded with a fuse base. When using mains voltagehalogen lamps- dimmers Additional Notes When using mains voltage halogen load transformer - maximum rating is 210VA. To only be should be de-rated by 25%. used with Touch Master Dimmers Patents and Trademarks Hartland is a Registered Trade Mark No. 2344778 All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. All products listed conform to current British or It is the policy of the company to improve products European standard and the product information is as part of our development programme Therefore, we reserve the right to alter designs and dimensions without prior notice. correct at the time of going to press. Correct as at 16 October 2018 12:56 PM Illustrations and diagrams are reproduced within Due to manufacturing processes we cannot guarantee an exact colour match and shadings of the limitations of reproduction and printing process and are not binding. of certain finishes

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)179 710414 Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB

E: info@hamilton-litestat.com www.hamilton-litestat.com Registered in London No. 941624 VAT Registration No. 222 6607 84















Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio