## Hamilton

## making connections beautifully

The set of th	Dimensions
Wiring	Dimensions
EVIC Gasket Conductor Terminal Screw Correct position of conductor, screening braid and cable solated TV (female) (DAB Compatible) Satin Steel Effect 38 ht = 86.0mm Width = 86.0mm Depth = 5.0	HARLAND CFX DTP Non-solated TV (female)
conductor Terminal Screw Correct position of conductor, screening braid and cable solated TV (female) (DAB Compatible) Satin Steel Effect 38 ht = 86.0mm Width = 86.0mm Depth = 5.0	HARTLAND CFX DTVF Non-Isolated TV (female)
solated TV (female) (DAB Compatible) Satin Steel Effect 38 nt = 86.0mm Width = 86.0mm Depth = 5.0	Dmm
Satin Steel Effect 38 nt = 86.0mm Width = 86.0mm Depth = 5.0	Dmm
38 nt = 86.0mm Width = 86.0mm Depth = 5.0	Dmm
nt = 86.0mm Width = 86.0mm Depth = 5.0	Dmm
nt = 86.0mm Width = 86.0mm Depth = 5.0	Dmm
	Dmm
0.3mm Grid Fixing = CFX Clips	
<u></u>	
lti-strand	
ed (ref BS7671 415.2.1)	
·	
 Jnly	
2 169-2 Female Socket) Usually used for FM	/ (DAB) outlet
	· ·
stered Trade Mark No 2398667 is a Registered Design under Reference No	DS.
	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.
	Correct as at 16 October 2018 12:38 P E&C
	Dnly C 169-2 Female Socket) Usually used for FM 10 MHz istered Trade Mark No 2398667 is a Registered Design under Reference No 46 SS2 = 3023445 ssories are manufactured under an accredited SO 9001 : 2015 Quality Management System. ue to manufacturing processes we cannot antee an exact colour match and shadings of

SL