

## making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

	74CR23SS-W			
Herning   Primary Range	Hartland CFX Satin Steel Effect 3 gang 10AX 2 Way Rocker Satin Steel/White			
Primary Range Nariand CFX Insert Type 3 gang TOAX 2 Way Rocker Insert Type 3 gang TOAX 2 Way Rocker Plate Finish Hartland CFX Satin Seed Effect Insert Colour EANT 3 Baccode Satin Seed Effect EART 3	Item Image	Wiring	Dimensions	
Primary Range Harsland CFX Insert Type 3 g.agang 10A.X.2 Way Rocker Harsland CFX Salin Steel Effect Insert Colour Salin Steel White EAN13 Bircode 5917-504-827230 Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth Switchad Poles Single  Zomm Minimum Wall Box Depth 50.0mm Grid Fixing = CFX Clips Minimum Wall Box Depth 50.0mm Grid Fixing = CFX Clips Minimum Wall Box Depth 50.0mm Grid Fixing = CFX Clips Minimum Wall Box Depth 50.0mm Grid Fixing = CFX Clips Minimum Load Fixing = CFX Clips Minimum Load Fixing = CFX Clips 50.0mm Grid Fixing =		No. of the late	HARTLAND CFX R23 2 Way Rocker	
Insert Type 3 gang 10AX 2 Way Rocker Plate Finish Hartland CFX Satin Steel Effect Insert Colour Satin Steel Effect Insert Colour Satin Steel Effect EAN13 Barcode 5017504267230 Dimensions (Nominal) Single: Height = 86.0mm Wildh = 86.0mm Depth = 5.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 25mm Switched Poles Single Current Rating 10AX Voltage 200250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5 x 1mm2 Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 4 1 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 6 1 x 6mm2 Earth Terminal Capacity 6 1 x 6mm2 Earth Terminal Capacity 6 1 x 6mm2 Earth Terminal Capacity 7 1 x 6mm2 Earth Terminal Capacity 8 1 x 6mm2 Earth Terminal Capacity 9 1 x 6mm2 Earth Terminal Capacity 9 1 x 6mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 6 1 x 6mm2 Earth Terminal Capacity 7 x 6mm2 Earth Terminal Capacity 8 1 x 6mm2 Earth Terminal Capacity 8 1 x 6mm2 Earth Terminal Capacity 6 1 x 6mm2 Earth Termin		Alternative 2 way swelching Core in Long Out Intermediate swelching Intermediate swelching	86.0	
Plate Finish Hartland CFX Satin Steel Effect Insert Colour Satin Steel White EAN13 Barcode 50175042672730 Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm Brixing Hole Centres Bax Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 25mm Switched Poles Single Current Rating 10AX Votage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz Patting P2XD Contact Gap Minimum 3mm Frequency 1P2XD Contact Gap Minimum 3mm Freminal Capacity 1 5 x tmm2 Ferminal Capacity 1 5 x tmm2 Ferminal Capacity 3 1 x 2.5mm2 Ferminal Capacity 3 1 x 2.5mm2 Ferminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 6 1 x 6mm2 Multi-strand Earth Terminal Capacity 6 1 x 6mm2 Multi-strand Earth Terminal Capacity 6 1 x 6mm2 Multi-strand Earth Terminal Capacity 7 5 x 1 x 6mm2 Earth Terminal Capacity 8 5 x 1 x 6mm2 Earth Terminal Capacity 8 5 x 1 x 6mm2 Multi-strand Earth Terminal Capacity 9 5 x 1 x 6mm2 Multi-strand Earth Terminal Capacity 6 1 x 6mm2 Multi-strand Earth Terminal Capacity 6 1 x 6mm2 Multi-strand Earth Terminal Capacity 7 5 x 6mm2 Multi-strand Earth Terminal Capacity 6 1 x 6mm2 Multi-strand Earth Terminal Capacity 6 1 x 6mm2 Multi-strand Earth Terminal Capacity 6 1 x 6mm2 Multi-strand Earth Terminal Capacity 7 5 x 6mm2 Multi-strand Earth Terminal Capacity 6 1 x 6mm2 Multi-strand Earth Terminal Capacity 6 x				
Insert Colour Satin SteelWhite EAN13 Barcode 5017504257230 Dimensions (Nominal) Single: Height = 86.0mm Width = 96.0mm Depth = 5.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 25mm Switched Poles Single Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5x t mm2 Terminal Capacity 1 5x t mm2 Terminal Capacity 1 5x t mm2 Terminal Capacity 3 1x 2.5mm2 Terminal Capacity 4 1x 4mm2 Multi-strand Terminal Capacity 1 5x t mm2 Earth Terminal Capacity 3 1x 2.5mm2 Earth Terminal Capacity 4 1x 4mm2 Multi-strand Earth Terminal Capacity 5 1x 6mm2 Earth Terminal Capacity 4 1x 4mm2 Multi-strand Earth Terminal Capacity 5 1x 6mm2 Earth Terminal Capacity 6 1x 6mm2 Earth Terminal Capacity 6 1x 6mm2 Earth Terminal Capacity 6 1x 6mm2 Earth Terminal Capacity 7 1x 6mm2 Earth Terminal Capacity 8 1x 6mm2 Earth Terminal Capacity 8 1x 6mm2 Earth Terminal Capacity 9 1x 6mm2 Earth Terminal Capacity 1 1x 6mm2 Earth Terminal Capacity 9 1x 6mm2 Earth Terminal Capacit		,		
EAN13 Barcode 5017504267230  Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm Fixing Hole Centres  Box Fixing Hole Centres  Minimum Wall Box Depth 25mm  Switched Poles Single  Current Rating 10AX  Voltage 220250V AC  Maximum Load 10 Amp inductive  Mains Frequency 50Hz  IP Rating PEXD  Contact Gap Minimum 5mm  Terminal Capacity 1 5x 1mm2  Terminal Capacity 2 4x 1.5mm2  Terminal Capacity 3 1x 2.5mm2  Terminal Capacity 3 1x 2.5mm2  Terminal Capacity 4 1x 4mm2 Multi-strand  Terminal Capacity 1 5x 1mm2  Earth Terminal Capacity 3 3x 2.5mm2  Earth Terminal Capacity 3 3x 2.5mm2  Earth Terminal Capacity 3 1x 4mm2 Multi-strand  Earth Terminal Capacity 5 1x 6mm2  Earth Terminal Capacity 6 1x 4mm2 Multi-strand  Earth Terminal Capacity 6 1x 4mm2 Multi-strand  Earth Terminal Capacity 6 1x 6mm2  Earth Terminal Capacity 7 1x 6mm2  Earth Terminal Capacity 8 1x 6mm2  Earth Terminal Capacity 6 1x 6mm2  Earth Terminal Capacity 6 1x 6mm2  Earth Terminal Capacity 7 1x 6mm2  Earth Terminal Capacity 6 1x 6mm2  Earth Terminal Capacity 7 1x 6mm2  Earth Terminal Capacity 6 1x 6mm2  Earth Terminal Capacity 7 1x 6mm2  Earth Terminal Capacity 6 1x 6mm2  Earth Terminal Capacity 7 1x 6mm2  Earth Terminal Capacity 6 1x 6mm2  Earth Terminal Capacity 7 1x 6mm2  Earth Terminal Capacity 6 1x 6mm2  Earth Terminal Capacity 7 1x 6mm2  Eart				
Dimensions (Nominal)  Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm  Fixing Hole Centres  Box Fixing = 60.3mm Grid Fixing = CFX Clips  Minimum Wall Box Depth  Switched Poles  Current Rating  10AX  Voltage  220/250V AC  Maximum Load  10 Amp inductive  Mains Frequency  10 Amp inductive  Mai	Insert Colour			
Fixing Hole Centres  Box Fixing = 60.3mm Grid Fixing = CFX Clips  Minimum Wall Box Depth  25mm  Single  Current Rating  10AX  Voltage  220/250V AC  Maximum Load  10 Amp inductive  Mains Frequency  50Hz  IP Rating  1P2XD  Contact Gap Minimum  Terminal Capacity 1  5 x 1mm2  Terminal Capacity 2  4 x 1.5mm2  Terminal Capacity 3  1 x 2.5mm2  Terminal Capacity 3  1 x 4mm2 Multi-strand  Terminal Capacity 5  1 x 6mm2  Earth Terminal Capacity 1  5 x 1mm2  Earth Terminal Capacity 1  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 3  1 x 4mm2 Multi-strand  Earth Terminal Capacity 5  Earth Terminal Capacity 1  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 3  1 x 6mm2  Earth Terminal Capacity 5  Earth Terminal Capacity 6  Earth Terminal Capacity 6  Earth Terminal Capacity 7  Earth Terminal Capacity 8  Earth Terminal Capacity 9	EAN13 Barcode			
Minimum Wall Box Depth 25mm  Switched Poles Single  Current Rating 10AX  Voltage 220/250V AC  Maximum Load 10 Amp inductive  Mains Frequency 50Hz  IP Rating IP2XD  Contact Gap Minimum 3mm  Terminal Capacity 1 5x 1mm2  Terminal Capacity 1 5x 1mm2  Terminal Capacity 2 4x 1.5mm2  Terminal Capacity 3 1x 2.5mm2  Terminal Capacity 4 1 x 4mm2 Multi-strand  Terminal Capacity 5 1 x 6mm2  Earth Terminal Capacity 5 1 x 6mm2  Earth Terminal Capacity 1 5x 1mm2  Earth Terminal Capacity 1 5x 1mm2  Earth Terminal Capacity 3 1x 2.5mm2  Earth Terminal Capacity 5 1 x 6mm2  Earth Terminal Capacity 5 5x 1mm2  Earth Terminal Capacity 5 5x 1mm2  Earth Terminal Capacity 5 5x 1mm2  Earth Terminal Capacity 6 5x 1mm2  Earth Terminal Capacity 7 5x 1mm2  Earth Terminal Capacity 8 1x 4mm2 Multi-strand  Earth Terminal Capacity 9 5x 1x 6mm2  Earth Terminal Capacity 9 1x 4mm2 Multi-strand  Earth Terminal Capacity 9 5x 1x 6mm2  Earth Terminal Capacity 9 1x 4mm2 Multi-strand  Earth Terminal Capacity 9 1x 6mm2  Earth	, , ,	1		
Switched Poles Single Current Rating 10AX Voltage 220/250 V AC Maximum Load 10 Amp Inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5 x 1mm2 Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 1 x 2.5mm2 Terminal Capacity 4 1 x 4mm2 Multi-strand Terminal Capacity 4 1 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 3 1 x 2.5mm2 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 6 1 x 6mm2 Earth Terminal Capacity 6 1 x 6mm2 Earth Terminal Capacity 7 4 x 4 x 4 x 4 x 4 x 4 x 4 x 4 x 4 x 4				
Current Rating 10AX Voltage 220/250V AC 10 Amp inductive 220/250V AC 10 Amp inductive 10 Am	·			
Voltage   220/250 V AC   Maximum Load   10 Amp inductive				
Maximum Load  Mains Frequency  SoHz  IP Rating  IP2XD  Contact Gap Minimum  Smm  Terminal Capacity 1  Sx 1mm2  Terminal Capacity 2  4 x 1.5mm2  Terminal Capacity 3  1 x 2.5mm2  Terminal Capacity 4  1 x 4mm2 Multi-strand  Terminal Capacity 5  1 x 6mm2  Earth Terminal Capacity 1  Sx 1mm2  Earth Terminal Capacity 5  1 x 6mm2  Earth Terminal Capacity 1  Sx 1mm2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 3  Earth Terminal Capacity 3  Xx 2.5mm2  Earth Terminal Capacity 3  Xx 2.5mm2  Earth Terminal Capacity 4  1 x 4mm2 Multi-strand  Earth Terminal Capacity 5  Ix 6mm2  Product Class 1  Must be earthed  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Maximum Installation Altitude  Standard/Approval  Extended Amk No 2398667  Patents and Trademarks  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter designs and dimensions without prior notice. EXC	Current Rating			
Mains Frequency 50Hz  IP Rating IP2XD  Contact Gap Minimum 3mm  Terminal Capacity 1 5 x 1mm2  Terminal Capacity 2 4 x 1.5mm2  Terminal Capacity 3 1 x 2.5mm2  Terminal Capacity 4 1 x 4mm2 Multi-strand  Terminal Capacity 5 1 x 6mm2  Earth Terminal Capacity 1 5 x 1mm2  Earth Terminal Capacity 1 5 x 1mm2  Earth Terminal Capacity 2 4 x 1.5mm2  Earth Terminal Capacity 3 3 x 2.5mm2  Earth Terminal Capacity 3 1 x 6mm2  Earth Terminal Capacity 4 1 x 6mm2  Forduct Class 1 1 x 6mm2  Product Class 1 Must be earthed  Ambient Operating Temperature 5° to +40°C  Recommended Location Internal Use Only  Maximum Installation Altitude 2000m  Standard/Approval BS EN 60669-1  CFX is a Registered Trade Mark No 2398667  Fatents and Trademarks His the billionation is correct at the time of going to press.  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  Illustrations and diagrams are reproduced within the limitations of reproduction and printing grantees are exact color match and shadings of Correct as at 16 October 2018 12:38 Pc guarantee an exact color match and shadings of EXEC	Voltage			
IP Rating	Maximum Load	10 Amp inductive		
Contact Gap Minimum  Ferminal Capacity 1  Forminal Capacity 2  4 x 1.5mm2  Terminal Capacity 3  1 x 2.5mm2  Terminal Capacity 4  1 x 4mm2 Multi-strand  Terminal Capacity 5  1 x 6mm2  Earth Terminal Capacity 1  Earth Terminal Capacity 1  Earth Terminal Capacity 2  4 x 1.5mm2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 4  1 x 4mm2 Multi-strand  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 4  1 x 4mm2 Multi-strand  Earth Terminal Capacity 5  1 x 6mm2  Must be earthed  Ambient Operating Temperature  Recommended Location  Internal Use Only  Maximum Installation Altitude  Standard/Approval  BS EN 60669-1  CCFX is a Registered Trade Mark No 2398667  Hartland CFX is a Registered Design under Reference Nos.  R21 = 3023446 SS2 = 3023445  All products listed conform to current British or European standard and the product information is correct at the time of ging to press.  All products listed conform to current British or European standard and the product information is correct at the time of ging to press.  All products listed conform to current British or European standard and the product information is correct at the time of ging to press.  All products listed conform to current British or European standard and the product information is correct at the time of ging to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to after designs and dimensions without prior notice.  Due to manufacturing processes we cannot Correct as at 16 October 2018 12:38 PC (appearance an exact colour match and shadings of Correct as at 16 October 2018 12:38 PC (appearance an exact colour match and shadings of Correct as at 16 October 2018 12:38 PC (appearance an exact colour match and shadings of Correct as at 16 October 2018 12:38 PC (appearance an exact colour match and shadings of Correct as 2 16 October 2018 12:38 PC (appearance an exact colour match and shadings of Corr				
Terminal Capacity 2	IP Rating	IP2XD		
Terminal Capacity 2  Terminal Capacity 3  1 x 2.5mm2  Terminal Capacity 4  1 x 4mm2 Multi-strand  Terminal Capacity 5  1 x 6mm2  Earth Terminal Capacity 1  5 x 1mm2  Earth Terminal Capacity 2  4 x 1.5mm2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 4  1 x 4mm2 Multi-strand  Earth Terminal Capacity 5  1 x 6mm2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 4  1 x 4mm2 Multi-strand  Earth Terminal Capacity 5  1 x 6mm2  Earth Terminal Capacity 5  1 x 6mm2  Earth Terminal Capacity 4  2 x 1.5mm2  Earth Terminal Capacity 5  1 x 6mm2  Earth Terminal Capacity 6  Extremal Capacity 6  1 x 6mm2  Earth Terminal Capacity 7  Earth Terminal Capacity 8  Earth Terminal Capacity 8  2 x 1.5mm2  Earth Terminal Capacity 9  2 x 1.5mm2  Earth Terminal Capacity 9  2 x 2.5mm2  Earth Terminal Capacity 9  2 x 1.5mm2  Earth Terminal Capacity 9  Earth Termi	•	3mm		
Terminal Capacity 3  Terminal Capacity 4  1 x 4mm2 Multi-strand  Terminal Capacity 5  1 x 6mm2  Earth Terminal Capacity 1  Earth Terminal Capacity 2  Earth Terminal Capacity 2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 3  Earth Terminal Capacity 3  Earth Terminal Capacity 3  Earth Terminal Capacity 4  Earth Terminal Capacity 4  Earth Terminal Capacity 5  1 x 6mm2  Product Class 1  Must be earthed  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m  Standard/Approval  BS EN 60669-1  CFX is a Registered Trade Mark No 2398667  Hartland CFX is a Registered Design under Reference Nos.  R21 = 3023446  SS2 = 3023445  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  BS EN ISO 9001 : 2015 Quality Management System.  Due to manufacturing processes we cannot and dimensions without prior notice.  Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 16 October 2018 12:38 PEX	Terminal Capacity 1	5 x 1mm2		
Terminal Capacity 4  1 x 4mm2 Multi-strand  Terminal Capacity 5  1 x 6mm2  Earth Terminal Capacity 1  5 x 1mm2  Earth Terminal Capacity 2  4 x 1.5mm2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 4  1 x 4mm2 Multi-strand  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 4  1 x 4mm2 Multi-strand  Earth Terminal Capacity 5  1 x 6mm2  Froduct Class 1  Must be earthed  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m  Standard/Approval  BS EN 60669-1  CFX is a Registered Trade Mark No 2398667  Hartland CFX is a Registered Design under Reference Nos. R21 = 3023446 SS2 = 3023445  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  BILUstrations and diagrams are reproduced within the limitations of reproduction and printing guarantee an exact colour match and shadings of Correct as at 16 October 2018 12:38 PEX	Terminal Capacity 2	4 x 1.5mm2		
Terminal Capacity 5  Earth Terminal Capacity 1  Earth Terminal Capacity 2  Earth Terminal Capacity 2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 4  1 x 4mm2 Multi-strand  Earth Terminal Capacity 5  1 x 6mm2  Product Class 1  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  Standard/Approval  BS EN 60669-1  CFX is a Registered Trade Mark No 2398667  Hartland CFX is a Registered Design under Reference Nos.  R21 = 3023446 SS2 = 3023445  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter designs and dimensions without prior notice.  Due to manufacturing processes we cannot the limitations of reproduction and printing guarantee an exact colour match and shadings of Correct as at 16 October 2018 12:38 P E&C.	Terminal Capacity 3	1 x 2.5mm2		
Earth Terminal Capacity 1 5 x 1mm2  Earth Terminal Capacity 2 4 x 1.5mm2  Earth Terminal Capacity 3 3 x 2.5mm2  Earth Terminal Capacity 4 1 x 4mm2 Multi-strand  Earth Terminal Capacity 5 1 x 6mm2  Product Class 1 Must be earthed  Ambient Operating Temperature -5° to +40°C  Recommended Location Internal Use Only  Maximum Installation Altitude 2000m  Standard/Approval BS EN 60669-1  CFX is a Registered Trade Mark No 2398667  Hartland CFX is a Registered Design under Reference Nos. R21 = 3023446 SS2 = 30234445  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All products listed conform to product information is correct at the time of going to press.  BLIILUSTRAING OF REPORT OF THE PROPORTION OF THE PROPORTI	Terminal Capacity 4	1 x 4mm2 Multi-strand		
Earth Terminal Capacity 2  Earth Terminal Capacity 3  Earth Terminal Capacity 4  Earth Terminal Capacity 4  Earth Terminal Capacity 5  Product Class 1  Ambient Operating Temperature  Recommended Location  Internal Use Only  Maximum Installation Altitude  Standard/Approval  Estandard/Approval  BS EN 60669-1  CFX is a Registered Trade Mark No 2398667  Hartland CFX is a Registered Design under Reference Nos.  R21 = 3023446 SS2 = 3023445  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  Blustrations and diagrams are reproducted within the limitations of reproduction and printing guarantee an exact colour match and shadings of  Each Terminal Capacity 3  3 x 2.5mm2  1 x 4mm2 Multi-strand  1 x 4mm2 Multi-strand  1 x 4mm2 Multi-strand  1 x 4mm2 Multi-strand  2 x 4mm2 Multi-strand  3 x 2.5mm2  Each Terminal Capacity 3  2 x 4mm2 Multi-strand  3 x 2.5mm2  4 x 1.5mm2  Each Terminal Capacity 3  2 x 4mm2 Multi-strand  3 x 2.5mm2  4 x 1.5mm2  5 x 6 x 4mm2  CFX is a Registered Trade Mark No 2398667  Hartland CFX is a Registered Design under Reference Nos.  R21 = 3023446 SS2 = 3023445  R21 = 3023446 SS2 = 3023445  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter designs and dimensions without prior notice.  Correct as at 16 October 2018 12:38 P guarantee an exact colour match and shadings of		-		
Earth Terminal Capacity 3  Earth Terminal Capacity 4  Earth Terminal Capacity 4  Earth Terminal Capacity 5  1 x 4mm2 Multi-strand  Earth Terminal Capacity 5  1 x 6mm2  Product Class 1  Ambient Operating Temperature  Recommended Location  Internal Use Only  Maximum Installation Altitude  Standard/Approval  BS EN 60669-1  CFX is a Registered Trade Mark No 2398667  Hartland CFX is a Registered Design under Reference Nos.  R21 = 3023446 SS2 = 3023445  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  Bllustrations and diagrams are reproduced within the limitations of reproduction and printing  Due to manufacturing processes we cannot guarantee an exact colour match and shadings of  Correct as at 16 October 2018 12:38 P EXC	Earth Terminal Capacity 1	5 x 1mm2		
Earth Terminal Capacity 4  Earth Terminal Capacity 5  Product Class 1  Ambient Operating Temperature  Recommended Location  Must be earthed  Ambient Operating Temperature  Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m  Standard/Approval  BS EN 60669-1  CFX is a Registered Trade Mark No 2398667  Hartland CFX is a Registered Design under Reference Nos.  R21 = 3023446 SS2 = 3023445  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Bllustrations and diagrams are reproduced within the limitations of reproduction and printing guarantee an exact colour match and shadings of Correct as at 16 October 2018 12:38 PEX	Earth Terminal Capacity 2	4 x 1.5mm2		
Earth Terminal Capacity 5  Product Class 1  Must be earthed  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m  Standard/Approval  BS EN 60669-1  CFX is a Registered Trade Mark No 2398667  Hartland CFX is a Registered Design under Reference Nos. R21 = 3023446 SS2 = 3023445  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  BS EN ISO 9001 : 2015 Quality Management System.  Due to manufacturing processes we cannot the limitations of reproduction and printing  Due to manufacturing processes we cannot guarantee an exact colour match and shadings of  Correct as at 16 October 2018 12:38 P EXC	Earth Terminal Capacity 3	3 x 2.5mm2		
Product Class 1  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m  Standard/Approval  BS EN 60669-1  CFX is a Registered Trade Mark No 2398667  Hartland CFX is a Registered Design under Reference Nos. R21 = 3023446 SS2 = 3023445  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  Illustrations and diagrams are reproduced within the limitations of reproduction and printing  Due to manufacturing processes we cannot guarantee an exact colour match and shadings of  Correct as at 16 October 2018 12:38 P E&C	Earth Terminal Capacity 4	1 x 4mm2 Multi-strand		
Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m  Standard/Approval  BS EN 60669-1  CFX is a Registered Trade Mark No 2398667  Hartland CFX is a Registered Design under Reference Nos. R21 = 3023446 SS2 =3023445  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All products listed conform to current British or BS EN ISO 9001 : 2015 Quality Management System.  Illustrations and diagrams are reproduced within the limitations of reproduction and printing  Due to manufacturing processes we cannot guarantee an exact colour match and shadings of  Correct as at 16 October 2018 12:38 P E&C  EXCENTIBLE OF THE PROPERTY OF	Earth Terminal Capacity 5	1 x 6mm2		
Recommended Location Internal Use Only  Maximum Installation Altitude 2000m  Standard/Approval BS EN 60669-1  Patents and Trademarks CFX is a Registered Trade Mark No 2398667 Hartland CFX is a Registered Design under Reference Nos. R21 = 3023446 SS2 = 3023445  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All products listed conform to current British or BS EN ISO 9001 : 2015 Quality Management System.  Illustrations and diagrams are reproduced within the limitations of reproduction and printing guarantee an exact colour match and shadings of Correct as at 16 October 2018 12:38 P E&C	Product Class 1	Must be earthed		
Maximum Installation Altitude  2000m  Standard/Approval  BS EN 6069-1  CFX is a Registered Trade Mark No 2398667  Hartland CFX is a Registered Design under Reference Nos.  R21 = 3023446 SS2 = 3023445  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Illustrations and diagrams are reproduced within the limitations of reproduction and printing  Due to manufacturing processes we cannot guarantee an exact colour match and shadings of  Correct as at 16 October 2018 12:38 P E&C  EXCENTIBLE OF TRANSPORT	Ambient Operating Temperature	-5° to +40°C		
Standard/Approval  BS EN 60669-1  CFX is a Registered Trade Mark No 2398667  Hartland CFX is a Registered Design under Reference Nos. R21 = 3023446 SS2 = 3023445  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Illustrations and diagrams are reproduced within the limitations of reproduction and printing guarantee an exact colour match and shadings of  BS EN 60669-1  CFX is a Registered Trade Mark No 2398667  Hartland CFX is a Registered Design under Reference Nos. R21 = 3023446  BI It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.  Correct as at 16 October 2018 12:38 P	Recommended Location	Internal Use Only		
Patents and Trademarks  CFX is a Registered Trade Mark No 2398667 Hartland CFX is a Registered Design under Reference Nos. R21 = 3023446 SS2 = 3023445  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Illustrations and diagrams are reproduced within the limitations of reproduction and printing guarantee an exact colour match and shadings of  CFX is a Registered Trade Mark No 2398667 Hartland CFX is a Registered Design under Reference Nos. R21 = 3023446 SS2 = 3023445  It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.  Correct as at 16 October 2018 12:38 P	Maximum Installation Altitude			
Patents and Trademarks  Hartland CFX is a Registered Design under Reference Nos. R21 = 3023446 SS2 = 3023445  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Illustrations and diagrams are reproduced within the limitations of reproduction and printing  Due to manufacturing processes we cannot guarantee an exact colour match and shadings of  Tit is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.  Correct as at 16 October 2018 12:38 P E&C	Standard/Approval			
European standard and the product information is correct at the time of going to press.  BS EN ISO 9001 : 2015 Quality Management System.  BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter designs and dimensions without prior notice.  Illustrations and diagrams are reproduced within the limitations of reproduction and printing guarantee an exact colour match and shadings of E&C	Patents and Trademarks	Hartland CFX is a Registered Design under Reference Nos.		
the limitations of reproduction and printing guarantee an exact colour match and shadings of E&C	European standard and the product information is		as part of our development programme. Therefore, we reserve the right to alter designs	
Pluming A Out Heidel Consider During Control A S During Day of District on District Day of District on District During Control	the limitations of reproduction and printing	guarantee an exact colour match and shadings of	Correct as at 16 October 2018 12:38 PM E&OE	

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84















Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio