




## 74CR242SS-W

### Hartland CFX Satin Steel Effect 4 gang 20AX 2 Way Rocker Satin Steel/White

| Item Image  | Wiring   | Dimensions   |
|---|--|--|
|    |   |  <p style="text-align: center;"><b>Hamilton®</b><br/>HARTLAND CFX<br/>R242<br/>2 Way Rocker</p> |
| Primary Range   | Hartland CFX   |  |
| Insert Type   | 4 gang 20AX 2 Way Rocker   |  |
| Plate Finish  | Hartland CFX Satin Steel Effect  |  |
| Insert Colour   | Satin Steel/White  |  |
| EAN13 Barcode   | 5017504267391  |  |
| Dimensions (Nominal)  | Double: Height = 86.0mm Width = 145.0mm Depth = 5.0mm  |  |
| Fixing Hole Centres   | Box Fixing = 120.6mm Grid Fixing = CFX Clips   |  |
| Minimum Wall Box Depth  | 25mm   |  |
| Switched Poles  | Single   |  |
| Current Rating  | 20AX   |  |
| Voltage   | 220/250V AC  |  |
| Maximum Load  | 20 Amp inductive   |  |
| Mains Frequency   | 50Hz   |  |
| IP Rating   | IP2XD  |  |
| Contact Gap Minimum   | 3mm  |  |
| Terminal Capacity 1   | 5 x 1mm <sup>2</sup>   |  |
| Terminal Capacity 2   | 4 x 1.5mm <sup>2</sup>   |  |
| Terminal Capacity 3   | 2 x 2.5mm <sup>2</sup>   |  |
| Terminal Capacity 4   | 2 x 4mm <sup>2</sup> Multi-strand  |  |
| Terminal Capacity 5   | 1 x 6mm <sup>2</sup>   |  |
| Earth Terminal Capacity 1   | 6 x 1mm <sup>2</sup>   |  |
| Earth Terminal Capacity 2   | 5 x 1.5mm <sup>2</sup>   |  |
| Earth Terminal Capacity 3   | 3 x 2.5mm <sup>2</sup>   |  |
| Earth Terminal Capacity 4   | 2 x 4mm <sup>2</sup> Multi-strand  |  |
| Earth Terminal Capacity 5   | 1 x 6mm <sup>2</sup>   |  |
| Product Class 1   | Must be earthed  |  |
| Ambient Operating Temperature   | -5° to +40°C   |  |
| Recommended Location  | Internal Use Only  |  |
| Maximum Installation Altitude   | 2000m  |  |
| Standard/Approval   | BS EN 60669-1  |  |
| Patents and Trademarks  | CFX is a Registered Trade Mark No 2398667<br>Hartland CFX is a Registered Design under Reference Nos.<br>R21 = 3023446 SS2 = 3023445 |  |
| All products listed conform to current British or European standard and the product information is correct at the time of going to press. | All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.                                | It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.    |
| Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.                | Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes.                           | Correct as at 16 October 2018 12:38 PM E&OE  |

# Hamilton®

making connections beautifully

SL

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio