Hamilton

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio		
74SS1GP		
Hartland Grid-IT Satin Steel 1 gang 13A Switched Socket Grid Fix Aperture Plate		
Haritanu Ghu-H Satih Steel T gang TSA Switched Socket Ghu Fix Aperture Flate		
Item Image	Wiring	Dimensions
		Hemilton HARTLAND SSIGP Single plate with 1 x GRID-IT SS1 cutout
Primary Range	GRID-IT	
Insert Type	1 gang 13A Switched Socket Grid Fix Aperture Plate	
Plate Finish	Hartland GRID-IT Satin Steel	
Insert Colour	No Insert Colour	
EAN13 Barcode	5051164749217	
Dimensions (Nominal)	Single: Height = 88.0mm Width = 88.0mm Depth = 5.0mm	
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = 49.2mm	
Minimum Wall Box Depth	As Per Insert	
Switched Poles	N/A	
IP Rating	N/A	
Contact Gap Minimum	N/A	
Product Class 1	Face plate must be earthed	
Recommended Location	Internal Use Only	
Maximum Installation Altitude	2000m	
Additional Notes	See GRID-IT for a full range of inserts. Plates must be Earthed via the Earth Tag.	
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 15 October 2018 09:51 AM E&OE
R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Ro T: +44 (0)1747 860088 F: +44 (0)1179 710414 Registered Of E: info@hamilton-litestat.com www.hamilton-litestat.com Registered in	ad, Brislington, Bristol, BS4 5NZ fice 1 Rushmills, Bedford Road, Northampton NN4 7YB London No. 941624 VAT Registration No. 222 6607 84	Listed in Trimble product selector DSSPlus DSSPlus

SL