Hamilton

making connections beautifully

| | Wiring Accessories • Circuit Protection • Sr | nart Lighting Control & Multi-room Audio |
|--|---|--|
| | 761XTSSC-W | |
| | | |
| Hartland Satin Chror | ne 1 gang Multi-Way Touch Slave Controlle | r Satin Chrome/White |
| Item Image | Wiring | Dimensions |
| | | Hamilton |
| | Multi- Way Wiring using Slave module(s) | HATTLAND HATTLAND 1XTS Multi-WayTouch Slave Controller |
| | | |
| Primary Range | Hartland | |
| Insert Type | 1 gang Multi-Way Touch Slave Controller | |
| Plate Finish | Hartland GRID-IT Satin Chrome | |
| Insert Colour | Satin Chrome/White | |
| EAN13 Barcode | 5028690260424 | |
| Dimensions (Nominal) | Single: Height = 88.0mm Width = 88.0mm Depth = 5.0mm | |
| Weight | 142 GR | |
| Fixing Hole Centres | Box Fixing = 60.3mm Grid Fixing = 49.2mm | |
| Minimum Wall Box Depth | 35mm | |
| Wattage | The same as Touch Master or Ceiling Dimmer | |
| Switched Poles | N/A | |
| Current Rating | The same as Touch Master or Ceiling Dimmer | |
| Voltage | 220/250V AC | |
| Maximum Load | The same as Touch Master | |
| Mains Frequency | 50Hz | |
| IP Rating | IP2XD | |
| Contact Gap Minimum | N/A | |
| Terminal Capacity 1 | 2 x 1mm2 | |
| Terminal Capacity 2 | 2 x 1.5mm2 | |
| Earth Terminal Capacity 1 | 5 x 1mm2 | |
| Earth Terminal Capacity 2 | 4 x 1.5mm2 | |
| Earth Terminal Capacity 3 | 3 x 2.5mm2 | |
| Earth Terminal Capacity 4 | 1 x 4mm2 Multi-strand | |
| Earth Terminal Capacity 5 | 1 x 6mm2 | |
| Product Class 1 | Face plate must be earthed | |
| Ambient Operating Temperature | -5° to +40°C | |
| Recommended Location | Internal Use Only | |
| Maximum Installation Altitude | 2000m | |
| Standard/Approval | BS EN 60669-2-1 | |
| Additional Notes | Tungsten filament GU10 lamps must be branded with a fuse base. When using mains voltagehalogen lamps- dimmers should be de-rated by 25%. When using mains voltage halogen load transformer - maximum rating is 210VA. To only be used with Touch Master Dimmers | |
| Patents and Trademarks | Hartland is a Registered Trade Mark No. 2344778 | |
| All products listed conform to current British or European standard and the product information is correct at the time of going to press. | All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. | It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. |
| Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. | Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes. | Correct as at 16 October 2018 12:57 PM E&OE |
| R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Ro T: +44 (0)1747 860088 F: +44 (0)1179 710414 Registered Off E: info@hamilton-litestat.com www.hamilton-litestat.com Registered in I | dad, Brislington, Bristol, BS4 5NZ ice 1 Rushmills, Bedford Road, Northampton NN4 7YB ondon No. 941624 VAT Registration No. 222 6607 84 | Listed in Strimble, product selector DissPlus Distribution |

761XTSSC-W - Hartland Satin Chrome 1 gang Multi-Way Touch Slave Controller Satin Chrome/White

SL

Hamilton

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio