Hamilton

making connections beautifully

SL

| | Wiring Accessories • Circuit Protection • Sr | nart Lighting Control & Multi-room Audio |
|--|--|---|
| | 76MED2B | |
| Hartland EuroFix Satin Ch | rome Media Plate EURO4 aperture + 4 X13 | A Unswitched Socket Black |
| Item Image | Wiring | Dimensions |
| | | |
| | Neutral Liev | EURO4 Aperture with 4 x 13A Unswitched Socket |
| | | |
| Primary Range | EuroFix | |
| Insert Type | Media Plate EURO4 aperture + 4 X13A Unswitched Socket | |
| Plate Finish | Hartland EuroFix Satin Chrome | |
| Insert Colour | Black | |
| EAN13 Barcode | 5028690261322 | |
| Dimensions (Nominal) | 150x210: Height = 210mm Width = 146.0mm Depth = 5.0mm | |
| Fixing Hole Centres | Box Fixing = 120.6 mm x 3 Grid Fixing = N/A | |
| Minimum Wall Box Depth | As Per Inserts | |
| Switched Poles | None | |
| Current Rating | 13 Amp | |
| Voltage | 220/250V AC | |
| Maximum Load | 13 Amp (socket) | |
| Mains Frequency | 50Hz | |
| IP Rating | IP2XD | |
| Contact Gap Minimum | None | |
| Terminal Capacity 1 | 3 x 2.5mm2 | |
| Terminal Capacity 2 | 3 x 4mm2 | |
| Terminal Capacity 3 | 2 x 6mm2 Multi-Strand | |
| Terminal Capacity 4 | 1 x 10mm2 | |
| Earth Terminal Capacity 1 | 3 x 2.5mm2 | |
| Earth Terminal Capacity 2 | 3 x 4mm2 | |
| Earth Terminal Capacity 3 | 2 x 6mm2 Multi-strand | |
| Earth Terminal Capacity 4 | 1 x 10mm2 | |
| Product Class 1 | Must be earthed (socket) | |
| Ambient Operating Temperature | -5° to +40°C | |
| Recommended Location | Internal Use Only | |
| Maximum Installation Altitude | 2000m | |
| Standard/Approval | BS 1363-2 (socket) | |
| Additional Notes | SPECIAL NOTE : When mains voltage & telecom/data/TV are mixed on the same plate a suitable phase barrier MUST be used in the wall box to shield the mains. Shuttered:Yes | |
| Patents and Trademarks | EuroFix is a Registered Trade Mark No. 2560270 | |
| All products listed conform to current British or European standard and the product information is correct at the time of going to press. | All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. | It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. |
| Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. | Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes. | Correct as at 15 October 2018 09:01 AM E&OE |
| R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Rc T: +44 (0)1747 860088 F: +44 (0)1179 710414 Registered O E: info@hamilton-litestat.com www.hamilton-litestat.com Registered in | Ad, Brislington, Bristol, BS4 5NZ fice 1 Rushmills, Bedford Road, Northampton NN4 7YB London No. 941624 VAT Registration No. 222 6607 84 | Listed in Strinble DISCRIME Selector DISCRIME CREATER |