SL

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

771X60

Hartland Bright Chrome 1 gang 600W Resistive Leading Edge Push On-Off Rotary 2 Way Switching Dimmer Bright Chrome Item Image Wiring **Dimensions** Hamilton HARTLAND 1X60 ading Edge Push On-Off Rotary Way Switching Dimmer Primary Range Hartland Insert Type 1 gang 600W Resistive Leading Edge Push On-Off Rotary 2 Way Switching Dimmer Plate Finish Hartland Box Bright Chrome Insert Colour **Bright Chrome** EAN13 Barcode 5017503279456 Dimensions (Nominal) Single: Height = 88.0mm Width = 88.0mm Depth = 5.0mm Weight 183 GR Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = N/A Minimum Wall Box Depth 35mm Wattage 600W Switched Poles Single **Current Rating** 2.5 Amp Voltage 220/250V AC Maximum Load 600W resistive Min Load 100W Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum N/A Terminal Capacity 1 2 x 1mm2 Terminal Capacity 2 2 x 1.5mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Face plate must be earthed -5° to +40°C **Ambient Operating Temperature** Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-2-1 Tungsten filament GU10 lamps must be branded with a fuse base. When using mains voltage halogen lamps- dimmers Additional Notes should be de-rated by 25%. When dimming LED lamps de-rated by 75% - please contact our Technical for compatibility. Patents and Trademarks Hartland is a Registered Trade Mark No. 2344778 All products listed conform to current British or All accessories are manufactured under an accredited It is the policy of the company to improve products European standard and the product information is BS EN ISO 9001: 2015 Quality Management System. as part of our development programme.

Therefore, we reserve the right to alter designs correct at the time of going to press. and dimensions without prior notice. Illustrations and diagrams are reproduced within Due to manufacturing processes we cannot Correct as at 16 October 2018 12:58 PM the limitations of reproduction and printing guarantee an exact colour match and shadings of

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YE Registered in London No. 941624 VAT Registration No. 222 6607 84















Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio