SL

## making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

**773XLEDITB100** 

Hartland Bright Chrome 3g 100W LED 2 Way Push On/Off Rotary Dimmer Bright Chrome Item Image Wiring **Dimensions** Hamilton LEDITB100 2 Way Dimme Primary Range Hartland Insert Type 3 gang 100W LED Trailing/Leading Edge Push On/Off Rotary 2 Way Switching Dimmer Plate Finish Hartland Box Bright Chrome Insert Colour **Bright Chrome** EAN13 Barcode 5017504079505 Dimensions (Nominal) Double: Height = 88.0mm Width = 144.5mm Depth = 5.0mm Fixing Hole Centres Box Fixing = 120.6mm Grid Fixing = N/A Minimum Wall Box Depth 35mm Wattage 5-70W Per Gang Switched Poles Single Current Rating 0.3A Per Gang Voltage 230V-240V Maximum Load 5-70W Per Gang Mains Frequency 50Hz IP Rating IP2XD Terminal Capacity 1 2X1mm<sup>2</sup> Terminal Capacity 2 2X1.5mm<sup>2</sup> Earth Terminal Capacity 1 5X1mm<sup>2</sup> Earth Terminal Capacity 2 4X1.5mm<sup>2</sup> Earth Terminal Capacity 3 3X2.5mm<sup>2</sup> Earth Terminal Capacity 4 1X4mm<sup>2</sup> Multi-Strand Earth Terminal Capacity 5 1X6mm² Product Class 1 Face plate muct be earthed -5°C to +40°C **Ambient Operating Temperature** Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-2-1 Additional Notes Trailing Edge & Leading Edge Dimmer Patents and Trademarks Hartland is a Registered Trade Mark No. 2344778 All products listed conform to current British or All accessories are manufactured under an accredited It is the policy of the company to improve products European standard and the product information is BS EN ISO 9001: 2015 Quality Management System. as part of our development programme Therefore, we reserve the right to alter designs correct at the time of going to press. and dimensions without prior notice. Illustrations and diagrams are reproduced within Due to manufacturing processes we cannot Correct as at 16 October 2018 12:58 PM the limitations of reproduction and printing guarantee an exact colour match and shadings of E&OE process and are not binding.

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84 hamilton-litestat.com www.hamilton-litestat.com











