Hamilton

making connections beautifully

SL

	Wiring Accessories • Circuit Protection • Sn	nart Lighting Control & Multi-room Audio					
773XTMBC-W							
Hartland Bright Chrome 3x250W/210VA Resistive/Inductive Trailing Edge Touch Master Multi-Way Dimmers Bright Chrome/White							
Item Image	Wiring	Dimensions					
	Multi- Way Wiring using Slave module(s)	Hamilton HARTLAND 3XTM Resistive/Inductive Trailing Edge Touch Master Multi-Way Dimmer					
	Live Lit s Constrained Live Lit s Constrained Lit s						
Primary Range	Hartland						
Insert Type	3 gang 250W/210VA Resistive/Inductive Trailing Edge Touch Master Multi-Way Dimmer						
Plate Finish	Hartland GRID-IT Bright Chrome						
Insert Colour	Bright Chrome/White						
EAN13 Barcode	5028690270409						
Dimensions (Nominal)	Double: Height = 88.0mm Width = 144.5mm Depth = 5.0mm						
Fixing Hole Centres	Box Fixing = 120.6mm Grid Fixing = 106.5mm						
Minimum Wall Box Depth	35mm						
Wattage	250W Resistive 210VA Inductive						
Switched Poles	N/A						
Current Rating	1.1 Amps per gang						
Voltage	220/250V AC						
Maximum Load	250W Resistive per gang 210VA Inductive Min Load 25W/25VA						
Mains Frequency	50Hz						
IP Rating	IP2XD						
Contact Gap Minimum	N/A						
Terminal Capacity 1	2 x 1mm2						
Terminal Capacity 2	2 x 1.5mm2						
Earth Terminal Capacity 1	5 x 1mm2						
Earth Terminal Capacity 2	4 x 1.5mm2						
Earth Terminal Capacity 3	3 x 2.5mm2						
Earth Terminal Capacity 4	1 x 4mm2 Multi-strand						
Earth Terminal Capacity 5	1 x 6mm2						
Product Class 1	Face plate must be earthed						
Ambient Operating Temperature	-5° to +40°C						
Recommended Location	Internal Use Only						
Maximum Installation Altitude	2000m						
Standard/Approval	BS EN 60669-2-1						
Additional Notes	TRAILING EDGE TECHNOLOGY DIMMERS. Are suitable for control of both resistive and inductive loads. When used for dimming low voltage electronic halogen transformers it must be noted that the dimmer controls the primary side of the transformer. Tungsten filament GU10 lamps must be branded with a fuse base. When using mains voltagehalogen lamps-dimmers should be de-rated by 25%. When dimming LED lamps de-rated by 75% - please contact our Technical for compatibility. When using mains voltage halogen load transformer - maximum rating is 210VA. NOTE: For multi-way switching a push to make retractive switch should be installed in the other positions. (Note:standard two way switches will not work with this product)						

Hamilton

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

773XTMBC-W

Hartland Bright Chrome 3x250W/210VA Resistive/Inductive Trailing Edge Touch Master Multi-Way Dimmers Bright Chrome/White

Hartland is a Registered Trade Mark No. 2344778

Patents and Trademarks	Hartland is a Registered Trade Mark No. 2344778					
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an acc BS EN ISO 9001 : 2015 Quality Management S					
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannu guarantee an exact colour match and shading of certain finishes.		Correct as at 16 October 2018 12:58 PM E&OE			
R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Ro T: +44 (0)1747 860088 F: +44 (0)1179 710414 Registered Off E: info@hamilton-litestat.com www.hamilton-litestat.com Registered in I	ad, Brislington, Bristol, BS4 5NZ ice 1 Rushmills, Bedford Road, Northampton NN4 7YB ondon No. 941624 VAT Registration No. 222 6607 84		-itish British of Institute Institute Design	Listed in Trimble	Product selector	

SL