Hamilton

making connections beautifully

	Wining Accessories • Circuit Protection • Sr	nart Lighting Control & Multi-room Audio	
Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio			
<u>774XTSBC-B</u>			
Hartland Bright Chrome 4 gang Multi-Way Touch Slave Controller Bright Chrome/Black			
Item Image	Wiring	Dimensions	
	Multi- Way Wiring using Slave module(s)	Hemilton HARTLAND 4XTS Multi-WayTouch Slave Controller	
	MATTER MODULE IS USED PER CIRCUIT.		
Primary Range	Hartland		
Insert Type	4 gang Multi-Way Touch Slave Controller		
Plate Finish	Hartland GRID-IT Bright Chrome		
Insert Colour	Bright Chrome/Black		
EAN13 Barcode	5028690271451		
Dimensions (Nominal)	Double: Height = 88.0mm Width = 144.5mm Depth = 5.0mm		
Fixing Hole Centres	Box Fixing = 120.6mm Grid Fixing = 106.5mm		
Minimum Wall Box Depth	35mm		
	The same as Touch Master or Ceiling Dimmer		
Wattage Switched Poles			
	The same as Touch Master or Ceiling Dimmer		
Current Rating			
Voltage	220/250V AC		
Maximum Load	The same as Touch Master		
Mains Frequency	50Hz		
IP Rating	IP2XD		
Contact Gap Minimum			
Terminal Capacity 1	2 x 1mm2		
Terminal Capacity 2	2 x 1.5mm2		
Earth Terminal Capacity 1	5 x 1mm2		
Earth Terminal Capacity 2	4 x 1.5mm2		
Earth Terminal Capacity 3	3 x 2.5mm2		
Earth Terminal Capacity 4	1 x 4mm2 Multi-strand		
Earth Terminal Capacity 5	1 x 6mm2		
Product Class 1	Face plate must be earthed		
Ambient Operating Temperature	-5° to +40°C		
Recommended Location	Internal Use Only		
Maximum Installation Altitude	2000m		
Standard/Approval	BS EN 60669-2-1		
Additional Notes	Tungsten filament GU10 lamps must be branded with a fuse base. When using mains voltagehalogen lamps- dimmers should be de-rated by 25%. When using mains voltage halogen load transformer - maximum rating is 210VA. To only be used with Touch Master Dimmers		
Patents and Trademarks	Hartland is a Registered Trade Mark No. 2344778		
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.	
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 16 October 2018 12:58 PM E&OE	
R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ T: +44 (0)1747 860088 F: +44 (0)179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com Registered office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 660784			

SL

Hamilton

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio