




77CJ12W

Hartland CFX Bright Chrome 1 gang RJ12 Outlet - Unshielded White

Item Image	Wiring	Dimensions																											
	 <table border="1" data-bbox="808 646 966 730"> <thead> <tr> <th>RIGHT RJ11 / 12 Wiring colour codes:</th> <th>SOFT WIRES</th> <th>SOFT WIRES</th> </tr> </thead> <tbody> <tr> <td>1. NOT USED</td> <td>NOT USED</td> <td>NOT USED</td> </tr> <tr> <td>2. GREEN / White</td> <td>BLUE</td> <td></td> </tr> <tr> <td>3. ORANGE / White</td> <td>YELLOW</td> <td></td> </tr> <tr> <td>4. WHITE / Blue</td> <td>GREEN</td> <td></td> </tr> <tr> <td>5. BLUE / White</td> <td>RED</td> <td></td> </tr> <tr> <td>6. WHITE / Orange</td> <td>BLACK</td> <td></td> </tr> <tr> <td>7. NOT USED</td> <td>NOT USED</td> <td></td> </tr> <tr> <td>8. NOT USED</td> <td>NOT USED</td> <td></td> </tr> </tbody> </table>	RIGHT RJ11 / 12 Wiring colour codes:	SOFT WIRES	SOFT WIRES	1. NOT USED	NOT USED	NOT USED	2. GREEN / White	BLUE		3. ORANGE / White	YELLOW		4. WHITE / Blue	GREEN		5. BLUE / White	RED		6. WHITE / Orange	BLACK		7. NOT USED	NOT USED		8. NOT USED	NOT USED		 <p>Hamilton® HARTLAND CFX J12 1 gang RJ12 Outlet Unshielded 6 wire</p>
RIGHT RJ11 / 12 Wiring colour codes:	SOFT WIRES	SOFT WIRES																											
1. NOT USED	NOT USED	NOT USED																											
2. GREEN / White	BLUE																												
3. ORANGE / White	YELLOW																												
4. WHITE / Blue	GREEN																												
5. BLUE / White	RED																												
6. WHITE / Orange	BLACK																												
7. NOT USED	NOT USED																												
8. NOT USED	NOT USED																												

Primary Range	Hartland CFX
Insert Type	1 gang RJ12 Outlet - Unshielded
Plate Finish	Hartland CFX Bright Chrome
Insert Colour	White
EAN13 Barcode	5017504270551
Dimensions (Nominal)	Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips
Minimum Wall Box Depth	35mm
Switched Poles	N/A
IP Rating	IP2XD
Contact Gap Minimum	N/A
Earth Terminal Capacity 1	5 x 1mm ²
Earth Terminal Capacity 2	4 x 1.5mm ²
Earth Terminal Capacity 3	3 x 2.5mm ²
Earth Terminal Capacity 4	1 x 4mm ² Multi-strand
Earth Terminal Capacity 5	1 x 6mm ²
Product Class 1	Must be earthed (ref BS7671 415.2.1)
Ambient Operating Temperature	-5° to +40°C
Recommended Location	Internal Use Only
Maximum Installation Altitude	2000m
EuroFix Additional Notes	Can be used as either RJ11 (4 wires) or RJ12 (6 wires)
Patents and Trademarks	CFX is a Registered Trade Mark No 2398667 Hartland CFX is a Registered Design under Reference Nos. R21 = 3023446 SS2 = 3023445

<p>All products listed conform to current British or European standard and the product information is correct at the time of going to press.</p>	<p>All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.</p>	<p>It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.</p>
<p>Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.</p>	<p>Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes.</p>	<p>Correct as at 16 October 2018 12:39 PM E&OE</p>

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ
 T: +44 (0)1747 860088 F: +44 (0)1179 710414
 E: info@hamilton-litestat.com www.hamilton-litestat.com
 Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB
 Registered in London No. 941624 VAT Registration No. 222 6607 84



CERT. No. FM1238