Hamilton

making connections beautifully

| | Wiring Accessories • Circuit Protection • Sn | nart Lighting Control & Multi-room Audio |
|--|---|--|
| | 77COB | |
| | | |
| Hartl | and Bright Chrome 1 gang 20A Cable Outlet | Black |
| Item Image | Wiring | Dimensions |
| | | ● ● ● ● ● ● |
| | Prepare cord as shown below 10 35 25 5 25 10 10 10 10 10 10 10 10 10 10 10 10 10 | HEMILTON HARTLAND Cable outlet |
| Primary Range | Hartland | н |
| Insert Type | 1 gang 20A Cable Outlet | |
| Plate Finish | Hartland Box Bright Chrome | |
| Insert Colour | Black | |
| EAN13 Barcode | 5017503271764 | |
| Dimensions (Nominal) | Single: Height = 88.0mm Width = 88.0mm Depth = 5.0mm | |
| Fixing Hole Centres | Box Fixing = 60.3mm Grid Fixing = N/A | |
| Minimum Wall Box Depth | 35mm | |
| Switched Poles | None | |
| Current Rating | 20 Amp | |
| Voltage | 220/250V AC | |
| Maximum Load | 20 Amp | |
| Mains Frequency | 50Hz | |
| IP Rating | IP2XD | |
| Contact Gap Minimum | None | |
| Terminal Capacity 1 | 5 x 1mm2 | |
| Terminal Capacity 2 | 4 x 1.5mm2 | |
| Terminal Capacity 3 | 2 x 2.5mm2 | |
| Terminal Capacity 4 | 2 x 4mm2 Multi-strand | |
| Earth Terminal Capacity 1 | 6 x 1mm2 | |
| Earth Terminal Capacity 2 | 5 x 1.5mm2 | |
| Earth Terminal Capacity 3 | 3 x 2.5mm2 | |
| Earth Terminal Capacity 4 | 2 x 4mm2 Multi-strand | |
| Earth Terminal Capacity 5 | 1 x 6mm2 | |
| Product Class 1 | Must be earthed | |
| Ambient Operating Temperature | -5° to +40°C | |
| Recommended Location | Internal Use Only | |
| Maximum Installation Altitude | 2000m | |
| Cable Outlet Minimum/Maximum | Min = 0.75mm ² Max = 2.5mm ² | |
| Standard/Approval | BS 5733 | |
| Patents and Trademarks All products listed conform to current British or European standard and the product information is correct at the time of going to press. | Hartland is a Registered Trade Mark No. 2344778 All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. | It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. |
| Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. | Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes. | Correct as at 16 October 2018 12:58 PN E&OF |
| R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Ro T: +44 (0)1747 860088 F: +44 (0)1179 710414 Registered O E: info@hamilton-litestat.com Registered in | ad, Brislington, Bristol, BS4 5NZ ffice 1 Rushmills, Bedford Road, Northampton NN4 7YB London No. 941624 VAT Registration No. 222 6607 84 | Listed in STrinible LUCKINS ribble Ridduct Ribble |

SL