




77CUS99B

Hartland CFX Bright Chrome 2 gang 13A Unswitched Socket Black

| Item Image | Wiring | Dimensions |
|---|--|---|
|  |  |  |
| Primary Range | Hartland CFX | |
| Insert Type | 2 gang 13A Unswitched Socket | |
| Plate Finish | Hartland CFX Bright Chrome | |
| Insert Colour | Black | |
| EAN13 Barcode | 5017504010140 | |
| Dimensions (Nominal) | Double: Height = 86.0mm Width = 145.0mm Depth = 5.0mm | |
| Fixing Hole Centres | Box Fixing = 120.6mm Grid Fixing = CFX Clips | |
| Minimum Wall Box Depth | 35mm | |
| Switched Poles | None | |
| Current Rating | 13 Amp | |
| Voltage | 220/250V AC | |
| Maximum Load | 13 Amp | |
| Mains Frequency | 50Hz | |
| IP Rating | IP2XD | |
| Contact Gap Minimum | None | |
| Terminal Capacity 1 | 3 x 2.5mm ² | |
| Terminal Capacity 2 | 3 x 4mm ² | |
| Terminal Capacity 3 | 2 x 6mm ² Multi-Strand | |
| Terminal Capacity 4 | 1 x 10mm ² | |
| Earth Terminal Capacity 1 | 3 x 2.5mm ² | |
| Earth Terminal Capacity 2 | 3 x 4mm ² | |
| Earth Terminal Capacity 3 | 2 x 6mm ² Multi-strand | |
| Earth Terminal Capacity 4 | 1 x 10mm ² | |
| Product Class 1 | Must be earthed | |
| Ambient Operating Temperature | -5° to +40°C | |
| Recommended Location | Internal Use Only | |
| Maximum Installation Altitude | 2000m | |
| Standard/Approval | BS 1363-2 | |
| Additional Notes | Shuttered: Yes | |
| Patents and Trademarks | CFX is a Registered Trade Mark No 2398667 Hartland CFX is a Registered Design under Reference Nos. R21 = 3023446 SS2 = 3023445 | |
| All products listed conform to current British or European standard and the product information is correct at the time of going to press. | All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. | It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. |
| Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. | Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes. | Correct as at 16 October 2018 12:39 PM E&OE |

Hamilton®

making connections beautifully

SL

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio