Hamilton

making connections beautifully

SL

JL	SL THAKING CONNECTIONS DEAUTINITY		
Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio			
	77MED1B		
Hartland EuroEix Bright (Chrome Media Plate EURO4 aperture + 2 X13	A Linswitched Secket Black	
Item Image	Wiring	Dimensions	
		MED1 EURO4 Aperture with 2 x 13A Unswitched Socket	
Primary Range	EuroFix		
Insert Type	Media Plate EURO4 aperture + 2 X13A Unswitched Socket		
Plate Finish	Hartland EuroFix Bright Chrome		
Insert Colour	Black		
EAN13 Barcode	5028690271314		
Dimensions (Nominal)	150x150: Height = 146.0mm Width = 146.0mm Depth = 5.0mm		
Fixing Hole Centres	Box Fixing = 120.6mm x 2 Grid Fixing = N/A		
Minimum Wall Box Depth	As Per Inserts		
Switched Poles	None		
Current Rating	13 Amp		
Voltage	220/250V AC		
Maximum Load	13 Amp (socket)		
Mains Frequency	50Hz		
IP Rating	IP2XD		
Contact Gap Minimum	None		
Terminal Capacity 1	3 x 2.5mm2		
Terminal Capacity 2	3 x 4mm2		
Terminal Capacity 3	2 x 6mm2 Multi-Strand		
Terminal Capacity 4	1 x 10mm2		
Earth Terminal Capacity 1	3 x 2.5mm2		
Earth Terminal Capacity 2	3 x 4mm2		
Earth Terminal Capacity 3	2 x 6mm2 Multi-strand		
Earth Terminal Capacity 4	1 x 10mm2		
Product Class 1	Must be earthed (socket)		
Ambient Operating Temperature	-5° to +40°C		
Recommended Location	Internal Use Only		
Maximum Installation Altitude	2000m		
Standard/Approval	BS 1363-2 (socket)		
Additional Notes	SPECIAL NOTE : When mains voltage & telecom/data/TV are used in the wall box to shield the mains. Shuttered:Yes	e mixed on the same plate a suitable phase barrier MUST be	
Patents and Trademarks	EuroFix is a Registered Trade Mark No. 2560270		
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.	
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 15 October 2018 09:01 AM E&OE	
R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville T: +44 (0)1747 860088 F: +44 (0)1179 710414 Registered E: info@hamilton-litestat.com www.hamilton-litestat.com	Road, Brislington, Bristol, BS4 5NZ Office 1 Rushmills, Bedford Road, Northampton NN4 7YB in London No. 941624 VAT Registration No. 222 6607 84	Listed in Strimble Product Selector DSSPlus (String Control of Con	