

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

## 77SS2USBULTBC-B

| Hartland Bright Chrome 2 gang 13A D   | ouble Pole Switched Socket with 2 USB Ult   | ra Outlets 2x2.4A Bright Chrome/Black  |
|---|---|--|
| Item Image  | Wiring  | Dimensions   |
|   |   |  |
|   |   | ×  |
|   |   |  |
|   |   |  |
|   |   |  |
|   |   |  |
|   |   |  |
|   |   |  |
|   |   |  |
|   |   |  |
|   |   |  |
| Drimony Dongo   | Lloutond  |  |
| Primary Range   | Hartland 2 gang 13A Double Pole Switched Socket with 2 USB Outlets 2x2.4A (4.8A Total)                        |  |
| Insert Type Plate Finish  | Hartland Box Bright Chrome  |  |
| Insert Colour   |   |  |
| EAN13 Barcode   | Bright Chrome/Black 5017504090104   |  |
| Commodity Code  | 85363010  |  |
| Luckins TSI   | 405688014   |  |
|   | Double: Height = 88.0mm Width = 144.5mm Depth = 5.0mm   |  |
| Dimensions (Nominal) Weight   | Double: Height = 88.0mm   Width = 144.5mm   Depth = 5.0mm   |  |
| Fixing Hole Centres   | Box Fixing = 120.6mm Grid Fixing = N/A  |  |
| Minimum Wall Box Depth  | 35mm  |  |
| Switched Poles  | Double  |  |
| Current Rating  | 13 Amp, USB = 2.4A  |  |
| Voltage   | 13 Amp, USB = 2.4A<br>180/250V AC   |  |
| Maximum Load  | 13 Amp, USB = 2.4A  |  |
| Mains Frequency   | 50/60Hz   |  |
| IP Rating   | IP2XD   |  |
| Contact Gap Minimum   | 3mm   |  |
| Terminal Capacity 1   | 3 x 2.5mm2  |  |
| Terminal Capacity 1 Terminal Capacity 2   | 3 x 4mm2  |  |
| Terminal Capacity 3   | 2 x 6mm2 Multi-Strand   |  |
| Earth Terminal Capacity 1   | 3 x 2.5mm2  |  |
| Earth Terminal Capacity 2   | 3 x 4mm2  |  |
| Earth Terminal Capacity 3   | 2 x 6mm2 Multi-strand   |  |
| Product Class 1   | Must be earthed   |  |
| Ambient Operating Temperature   | -15°C to +40°C  |  |
| Recommended Location  | Internal Use Only   |  |
| Maximum Installation Altitude   | 2000m   |  |
| Standard/Approval   | BS 1363 + BS 5733 + EN 60950-1  |  |
| Patents and Trademarks  | Hartland is a Registered Trade Mark No. 2344778   |  |
| All products listed conform to current British or<br>European standard and the product information is<br>correct at the time of going to press. | All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.         | It is the policy of the company to improve products as part of our development programme.  Therefore, we reserve the right to alter designs and dimensions without prior notice. |
| Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.                      | Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes. | Correct as at 03 July 2019 07:23 AM E&OE   |

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ
T: +44 (0)1747 860088 F: +44 (0)1719 710414
E: info@hamilton-litestat.com www.hamilton-litestat.com Registered office 1 Rushmills, Bedford Road, Northar Registered in London No. 941624 VAT Registration N

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84











