SL

## making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

## **78C1XLEDITB100**

Hartland CFX Black Nickel 1g 100W LED 2 Way Push On/Off Rotary Dimmer Black Nickel Item Image Wiring **Dimensions** Hamilton HARTLAND CFX LEDITB100 2 Way Dimmer Hartland CFX Primary Range Insert Type 1 gang 100W LED Trailing/Leading Edge Push On/Off Rotary 2 Way Switching Dimmer Plate Finish Hartland CFX Black Nickel Insert Colour Black Nickel EAN13 Barcode 5017504079604 Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Wattage 5-100W (10 LED Lamps MAX) Switched Poles Single Current Rating 0.4A Voltage 230V-240V Maximum Load 5-100W (10 LED Lamps MAX) 50Hz Mains Frequency IP Rating IP2XD Terminal Capacity 1 2X1mm<sup>2</sup> Terminal Capacity 2 2X1.5mm<sup>2</sup> Earth Terminal Capacity 1 5X1mm<sup>2</sup> Earth Terminal Capacity 2 4X1.5mm<sup>2</sup> Earth Terminal Capacity 3 3X2.5mm<sup>2</sup> Earth Terminal Capacity 4 1X4mm<sup>2</sup> Multi-Strand Earth Terminal Capacity 5 1X6mm<sup>2</sup> Product Class 1 Face plate muct be earthed -5°C to +40°C **Ambient Operating Temperature** Internal Use Only Recommended Location Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-2-1 Additional Notes Trailing Edge & Leading Edge Dimmer CFX is a Registered Trade Mark No 2398667 Patents and Trademarks Hartland CFX is a Registered Design under Reference Nos. R21 = 3023446 SS2 = 3023445 All products listed conform to current British or All accessories are manufactured under an accredited It is the policy of the company to improve products European standard and the product information is BS EN ISO 9001: 2015 Quality Management System. as part of our development programme correct at the time of going to press. Therefore, we reserve the right to alter designs and dimensions without prior notice. Illustrations and diagrams are reproduced within Due to manufacturing processes we cannot Correct as at 16 October 2018 12:39 PM the limitations of reproduction and printing guarantee an exact colour match and shadings of process and are not binding.

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84









