## Hamilton

## making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio 78CSS2BK-B Hartland CFX Black Nickel 2 gang 13A Double Pole Switched Socket Black Nickel/Black Item Image Wiring Dimensions Hemilton SS2 Switched Socket Earth Primary Range Hartland CFX Insert Type 2 gang 13A Double Pole Switched Socket Plate Finish Hartland CFX Black Nickel Insert Colour Black Nickel/Black EAN13 Barcode 5017504282028 Dimensions (Nominal) Double: Height = 86.0mm Width = 145.0mm Depth = 5.0mm Weight 267 GR **Fixing Hole Centres** Box Fixing = 120.6mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Switched Poles Double Current Rating 13 Amp 220/250V AC Voltage Maximum Load 13 Amp 50Hz Mains Frequency IP Rating IP2XD Contact Gap Minimum 3mm **Terminal Capacity 1** 4 x 2.5mm2 **Terminal Capacity 2** 3 x 4mm2 **Terminal Capacity 3** 2 x 6mm2 Multi-Strand **Terminal Capacity 4** 1 x 10mm2 Earth Terminal Capacity 1 4 x 2.5mm2 Earth Terminal Capacity 2 3 x 4mm2 Earth Terminal Capacity 3 2 x 6mm2 Multi-strand Earth Terminal Capacity 4 1 x 10mm2 Product Class 1 Must be earthed -5° to +40°C Ambient Operating Temperature **Recommended Location** Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS 1363-2 Additional Notes Dual Earth: Yes CFX is a Registered Trade Mark No 2398667 Patents and Trademarks Hartland CFX is a Registered Design under Reference Nos. R21 = 3023446 SS2 = 3023445 All accessories are manufactured under an accredited All products listed conform to current British or It is the policy of the company to improve products European standard and the product information is BS EN ISO 9001 : 2015 Quality Management System. as part of our development programme correct at the time of going to press. Therefore, we reserve the right to alter designs and dimensions without prior notice. Illustrations and diagrams are reproduced within Due to manufacturing processes we cannot Correct as at 16 October 2018 12:40 PM guarantee an exact colour match and shadings of the limitations of reproduction and printing E&OE process and are not binding. of certain finishes. R Hamilton & Co Ltd. Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ Listed in STrimble % ECA T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84

SL

Hamilton

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio