SL

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

79C1XLEDITB100

Hartland CFX Antique Brass 1g 100W LED 2 Way Push On/Off Rotary Dimmer Antique Brass

Item Image Wiring **Dimensions** Hamilton HARTLAND CFX LEDITB100 2 Way Dimmer Hartland CFX Primary Range Insert Type 1 gang 100W LED Trailing/Leading Edge Push On/Off Rotary 2 Way Switching Dimmer Plate Finish Hartland CFX Antique Brass Insert Colour Antique Brass EAN13 Barcode 5017504079680 Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm Weight 200 GR Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Wattage 5-100W (10 LED Lamps MAX) Switched Poles Single **Current Rating** 0.4A Voltage 230V-240V 5-100W (10 LED Lamps MAX) Maximum Load Mains Frequency 50Hz IP Rating IP2XD Terminal Capacity 1 2X1mm² Terminal Capacity 2 2X1.5mm² Earth Terminal Capacity 1 5X1mm²

Ambient Operating Temperature -5°C to +40°C
Recommended Location Internal Use Only
Maximum Installation Altitude 2000m

Standard/Approval BS EN 60669-2-1
Additional Notes Trailing Edge & Leading Edge Dimmer

Patents and Trademarks

CFX is a Registered Trade Mark No 2398667

Hartland CFX is a Registered Design under Reference Nos.

R21 = 3023446

SS2 = 3023445

4X1.5mm²

3X2.5mm²

1X6mm²

1X4mm² Multi-Strand

Face plate muct be earthed

All products listed conform to current British or European standard and the product information is correct at the time of going to press.

Illustrations and diagrams are reproduced within

the limitations of reproduction and printing process and are not binding.

All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.

Due to manufacturing processes we cannot guarantee an exact colour match and shadings of

of certain finishes

It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.

Correct as at 16 October 2018 12:40 PM

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com

Earth Terminal Capacity 2

Earth Terminal Capacity 3

Earth Terminal Capacity 4

Earth Terminal Capacity 5

Product Class 1

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84















Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio