

## making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

## 79CRRTAB-B

	Hartland CFX Antique Brass 1 g	79CRRTAB-B ang 10AX Push To Make/Push to Break Retra	active Rocker Antique Brass/Black	
Primary Range Harifand CFX  Insert Type 1 gave 1 to New Plus in Service Retractive Rocker  Phase Probe Harifand CFX  Insert Type 1 1 gave 1 to New Plus in Service Retractive Rocker  Phase Probe Harifand CFX  Insert Type 1 1 gave 1 to New Plus in Service Retractive Rocker  Phase Probe Harifand CFX Antique Brass  Insert Colour Antique Brass Brass  Insert Colour Brass  Insert Colour Antique Brass Brass  Insert Colour A	Item Image	Wiring	Dimensions	
Primary Range Hartland CFX Insert Type 1 agang 10AX Push To Makei Push to Break Retractive Rocker Pate Finds Insert Colour Antique Brass Insert Colour		Com  Com  L2 L1	HARTLAND CFX CFXRRT	
Insert Type			- 152 T	
Pate Finish Insert Colour Antique Brass Black EAN13 Barcode 5017504282195 Denensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm Fixing Hole Centres Box Exing = 60.3mm Grld Fixing = CFX Clips Minimum Wall Bax Depth 25mm Switched Poles Single Current Rating 10AX Voltage 220250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz Prating PPXD Contact Gap Minimum 3mm 1P2XD Contact Gap Minimum 3mm 1P3mm 1Capacity 1 1 x 4.5mm2 1Faminal Capacity 3 1 x 2.5mm2 1Faminal Capacity 3 1 x 4.5mm2 1Faminal Capacity 4 1 x 4.7mm2 Multi-strand 1Faminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 1 x 1.5mm2 Earth Terminal Capacity 3 1 x 4.7mm2 Multi-strand 1 x 4.7mm2 Multi-str	Primary Range	Hartland CFX		
Insert Colour  Antique Brass/Black  5017504/292195  5017504/292195  Box Fixing = 60.3mm Width = 86.0mm Depth = 5.0mm  Fixing Hole Centres  Box Fixing = 60.3mm Grid Fixing = CFX Clips  Minimum Wall Box Depth  25mm  Switched Poles  Single  Current Rating  10AX  Voltage  220/250V AC  Maximum Load  10 Amp inductive  Mains Frequency  50Hz  1P2XD  Contact Gap Minimum  3mm  Tarminal Capacity 1  5 x 1mm2  Tarminal Capacity 1  5 x 1mm2  Tarminal Capacity 3  1 x 2.5mm2  Tarminal Capacity 3  1 x 1 x 1.5mm2  Tarminal Capacity 4  1 x 4.mmx Multi-strand  Tarminal Capacity 5  5 x 1 mm2  Earth Terminal Capacity 1  5 x 1 mm2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 3  5 x 1 mm2  Earth Terminal Capacity 3  Earth Terminal Capacity 4  Earth Terminal Capacity 5  Earth Terminal Capacity 5  Earth Terminal Capacity 6  Earth	Insert Type	1 gang 10AX Push To Make/Push to Break Retractive Rocker		
EAN13 Barcode 5017504292195 Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm Fixing Holo Centres 80x Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 25mm Switched Poles Single Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5 x fmm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 1 x 2.5mm2 Terminal Capacity 3 1 x 2.5mm2 Terminal Capacity 4 1 x 4mm2 Multi-strand Terminal Capacity 3 3 3 x 2.5mm2 Earth Terminal Capacity 4 5 x fmm2 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 6 1 x 6mm2 Earth Terminal Capacity 7 5 x fmm2 Earth Terminal Capacity 8 5 x fmm2 Earth Terminal Capacity 9 x fmm2 Earth Termina	Plate Finish	Hartland CFX Antique Brass		
Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm  Box Fixing = 60.3mm Grid Fixing = CFX Clips  Minimum Wall Box Depth Switched Poles Single Current Rating 10AX Voltage 10AX Voltage 220/256V AC Maximum Load 10 Amp inductive Mains Frequency 10P Rating 10P2XD Contact Gap Minimum 3mm 10Fixing 1 Capacity 1 5 x 1mm2 10Fixing 1 Capacity 1 1 x 2.5mm2 10Fixing 1 x 2.5	Insert Colour	Antique Brass/Black		
Fixing Hole Centres   Box Fixing = 60.3mm Grid Fixing = CFX Clips	EAN13 Barcode	5017504292195		
Minimum Wall Box Depth Switched Poles Single Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 1 x 2.5mm2 Terminal Capacity 3 1 x 2.5mm2 Terminal Capacity 4 1 x 4mm2 Multi-strand Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 1 x 2.5mm2 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 6 Froduct Class 1 Ambient Operating Temperature 5 to 4-0°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Ratination Internal Use Only Maximum Installation Altitude 2000m Ratination Internal Use Only Maximum Installation Altitude Be Standard/Approval B S R 06669-1  All secsosories are manufactured under an accreation Internal Use Only Internal Use Only Internal Use Only Internal Operation of the product information is correct at the time of going to press.  All spoducts listed contorn to current British or European to improve products a spin of oir development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.  Blustrations and diagrams are reproducted within the limitations of reproduction and printing processes are a cost brindings of cotential finisher.  But the reprocess and are not brindings  Due to manufacturing processes we cannot printing and dimensions without prior notice.  E&C.  Correct as at 16 October 2018 12-4.0 P E&C.  Correct as at 16 October 2018 12-4.0 P E&C.  Correct as at 16 October 2018 12-4.0 P E&C.  Correct as at 16 October 2018 12-4.0 P E&C.  Correct as at 16 October 2018 12-4.0 P E&C.  Correct as at 16 October 2018 12-4.0 P E&C.  Correct as at 16 October 2018 12-4.0 P E&C.  Correct as a	Dimensions (Nominal)	Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm		
Switched Poles Current Rating 10AX 200/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP Ratin	Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips		
Current Rating	Minimum Wall Box Depth	25mm		
Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IPZXD Contact Gap Minimum 3mm Terminal Capacity 1 5 x 1mm2 Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 1 x 2.5mm2 Terminal Capacity 4 1 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 6 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature 5 to 40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m  Standard/Approval BS EN 60669-1  Patents and Trademarks 4 Registered Trade Mark No 2398667 Harland CFX is a Registered Trade Mark No 239867 European standard and the product information is correct at the time of going to press.  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  Business and diagrams are reproducted within the limitations and diagrams are reproducted within the limitations of reproduction and printing processes we cannot guarantee an exact colour match and shadings of of cetar in Rishes.	Switched Poles	Single		
Maximum Load 10 Amp inductive  Mains Frequency 50Hz  IP Rating IP2XD  Contact Gap Minimum 3mm  Terminal Capacity 1 5x 1mm2  Terminal Capacity 2 4x 1.5mm2  Terminal Capacity 3 1x 2.5mm2  Terminal Capacity 4 1x 4mm2 Multi-strand  Terminal Capacity 5 1x 6mm2  Earth Terminal Capacity 1 5x 1mm2  Earth Terminal Capacity 1 5x 1mm2  Earth Terminal Capacity 2 4x 1.5mm2  Earth Terminal Capacity 3 1x 6mm2  Earth Terminal Capacity 4 1x 4mm2 Multi-strand  Earth Terminal Capacity 5 1x 6mm2  Earth Terminal Capacity 5 1x 6mm2  Earth Terminal Capacity 6 1x 6mm2  Forduct Class 1 1x 6mm2  Forduct Class 1x 6mm2  Forduc	Current Rating	10AX		
Mains Frequency  Description  Brating	Voltage	220/250V AC		
P2XD   Contact Gap Minimum   3mm	Maximum Load	10 Amp inductive		
Contact Gap Minimum  Terminal Capacity 1  Terminal Capacity 2  4 x 1.5mm2  Terminal Capacity 3  1 x 2.5mm2  Terminal Capacity 4  1 x 4mm2 Multi-strand  Terminal Capacity 5  1 x 6mm2  Earth Terminal Capacity 1  5 x 1mm2  Earth Terminal Capacity 1  5 x 1mm2  Earth Terminal Capacity 2  4 x 1.5mm2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 3  1 x 4mm2 Multi-strand  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 4  1 x 4mm2 Multi-strand  Earth Terminal Capacity 5  1 x 6mm2  Product Class 1  Must be earthed  Ambient Operating Temperature  5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m  Standard/Approval  BS EN 60669-1  CFX is a Registered Trade Mark No 2399667  Hartland CFX is a Registered Design under Reference Nos. R21 = 3023446 SS2 = 3023445  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to late designs and dimensions without prior notice.  Therefore, we reserve the right to late designs and dimensions without prior notice.  E&C ortant insishes.	Mains Frequency	50Hz		
Terminal Capacity 1 5 x 1mm2  Terminal Capacity 2 4 x 1.5mm2  Terminal Capacity 3 1 x 2.5mm2  Terminal Capacity 4 1 x 4mm2 Multi-strand  Terminal Capacity 5 1 x 6mm2  Earth Terminal Capacity 1 5 x 1mm2  Earth Terminal Capacity 2 4 x 1.5mm2  Earth Terminal Capacity 2 4 x 1.5mm2  Earth Terminal Capacity 3 3 x 2.5mm2  Earth Terminal Capacity 3 3 x 2.5mm2  Earth Terminal Capacity 4 1 x 4mm2 Multi-strand  Earth Terminal Capacity 5 1 x 6mm2  Product Class 1 Must be earthed  Ambient Operating Temperature 55 to +40°C  Recommended Location Internal Use Only  Maximum Installation Altitude 2000m  Standard/Approval BS EN 6069-1  CPX is a Registered Trade Mark No 2398667  Hartland CPX is a Registered Design under Reference Nos. R21 = 3023446 SSE = 3023445 SSE =	IP Rating	IP2XD		
Terminal Capacity 3  1 x 2.5mm2  Terminal Capacity 4  1 x 4mm2 Multi-strand  Terminal Capacity 5  1 x 6mm2  Earth Terminal Capacity 1  Earth Terminal Capacity 2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 3  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 3  Earth Terminal Capacity 3  Earth Terminal Capacity 3  Earth Terminal Capacity 4  1 x 4mm2 Multi-strand  Earth Terminal Capacity 4  1 x 4mm2 Multi-strand  Earth Terminal Capacity 5  1 x 6mm2  Product Class 1  Must be earthed  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m  Standard/Approval  BS EN 60669-1  Patents and Trademarks  CFX is a Registered Trade Mark No 2398667  Harltand CFX is a Registered Design under Reference Nos. R21 = 3023446 SS2 = 3023445  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter designs and dimensions without prior notice.  European standard and the production mark of production and printing guarantee an exact colour match and shadings of process and are not blinding.  Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes.	Contact Gap Minimum	3mm		
Terminal Capacity 3  1 x 2.5mm2  Terminal Capacity 4  1 x 4mm2 Multi-strand  1 x 6mm2  Earth Terminal Capacity 1  Earth Terminal Capacity 2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 3  Earth Terminal Capacity 3  Earth Terminal Capacity 4  1 x 4mm2 Multi-strand  Earth Terminal Capacity 4  Earth Terminal Capacity 4  1 x 4mm2 Multi-strand  Earth Terminal Capacity 5  1 x 6mm2  Product Class 1  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m  Standard/Approval  BS EN 60669-1  CFX is a Registered Trade Mark No 2398667  Hartland CFX is a Registered Design under Reference Nos. R21 = 3023446 SS2 = 3023445  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  BILUSTRIVEN STANDARD STAND	Terminal Capacity 1	5 x 1mm2		
Terminal Capacity 4  1 x 4mm2 Multi-strand  Terminal Capacity 5  Earth Terminal Capacity 1  Earth Terminal Capacity 2  Earth Terminal Capacity 2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 4  Earth Terminal Capacity 4  Earth Terminal Capacity 4  Earth Terminal Capacity 5  Ix 4mm2 Multi-strand  Earth Terminal Capacity 4  Earth Terminal Capacity 5  Ix 4mm2 Multi-strand  Earth Terminal Capacity 6  Earth Terminal Capacity 6  Earth Terminal Capacity 7  Ix 4mm2 Multi-strand  Earth Terminal Capacity 8  Earth Terminal Capacity 8  Ix 4mm2 Multi-strand  Earth Terminal Capacity 9  Ix 4x 4mm2 Mul	Terminal Capacity 2	4 x 1.5mm2		
Terminal Capacity 5  Earth Terminal Capacity 1  Earth Terminal Capacity 2  Earth Terminal Capacity 2  Earth Terminal Capacity 3  Earth Terminal Capacity 3  Earth Terminal Capacity 4  Earth Terminal Capacity 4  Earth Terminal Capacity 4  Earth Terminal Capacity 5  Earth Terminal Capacity 6  Earth Terminal Capacity 7  Earth Terminal Capacity 8  Earth Terminal Capacity 9	Terminal Capacity 3	1 x 2.5mm2		
Earth Terminal Capacity 1 5 x 1mm2  Earth Terminal Capacity 2 4 x 1.5mm2  Earth Terminal Capacity 3 3 x 2.5mm2  Earth Terminal Capacity 4 1 x 4mm2 Multi-strand  Earth Terminal Capacity 5 1 x 6mm2  Product Class 1 Must be earthed  Ambient Operating Temperature 5° 0° to 40°C  Recommended Location Internal Use Only  Maximum Installation Altitude 2000m  Standard/Approval BS EN 6069-1  CFX is a Registered Trade Mark No 2398667  Harthand CFX is a Registered Design under Reference Nos. R21 = 3023446 SS2 = 3023445  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  Bue to manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.  Correct as at 16 October 2018 12:40 P E&C or examination in Survey and the contain finishes.	Terminal Capacity 4	1 x 4mm2 Multi-strand		
Earth Terminal Capacity 2  Earth Terminal Capacity 3  Earth Terminal Capacity 4  Earth Terminal Capacity 4  Earth Terminal Capacity 5  Product Class 1  Must be earthed  Ambient Operating Temperature  Ambient Operating Temperature  Fecommended Location  Internal Use Only  Maximum Installation Altitude  Standard/Approval  BS EN 60669-1  CFX is a Registered Trade Mark No 2398667  Hartland CFX is a Registered Design under Reference Nos.  R21 = 3023446 SS2 = 3023445  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  BAII cocessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  BAII cocessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Correct at the time of going to press.  BAII cocessories are manufacturing processes we cannot the limitations of reproduction and printing processes and are not binding.  Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Terminal Capacity 5	1 x 6mm2		
Earth Terminal Capacity 3  Earth Terminal Capacity 4  Earth Terminal Capacity 4  Earth Terminal Capacity 5  1 x 4mm2 Multi-strand  Earth Terminal Capacity 5  1 x 6mm2  Product Class 1  Must be earthed  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m  Standard/Approval  BS EN 60669-1  CFX is a Registered Trade Mark No 2398667  Hartland CFX is a Registered Design under Reference Nos.  R21 = 3023446 SS2 = 3023445  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  But is the policy of the company to improve products as a part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.  But is the policy of the company to improve products as a part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.  Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Earth Terminal Capacity 1	5 x 1mm2		
Earth Terminal Capacity 4  Earth Terminal Capacity 5  1 x 6mm2  Product Class 1  Must be earthed  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m  Standard/Approval  BS EN 6069-1  CFX is a Registered Trade Mark No 2398667  Hartland CFX is a Registered Design under Reference Nos. R21 = 3023446 SS2 = 3023445  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN 150 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter designs and dimensions without prior notice.  Due to manufacturing processes we cannot guarantee an exact colour match and shadings of process and are not binding.  Correct as at 16 October 2018 12:40 P Guarantee an exact colour match and shadings of of certain finishes.	Earth Terminal Capacity 2	4 x 1.5mm2		
Earth Terminal Capacity 5  Product Class 1  Must be earthed  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m  Standard/Approval  BS EN 6069-1  CFX is a Registered Trade Mark No 2398667  Hartland CFX is a Registered Design under Reference Nos. R21 = 3023446 SS2 = 3023445  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter designs and dimensions without prior notice.  Due to manufacturing processes we cannot guarantee an exact colour match and shadings of process and are not binding.  Correct as at 16 October 2018 12:40 P ERC	Earth Terminal Capacity 3	3 x 2.5mm2		
Product Class 1  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m  Standard/Approval  BS EN 60669-1  CFX is a Registered Trade Mark No 2398667 Hartland CFX is a Registered Design under Reference Nos. R21 = 3023446 SS2 = 3023445  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter designs and dimensions without prior notice.  Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.  Correct as at 16 October 2018 12:40 P ERCOMMENTAL CORRECT STANDARD STA	Earth Terminal Capacity 4	1 x 4mm2 Multi-strand	1 x 4mm2 Multi-strand	
Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m  Standard/Approval  BS EN 60669-1  CFX is a Registered Trade Mark No 2398667 Hartland CFX is a Registered Design under Reference Nos. R21 = 3023446 SS2 = 3023445  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter designs and dimensions without prior notice.  Due to manufacturing processes we cannot the limitations of reproduction and printing process and are not binding.  Correct as at 16 October 2018 12:40 P ERC	Earth Terminal Capacity 5	1 x 6mm2		
Recommended Location Internal Use Only  Maximum Installation Altitude 2000m  Standard/Approval BS EN 60669-1  Patents and Trademarks CFX is a Registered Trade Mark No 2398667  Hartland CFX is a Registered Design under Reference Nos. R21 = 3023446 SS2 = 3023445  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Illustrations and diagrams are reproduced within the limitations of reproduction and printing processes we cannot guarantee an exact colour match and shadings of of certain finishes.  Correct as at 16 October 2018 12:40 P E&C of certain finishes.	Product Class 1	Must be earthed		
Maximum Installation Altitude  2000m  Standard/Approval  BS EN 60669-1  CFX is a Registered Trade Mark No 2398667  Hartland CFX is a Registered Design under Reference Nos. R21 = 3023446 SS2 = 3023445  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Illustrations and diagrams are reproduced within the limitations of reproduction and printing processes we cannot guarantee an exact colour match and shadings of process and are not binding.  Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Ambient Operating Temperature	-5° to +40°C	-5° to +40°C	
Standard/Approval  BS EN 60669-1  CFX is a Registered Trade Mark No 2398667  Hartland CFX is a Registered Design under Reference Nos. R21 = 3023446 SS2 = 3023445  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.  Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.  BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter designs and dimensions without prior notice.  Correct as at 16 October 2018 12:40 P E&C of certain finishes.	Recommended Location			
Patents and Trademarks  CFX is a Registered Trade Mark No 2398667 Hartland CFX is a Registered Design under Reference Nos. R21 = 3023446 SS2 = 3023445  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.  Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.  CFX is a Registered Trade Mark No 2398667 Hartland CFX is a Registered Design under Reference Nos. R21 = 3023446 SS2 = 3023445  It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.  Correct as at 16 October 2018 12:40 P E&C process and are not binding.	Maximum Installation Altitude			
Patents and Trademarks  Hartland CFX is a Registered Design under Reference Nos. R21 = 3023446 SS2 = 3023445  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.  Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.  BIT is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.  Correct as at 16 October 2018 12:40 P ESC of certain finishes.	Standard/Approval			
European standard and the product information is correct at the time of going to press.  BS EN ISO 9001 : 2015 Quality Management System.  BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter designs and dimensions without prior notice.  Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.  Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.  Correct as at 16 October 2018 12:40 P E&C of certain finishes.	Patents and Trademarks	Hartland CFX is a Registered Design under Reference Nos.		
the limitations of reproduction and printing guarantee an exact colour match and shadings of process and are not binding. guarantee an exact colour match and shadings of certain finishes.	European standard and the product information is		as part of our development programme. Therefore, we reserve the right to alter designs	
	the limitations of reproduction and printing	guarantee an exact colour match and shadings of of certain finishes.	Correct as at 16 October 2018 12:40 PM E&OE	

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84















Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio