## Hamilton

## making connections beautifully

SL

	Wiring Accessories • Circuit Protection • Sr	nart Lighting Control & Multi-room Audio
	7BC4X40BL	
Hartland CEX Colours Let Black 4x400M	V Resistive Leading Edge Push On-Off Rotary	2 Way Switching Dimmors may 250W por
	gang Black	
Item Image	Wiring	Dimensions
	Dommer-Wiring Law Nupru Law Nupru Mutan And Nupru And Nupru	Hemilton HARTLAND CFX COLOURS P4X40 Resistive Leading Edge Push On-Off Rotary 2 Way Switching Dimmer
Primary Range	Hartland CFX Colours	
Insert Type	4 gang 400W Resistive Leading Edge Push On-Off Rotary 2 Way Switching Dimmer max 250W per gang	
Plate Finish	Hartland CFX Colours Jet Black	
Insert Colour	Black	
EAN13 Barcode	5017504006792	
	Double: Height = 86.0mm Width = 146.0mm Depth = 5.0mm	
Dimensions (Nominal)		
Fixing Hole Centres	Box Fixing = 120.6mm Grid Fixing = CFX Push	
Minimum Wall Box Depth	35mm	
Wattage	250W per gang	
Switched Poles	Single	
Current Rating	1. Amps per gang	
Voltage	220/250V AC	
Maximum Load	250W resistive per gang	
Mains Frequency	50Hz	
P Rating	IP2XD	
Contact Gap Minimum	N/A	
Terminal Capacity 1	2 x 1mm2	
Terminal Capacity 2	2 x 1.5mm2	
Earth Terminal Capacity 1	5 x 1mm2	
Earth Terminal Capacity 2	4 x 1.5mm2	
Earth Terminal Capacity 3	3 x 2.5mm2	
Earth Terminal Capacity 4	1 x 4mm2 Multi-strand	
Earth Terminal Capacity 5	1 x 6mm2	
Product Class 1	Face plate must be earthed	
Ambient Operating Temperature	-5° to +40°C	
Recommended Location	Internal Use Only	
Maximum Installation Altitude	2000m	
Standard/Approval	BS EN 60669-2-1	
Additional Notes	Tungsten filament GU10 lamps must be branded with a fuse base. When using mains voltagehalogen lamps- dimmers should be de-rated by 25%. When dimming LED lamps de-rated by 75% - please contact our Technical for compatibility.	
Patents and Trademarks	CFX is a Registered Trade Mark No 2398667	
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 15 October 2018 10:21 AN E&OF
R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville T: +44 (0)1747 860088 F: +44 (0)1179 710414 Registere E: info@hamilton-litestat.com www.hamilton-litestat.com Registere	Road, Brislington, Bristol, BS4 5NZ d Office 1 Rushmills, Bedford Road, Northampton NN4 7YB d in London No. 941624 VAT Registration No. 222 6607 84	Listed in Trimble. Product Product Selector CRT. No. PMID: CRT. No. PMID: 2000 CRT. NO

Hamilton

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio