## Hamilton

## making connections beautifully

	Wiring Accessories • Circuit Protection • Sn	nart Lighting Control & Multi-room Audio
	7CBCUS13B	
Hartland (	FX Copper Bronze 1 gang 13A Unswitched S	Socket Black
	A Copper Diolize 1 gaily 13A Oliswitched C	JUCKET DIACK
Item Image	Wiring	Dimensions
, and the second s		
	Neutral	Hemilton
		US13 Unswitched Socket
		- 19.2 -
		86.0
	1 guinter and	
Primary Range	Hartland CFX	
Insert Type	1 gang 13A Unswitched Socket	
Plate Finish	Hartland CFX Copper Bronze	
Insert Colour	Black	
EAN13 Barcode	5017504011383 Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm	
Dimensions (Nominal) Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips	
Minimum Wall Box Depth	35mm	
Switched Poles	None	
Current Rating	13 Amp	
Voltage	220/250V AC	
Maximum Load	13 Amp	
Mains Frequency	50Hz	
IP Rating	IP2XD IP2XD	
Contact Gap Minimum	None	
Terminal Capacity 1	3 x 2.5mm2	
Terminal Capacity 2	3 x 4mm2	
Terminal Capacity 3	2 x 6mm2 Multi-Strand	
Terminal Capacity 4	1 x 10mm2	
Earth Terminal Capacity 1 Earth Terminal Capacity 2	3 x 2.5mm2 3 x 4mm2	
Earth Terminal Capacity 3	2 x 6mm2 Multi-strand	
Earth Terminal Capacity 4	1 x 10mm2	
Product Class 1	Must be earthed	
Ambient Operating Temperature	-5° to +40°C	
Recommended Location	Internal Use Only	
Maximum Installation Altitude	2000m	
Standard/Approval	BS 1363-2	
Additional Notes	Shuttered: Yes	
Patents and Trademarks	CFX is a Registered Trade Mark No 2398667 Hartland CFX is a Registered Design under Reference Nos. R21 = 3023446 SS2 =3023445	
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 16 October 2018 12:40 PM E&OE
R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville F         T: +44 (0)1747 860088       F: +44 (0)179 710414       Registered         E: info@hamilton-litestat.com       Registered i	Road, Brislington, Bristol, BS4 5NZ Office 1 Rushmills, Bedford Road, Northampton NN4 7YB n London No. 941624 VAT Registration No. 222 6607 84	Listed in Strimule LUCKINS ribe selector Display

Hamilton

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio