

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

## **7EBC1X40**

	Hartland CFX Etrium Bronze 1x400W Resistive Leading Edge Push On-Off Rotary 2 Way Switching Dimmer Etrium Bronze			
Primary Range   Martinand CFX   Insent Type   1 gamp 400W Resistive Leading Edge Push On-Off Rotary 2 Way Switching Dimmer   Pata Finish   Hartinand CFX Entrum Bronze   Family Range   Martinand CFX Ent	Item Image	Wiring	Dimensions	
Insert Type		Nongrad  Lam    Change   Chang	HARTLAND CFX 1X40 1X40 Resistive Leading Edge Push On-Off Rotary 2 Way Switching Dimmer	
Plate Finish Insert Colour Etrium Bronze Exhi Sancode Sort7504011468 Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm Fixing Hole Centres Box Fixing = 60.3mm Gnid Fixing = CFX Clips Minimum Wall Box Depth S5mm Wattage 400W Wattage 400W Wattage 1.66.4mp Voltage 220/250V AC Wattage 220/250V AC Wattage 220/250V AC Wattage 1.70 Packing Pextor Unreal Rading Pizxin Practing Pizxing Pixxing Pixxin	Primary Range	Hartland CFX	•	
Plate Finish Insert Colour Etrium Bronze Exhi Sancode Sort7504011468 Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm Fixing Hole Centres Box Fixing = 60.3mm Gnid Fixing = CFX Clips Minimum Wall Box Depth S5mm Wattage 400W Wattage 400W Wattage 1.66.4mp Voltage 220/250V AC Wattage 220/250V AC Wattage 220/250V AC Wattage 1.70 Packing Pextor Unreal Rading Pizxin Practing Pizxing Pixxing Pixxin		1 gang 400W Resistive Leading Edge Push On-Off Rotary 2 Way Switching Dimmer		
EAN13 Barcode 5017504011468  Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm  Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips  Minimum Wall Box Depth 35mm  Wattage 400W  Wattage 400W  Single Current Rating 1.66.4mp  Voltage 220/250V AC  Maximum Load 400W resistive Min Load  Mains Frequency 50Hz  IP Rating IPZXD  Contact Gap Minimum NA  Terminal Capacity 1 2 x 1mm2  Terminal Capacity 1 5 x 1mm2  Earth Terminal Capacity 1 5 x 1mm2  Earth Terminal Capacity 3 3 x 2.5mm2  Earth Terminal Capacity 3 1 x 4mm2 Multi-strand  Earth Terminal Capacity 4 1 x 4mm2 Multi-strand  Earth Terminal Capacity 4 1 x 4mm2 Multi-strand  Earth Terminal Capacity 5 1 x 8mm2  Forduct Class 1 Face plate must be earthed  Ambient Operating Temperature 5-5 to 440°C  Ratingum Installation Altitude 2000m  Maximum Installation Altitude 2000m  Additional Notes 5 1 to 490°C  Patents and Trademarks  All products listed conform to current British or European standard and the product information is CFX is a Registered Dissipal must be branded with a fuse base. When using mains voltagehalogen lamps-dimmers should be de-rated by 25%. When dimming LED lamps de-rated by 75% - please contact our Technical for compatibility.  Patents and Trademarks  All products listed conform to current British or European standard and the product information is CFX is a Registered Dissipal must be branded with a fuse base. When using mains voltagehalogen lamps-dimmers should be de-rated by 25%. When dimming LED lamps de-rated by 75% - please contact our Technical for compatibility.  Patents and Trademarks  All products listed conform to current British or European standard and the product information is CFX is a Registered Dissipal must reducted under an accredited SS ENS D8001: 2015 Closibil Management System.  Bustrations and diagrams are reproduced within the limitations of reproduction and printing				
Dimensions (Nominal)  Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm  Box Fixing = 60.3mm Grid Fixing = CFX Clips  Minimum Wall Box Depth  35mm  Wattage  400W  Switched Poles Single Current Rating 1.66 Amp  Voltage 220/250V AC  Maximum Load 400W resistive Min Load  Mains Frequency 50Hz IP Rating IP2XD  Contact Gap Minimum N/A  Terminal Capacity 1  Terminal Capacity 1  Terminal Capacity 1  Terminal Capacity 1  Sarth Terminal Capacity 3  Sart 2.5mm2  Earth Terminal Capacity 3  Terminal Capacity 4  Terminal Capacity 4  Terminal Capacity 5  Terminal Capacity 5  Terminal Capacity 6  Terminal Capacity 6  Terminal Capacity 7  Terminal Capacity 8  Terminal Capacity 9  Termin	Insert Colour			
Fixing Hole Centres  Box Fixing = 60.3mm Grid Fixing = CFX Clips  Minimum Wall Box Depth  35mm  400W  Switched Poles  Single  Current Rating  1.66 Amp  Voltage  400W resistive Min Load  Mains Frequency  1.70 Part Rating  1.70 Pa	EAN13 Barcode	5017504011468		
Fixing Hole Centres  Box Fixing = 60.3mm Grid Fixing = CFX Clips  Minimum Wall Box Depth  35mm  400W  Switched Poles  Single  Current Rating  1.66 Amp  Voltage  400W resistive Min Load  Mains Frequency  1.70 Part Rating  1.70 Pa	Dimensions (Nominal)	Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm		
Minimum Wall Box Depth  35mm  Wattage  400W  Single  Current Rating  1.66 Amp  Voltage  220/250V AC  Maximum Load  400W resistive Min Load  Mains Frequency  50Hz  IP Rating  P2XD  Contact Gap Minimum  NIA  Terminal Capacity 1  2 x 1mm2  Terminal Capacity 1  2 x 1mm2  Earth Terminal Capacity 2  2 x 1.5mm2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 3  Earth Terminal Capacity 3  Terminal Capacity 5  Terminal Capacity 6  Terminal Capacity 7  Earth Terminal Capacity 8  Earth Terminal Capacity 9  Earth Terminal Capacity 9  Earth Terminal Capacity 1  Earth Terminal Capacity 1  Earth Terminal Capacity 1  Earth Terminal Capacity 3  Earth Terminal Capacity 6  Earth	Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips		
Wattage 400W Switched Poles 5ningle 1.66 Amp Voltage 220/250V AC Maximum Load 400W resistive Min Load Mains Frequency 50Hz PR ating IP2XD Contact Gap Minimum N/A Terminal Capacity 1 2 x 1mm2 Terminal Capacity 1 2 x 1mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 1 x 4mm2 Earth Terminal Capacity 4 1 x 4mm2 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 6 1 x 6mm2 Product Class 1 Face plate must be earthed Ambient Operating Temperature 5° to 440°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-2-1 Additional Notes Trugsten filement GU10 lamps must be branded with a fuse base. When using mains voltagehalogen lamps-dimmers should be de-rated by 25%. When dimming LED lamps de-rated by 75% - please contact our Technical for compatibility.  CEX is a Registered Trade Mark No 2398667 Harland CFX is a Registered Design under Reference Nos. R21 = 3023448 SS2	Minimum Wall Box Depth			
Current Rating		400W		
Voltage 220/250V AC  Maximum Load 400W resistive Min Load  Mains Frequency 50Hz  IP Rating IP2XD  Contact Gap Minimum N/A  Terminal Capacity 1 2 x 1.mm2  Terminal Capacity 1 5 x 1.mm2  Earth Terminal Capacity 1 5 x 1.mm2  Earth Terminal Capacity 2 4 x 1.5mm2  Earth Terminal Capacity 3 3 x 2.5mm2  Earth Terminal Capacity 3 1 x 4.mm2 Multi-strand  Earth Terminal Capacity 4 1 x 4.mm2 Multi-strand  Earth Terminal Capacity 5 1 x 6.mm2  Forduct Class 1 Face plate must be earthed  Ambient Operating Temperature 5° to +40°C  Recommended Location Internal Use Only  Maximum Installation Altitude 2000m  Standard/Approval BS EN 60669-2-1  Additional Notes Trugester Mark No 2399667  Patents and Trademarks Trademarks Registered Trade Mark No 2399667  Hartland CFX is a Registered Design under Reference Nos.  R21 = 3023446 SS2 = 3023445  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter designs and dimensions without prior notice.  BEN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter designs and dimensions without prior notice.  BEN ISO 9001 : 2015 Quality Management System.  Theref	Switched Poles	Single		
Maximum Load  400W resistive Min Load  Mains Frequency  50Hz  IP Rating  IP 2XD  Contact Gap Minimum  N/A  Terminal Capacity 1  2 x 1mm2  Terminal Capacity 1  2 x 1.5mm2  Earth Terminal Capacity 1  5 x 1mm2  Earth Terminal Capacity 2  4 x 1.5mm2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 4  1 x 4mm2 Multi-strand  Earth Terminal Capacity 5  1 x 6mm2  Product Class 1  Ambient Operating Temperature  5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m  Standard/Approval  Additional Notes  Patents and Trademarks  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All correct as at 16 October 2018 12.40 P (supplement programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.  BESEN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter designs and dimensions without prior notice.  Each Correct as at 16 October 2018 12.40 P (supplement programme) and demensions without prior notice.  Each Correct as at 16 October 2018 12.40 P (supplement programme) and demensions without prior notice.	Current Rating	1.66 Amp		
Mains Frequency    P Rating   IP2XD	Voltage	220/250V AC		
IP Rating	Maximum Load	400W resistive Min Load		
Contact Gap Minimum  N/A  Terminal Capacity 1  2 x 1mm2  Earth Terminal Capacity 2  Earth Terminal Capacity 1  Earth Terminal Capacity 1  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 3  Earth Terminal Capacity 3  Earth Terminal Capacity 3  Earth Terminal Capacity 4  Earth Terminal Capacity 4  Earth Terminal Capacity 5  I x 6mm2  Product Class 1  Ambient Operating Temperature  Face plate must be earthed  Ambient Operating Temperature  So to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m  Standard/Approval  Additional Notes  Tungsten filament GU10 lamps must be branded with a fuse base. When using mains voltagehalogen lamps- dimmers should be de-rated by 25%. When dimming LED lamps de-rated by 75% - please contact our Technical for compatibility.  CFX is a Registered Dragous Hardson CFX is a Registered Design under Reference Nos.  R21 = 3023446 SS2 = 3023445  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  BS EN 150 9001 : 2015 Quality Management System.  Due to manufacturing processes we cannot  Correct as at 16 October 2018 12:40 P Eack	Mains Frequency	50Hz		
Terminal Capacity 1 2 x 1.5mm2  Earth Terminal Capacity 2 2 x 1.5mm2  Earth Terminal Capacity 2 4 x 1.5mm2  Earth Terminal Capacity 2 4 x 1.5mm2  Earth Terminal Capacity 3 3 x 2.5mm2  Earth Terminal Capacity 4 1 x 4mm2 Multi-strand  Earth Terminal Capacity 4 1 x 4mm2 Multi-strand  Earth Terminal Capacity 5 1 x 6mm2  Product Class 1 Face plate must be earthed  Ambient Operating Temperature -5° to +40°C  Recommended Location Internal Use Only  Maximum Installation Altitude 2000m  Standard/Approval BS EN 60669-2-1  Additional Notes Tugsten filament GU10 lamps must be branded with a fuse base. When using mains voltagehalogen lamps- dimmers should be de-rated by 25%. When dimming LED lamps de-rated by 75% - please contact our Technical for compatibility.  CFX is a Registered Design under Reference Nos.  R21 = 3023446 SS2 =3023445  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  BEN 100 9001 : 2015 Quality Management System.  Due to manufacturing processes we cannot Correct as at 16 October 2018 12:40 P Each Correct as at 16 October 2018 12:40 P Each Capacity Capacity Correct as at 16 October 2018 12:40 P Each Capacity Capac	IP Rating	IP2XD		
Terminal Capacity 2  Earth Terminal Capacity 1  Earth Terminal Capacity 2  Earth Terminal Capacity 2  Earth Terminal Capacity 2  Earth Terminal Capacity 3  Earth Terminal Capacity 3  Earth Terminal Capacity 4  Earth Terminal Capacity 4  Earth Terminal Capacity 4  Earth Terminal Capacity 5  Product Class 1  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m  Standard/Approval  BS EN 60669-2-1  Tungsten filament GU10 lamps must be branded with a fuse base. When using mains voltagehalogen lamps- dimmers should be de-rated by 25%. When dimming LED lamps de-rated by 75% - please contact our Technical for compatibility.  CFX is a Registered Trade Mark No 2398667  Hartland CFX is a Registered Design under Reference Nos.  R21 = 3023446 SS2 = 3023445  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  BEN ISO 9001 : 2015 Quality Management System.  European standard and the product information is correct at the time of going to press.  Due to manufacturing processes we cannot the limitations of reproduction and printing guarantee an exact colour match and shadings of Correct as at 16 October 2018 12-40 P E&C	Contact Gap Minimum	N/A		
Earth Terminal Capacity 1 5 x 1mm2  Earth Terminal Capacity 2 4 x 1.5mm2  Earth Terminal Capacity 3 3 x 2.5mm2  Earth Terminal Capacity 4 1 x 4mm2 Multi-strand  Earth Terminal Capacity 5 1 x 6mm2  Product Class 1 Face plate must be earthed  Ambient Operating Temperature -5° to +40°C  Recommended Location Internal Use Only  Maximum Installation Altitude 2000m  Standard/Approval BS EN 60669-2-1  Additional Notes Tungsten filament GU10 lamps must be branded with a fuse base. When using mains voltagehalogen lamps- dimmers should be de-rated by 25%. When dimming LED lamps de-rated by 75% - please contact our Technical for compatibility.  CFX is a Registered Trade Mark No 2398667  Hartland CFX is a Registered Design under Reference Nos.  R21 = 3023446 SS2 = 3023445  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited SE EXCENTIAL SET OF THE PROPRIES AND A 18 and 150 a	Terminal Capacity 1	2 x 1mm2		
Earth Terminal Capacity 2  Earth Terminal Capacity 3  Earth Terminal Capacity 4  Earth Terminal Capacity 4  Earth Terminal Capacity 4  Earth Terminal Capacity 5  Product Class 1  Ambient Operating Temperature  Face plate must be earthed  -5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  Standard/Approval  Additional Notes  BS EN 60669-2-1  Tungsten filament GU10 lamps must be branded with a fuse base. When using mains voltagehalogen lamps- dimmers should be de-rated by 25%. When dimming LED lamps de-rated by 75% - please contact our Technical for compatibility.  CFX is a Registered Trade Mark No 2398667  Hartland CFX is a Registered Design under Reference Nos.  R21 = 3023446 SS2 = 3023445  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  But to the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.  Due to manufacturing processes we cannot the limitations of reproduction and printing guarantee an exact colour match and shadings of	Terminal Capacity 2	2 x 1.5mm2		
Earth Terminal Capacity 3  Earth Terminal Capacity 4  Earth Terminal Capacity 4  Earth Terminal Capacity 5  Product Class 1  Ambient Operating Temperature  Recommended Location  Maximum Installation Altitude  Standard/Approval  Additional Notes  BS EN 6069-2-1  Tungsten filament GU10 lamps must be branded with a fuse base. When using mains voltagehalogen lamps- dimmers should be de-rated by 25%. When dimming LED lamps de-rated by 75% - please contact our Technical for compatibility.  CFX is a Registered Trade Mark No 2398667  Hartland CFX is a Registered Design under Reference Nos.  R21 = 3023446 SS2 = 3023445  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  But is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.  Due to manufacturing processes we cannot guarantee an exact colour match and shadings of  EXCORDANG AND TOTAL TOTA	Earth Terminal Capacity 1	5 x 1mm2		
Earth Terminal Capacity 4  Earth Terminal Capacity 5  Product Class 1  Ambient Operating Temperature  Recommended Location  Internal Use Only  Maximum Installation Altitude  Standard/Approval  Additional Notes  BS EN 60669-2-1  Tungsten filament GU10 lamps must be branded with a fuse base. When using mains voltagehalogen lamps- dimmers should be de-rated by 25%. When dimming LED lamps de-rated by 75% - please contact our Technical for compatibility.  CFX is a Registered Trade Mark No 2398667  Harland CFX is a Registered Design under Reference Nos.  R21 = 3023446 SS2 = 3023445  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter designs and dimensions without prior notice.  Due to manufacturing processes we cannot the limitations of reproduction and printing guarantee an exact colour match and shadings of  Correct as at 16 October 2018 12:40 P EXC	Earth Terminal Capacity 2	4 x 1.5mm2		
Earth Terminal Capacity 5  Product Class 1  Ambient Operating Temperature  Ambient Operating Temperature  As on the product Class 1  Ambient Operating Temperature  As on the product Class 1  Additional Notes  Additional Notes  BS EN 60669-2-1  Tungsten filament GU10 lamps must be branded with a fuse base. When using mains voltagehalogen lamps- dimmers should be de-rated by 25%. When dimming LED lamps de-rated by 75% - please contact our Technical for compatibility.  CFX is a Registered Trade Mark No 2398667  Hartland CFX is a Registered Trade Mark No 2398667  Hartland CFX is a Registered Design under Reference Nos. R21 = 3023446 SS2 = 30234445  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Blustrations and diagrams are reproduced within the limitations of reproduction and printing guarantee an exact colour match and shadings of  Correct as at 16 October 2018 12:40 P guarantee an exact colour match and shadings of	Earth Terminal Capacity 3	3 x 2.5mm2		
Product Class 1  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m  Standard/Approval  BS EN 6069-2-1  Additional Notes  Additional Notes  Tungsten filament GU10 lamps must be branded with a fuse base. When using mains voltagehalogen lamps- dimmers should be de-rated by 25%. When dimming LED lamps de-rated by 75% - please contact our Technical for compatibility.  CFX is a Registered Trade Mark No 2398667  Hartland CFX is a Registered Design under Reference Nos.  R21 = 3023446 SS2 = 3023445  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter designs and dimensions without prior notice.  Due to manufacturing processes we cannot guarantee an exact colour match and shadings of  Correct as at 16 October 2018 12:40 P EXC	Earth Terminal Capacity 4	1 x 4mm2 Multi-strand		
Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m  Standard/Approval  BS EN 60669-2-1  Additional Notes  Tungsten filament GU10 lamps must be branded with a fuse base. When using mains voltagehalogen lamps- dimmers should be de-rated by 25%. When dimming LED lamps de-rated by 75% - please contact our Technical for compatibility.  CFX is a Registered Trade Mark No 2398667  Hartland CFX is a Registered Design under Reference Nos. R21 = 3023446 SS2 = 3023445  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Illustrations and diagrams are reproduced within the limitations of reproduction and printing  Due to manufacturing processes we cannot guarantee an exact colour match and shadings of  Correct as at 16 October 2018 12:40 P E&C	Earth Terminal Capacity 5	1 x 6mm2		
Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m  Standard/Approval  Additional Notes  BS EN 60669-2-1  Additional Notes  Tungsten filament GU10 lamps must be branded with a fuse base. When using mains voltagehalogen lamps- dimmers should be de-rated by 25%. When dimming LED lamps de-rated by 75% - please contact our Technical for compatibility.  CFX is a Registered Trade Mark No 2398667  Hartland CFX is a Registered Design under Reference Nos.  R21 = 3023446 SS2 = 3023445  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Illustrations and diagrams are reproduced within the limitations of reproduction and printing  Due to manufacturing processes we cannot guarantee an exact colour match and shadings of  Correct as at 16 October 2018 12:40 P ESC	Product Class 1	Face plate must be earthed	Face plate must be earthed	
Maximum Installation Altitude  Standard/Approval  BS EN 60669-2-1  Additional Notes  Tungsten filament GU10 lamps must be branded with a fuse base. When using mains voltagehalogen lamps- dimmers should be de-rated by 25%. When dimming LED lamps de-rated by 75% - please contact our Technical for compatibility.  CFX is a Registered Trade Mark No 2398667  Hartland CFX is a Registered Design under Reference Nos.  R21 = 3023446 SS2 = 3023445  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Illustrations and diagrams are reproduced within the limitations of reproduction and printing  Due to manufacturing processes we cannot guarantee an exact colour match and shadings of  Correct as at 16 October 2018 12:40 P E&C	Ambient Operating Temperature	-5° to +40°C		
Standard/Approval  BS EN 60669-2-1  Additional Notes  Tungsten filament GU10 lamps must be branded with a fuse base. When using mains voltagehalogen lamps- dimmers should be de-rated by 25%. When dimming LED lamps de-rated by 75% - please contact our Technical for compatibility.  CFX is a Registered Trade Mark No 2398667  Hartland CFX is a Registered Design under Reference Nos. R21 = 3023446 SS2 = 3023445  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Illustrations and diagrams are reproduced within the limitations of reproduction and printing guarantee an exact colour match and shadings of  E&C  CFX is a Registered Trade Mark No 2398667  Hartland CFX is a Registered Design under Reference Nos. R21 = 3023446 SS2 = 3023445  All accessories are manufactured under an accredited as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.  Due to manufacturing processes we cannot guarantee an exact colour match and shadings of  Correct as at 16 October 2018 12:40 P E&C	Recommended Location	Internal Use Only		
Additional Notes  Tungsten filament GU10 lamps must be branded with a fuse base. When using mains voltagehalogen lamps- dimmers should be de-rated by 25%. When dimming LED lamps de-rated by 75% - please contact our Technical for compatibility.  CFX is a Registered Trade Mark No 2398667 Hartland CFX is a Registered Design under Reference Nos. R21 = 3023446 SS2 = 3023445  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Illustrations and diagrams are reproduced within the limitations of reproduction and printing  Due to manufacturing processes we cannot guarantee an exact colour match and shadings of  Correct as at 16 October 2018 12:40 P E&C	Maximum Installation Altitude	2000m		
Additional Notes  should be de-rated by 25%. When dimming LED lamps de-rated by 75% - please contact our Technical for compatibility.  CFX is a Registered Trade Mark No 2398667 Hartland CFX is a Registered Design under Reference Nos. R21 = 3023446 SS2 =3023445  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Illustrations and diagrams are reproduced within the limitations of reproduction and printing  Due to manufacturing processes we cannot guarantee an exact colour match and shadings of  Correct as at 16 October 2018 12:40 P E&C	Standard/Approval	BS EN 60669-2-1		
Patents and Trademarks  Hartland CFX is a Registered Design under Reference Nos. R21 = 3023446 SS2 =3023445  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Illustrations and diagrams are reproduced within the limitations of reproduction and printing  Due to manufacturing processes we cannot guarantee an exact colour match and shadings of  E&C	Additional Notes	should be de-rated by 25%. When dimming LED lamps de-rated by 75% - please contact our Technical for compatibility.		
European standard and the product information is correct at the time of going to press.  BS EN ISO 9001 : 2015 Quality Management System.  BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter designs and dimensions without prior notice.  Illustrations and diagrams are reproduced within the limitations of reproduction and printing guarantee an exact colour match and shadings of E&C	Patents and Trademarks	Hartland CFX is a Registered Design under Reference Nos.		
the limitations of reproduction and printing guarantee an exact colour match and shadings of E&C	European standard and the product information is		as part of our development programme. Therefore, we reserve the right to alter designs	
R Hamilton & Co Ltd. Unit 10 Carrick Business Centre. 4-5 Bonville Road. Bristington Bristol. BS4 5N7	the limitations of reproduction and printing	guarantee an exact colour match and shadings of	Correct as at 16 October 2018 12:40 PM E&OE	

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84















Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio