SL

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

7EBC2J45B

Hartland CEV Etrium Pronze 2 gong P ME CAT SE Outlet | Unchielded Plack

	Hartland CFX Etrium Bronze 2 gang RJ45 CAT 5E Outlet - Unshielded Black			
Primary Range Hartland CFX Insert Type 2 gang R.45 CAT 5E Outlet - Unshielded Plate Finish Hartland CFX Firium Bronze Insert Colour Black EAN13 Barcode 50175A011611 Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm Fixing Hole Centres Box Fixing = 80.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth Switched Poles N/A IP Rating IP2XD Contact Gap Minimum NA Earth Terminal Capacity 1 5 x fmm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 1 x fmm2 Earth Terminal Capacity 4 1 x fmm2 Earth Terminal Capacity 5 1 x fmm2 Earth Terminal Capacity 5 1 x fmm2 Earth Terminal Capacity 6 1 x fmm2 Earth Terminal Capacity 6 1 x fmm2 Earth Terminal Capacity 9 1 x fmm2 Earth Terminal	Item Image	Wiring	Dimensions	
Primary Range Hartland CFX Insert Type 2 gang RJ45 CAT 5E Outlet - Unshielded Plate Finish Hartland CFX Insert Colour Black EAN13 Barcode 5017504011611 Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35.mm Switched Poles N/A IP Rating IP2XD Contact Gap Minimum NA Earth Terminal Capacity 1 5x tmm2 Earth Terminal Capacity 1 5x tmm2 Earth Terminal Capacity 2 4x 1.5mm2 Earth Terminal Capacity 3 3x 2.5mm2 Earth Terminal Capacity 5 1x 6mm2 Froduct Class 1 Must be earthed (ref BS7671 415.2.1) Ambient Operating Temperature 5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m EuroFix Additional Notes Can be used in both EIA 568A and EIA 568B writing schedules CFX is a Registered Trade Mark No 2398667 Hartland CFX is a Registered Teade Mark No 2398667 EuroFix Additional Notes Can be used in both EIA 568A and EIA 568B writing schedules CFX is a Registered Teade Mark No 2398667 Hartland CFX is a Registered Teade Mark No 2398667 Hartland CFX is a Registered Teade Mark No 2398667 Hartland CFX is a Registered Teade Mark No 2398667 Hartland CFX is a Registered Teade Mark No 2398667 Hartland CFX is a Registered Teade Mark No 2398667 Hartland CFX is a Registered Teade Mark No 2398667 Hartland CFX is a Registered Teade Mark No 2398667 Hartland CFX is a Registered Teade Mark No 2398667 Hartland CFX is a Registered Teade Mark No 2398667 Hartland CFX is a Registered Teade Mark No 2398667 Hartland CFX is a Registered Teade Mark No 2398667 Hartland CFX is a Registered Teade Mark No 2398667 Hartland CFX is a Registered Teade Mark No 2398667 Hartland CFX is a Registered Teade Mark No 2398667 Hartland CFX is a Registered Teade Mark No 2398667 Hartland CFX is a Registered Teade Mark No 2398667 Hartland Colour and Hartland Marked			HARTLAND CFX 2J45	
Insert Type		Fin ELA Writing Scheduler Colour Codes No. Shortender fields. Scheduler Colour Codes No. Shortender fields. Scheduler Colour Codes Well El Common Well El Corrace Well El Common Well El Corrace South El Common Bull With Common Bull With White O CARAGE! White Well El South With Colour Shorten CAPITALS. Pelson description of CAPITALS.	15.0	
Plate Finish Hartland CFX Etrium Bronze Insert Colour Black EAN13 Barcode 5017504011611 Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Switched Poles N/A IP Rating IP2XD Contact Gap Minimum N/A Earth Terminal Capacity 1 5 x Imm2 Earth Terminal Capacity 1 5 x Imm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 1 x 4mm2 Multi-strand Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed (ref BS7671 415.2.1) Ambient Operating Temperature 5-5* to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m EuroFix Additional Notes Can be used in both EIA 568A and EIA 568B wiriing schedules CFX is a Registered Trade Mark No 2398667 Hartland CFX is a Registered Design under Reference Nos. R21 = 3023446 SS2 = 3023445 It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Einstance of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Ellustrations and diagrams are reproduced within the limitations of reproduction mining guarantee an exact colour match and stadings of Correct as at 16 October 2018 124.	Primary Range	Hartland CFX		
Insert Colour	Insert Type	2 gang RJ45 CAT 5E Outlet - Unshielded		
EAN13 Barcode 5017504011611 Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Switched Poles N/A IP Rating IP2XD Contact Gap Minimum N/A Earth Terminal Capacity 1 5x 1mm2 Earth Terminal Capacity 2 4x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 1x 6mm2 Earth Terminal Capacity 4 1x 4mm2 Multi-strand Earth Terminal Capacity 5 1x 6mm2 Product Class 1 Must be earthed (ref BS7671 415.2.1) Ambient Operating Temperature -5* to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m EuroFix Additional Notes Can be used in both EIA 568A and EIA 568B wirring schedules CFX is a Registered Trade Mark No 2398667 Patents and Trademarks Can be used in both EIA 568A and EIA 568B wirring schedules CFX is a Registered Trade Mark No 2398667 Faltanal CFX is a Registered Trade	Plate Finish	Hartland CFX Etrium Bronze		
Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth Somm Switched Poles N/A Width = 86.0mm Width = 86.0mm Depth = 5.0mm N/A Width = 86.0mm Width = 86.0mm Depth = 5.0mm Somm Switched Poles N/A Width = 86.0mm Width = 86.0mm Depth = 5.0mm Somm Switched Poles N/A Parting Contact Gap Minimum N/A Earth Terminal Capacity 1 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 1 x 6mm2 Froduct Class 1 Must be earthed (ref BS7671 415.2.1) Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m EuroFix Additional Notes Can be used in both EIA 568A and EIA 568B wirring schedules CFK is a Registered Trade Mark No 2398667 Hartland CFK is a Registered Design under Reference Nos. R21 = 3023446 SS2 = 3023445 All products listed conform to current British or European standard and the product information is Correct at the time of going to press. All products listed conform to current British or European standard and the product information is Correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. Therefore, we reserve the right to alter designs and dimensions without prior notice. Therefore, we reserve the right to alter designs and dimensions without prior notice. Therefore, we reserve the right to alter designs and dimensions without prior notice. Therefore, we reserve the right to alter designs and dimensions without prior notice. Therefore, we reserve the right to alter designs and dimensions without prior notice. Therefore, we reserve the right to alter designs and dimensions without prior notice.	Insert Colour	Black		
Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm N/A IP Rating IP2XD Contact Gap Minimum N/A Earth Terminal Capacity 1 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 4 1 x xmm2 Multi-strand Earth Terminal Capacity 4 Earth Terminal Capacity 5 1 x 6mm2 Froduct Class 1 Must be earthed (ref BS7671 415.2.1) Ambient Operating Temperature Recommended Location Internal Use Only Maximum Installation Altitude EuroFix Additional Notes Can be used in both EIA 568A and EIA 568B wirring schedules CFX is a Registered Trade Mark No 2398667 Hartland CFX is a Registered Design under Reference Nos. R21 = 3023446 SS2 = 3023445 All products listed conform to current British or European standard and the product information is correct at the time of going to press. Business of eproduction and printing Due to manufacturing processes we cannot Correct as at 16 October 2018 12.41 Earth Terminal Capacity 3 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 For 0+40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m EuroFix Additional Notes Can be used in both EIA 568A and EIA 568B wirring schedules CFX is a Registered Design under Reference Nos. R21 = 3023446 SS2 = 3023445 All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 3 Eart	EAN13 Barcode	5017504011611		
Minimum Wall Box Depth Switched Poles N/A IP Rating IP2XD Contact Gap Minimum Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 2 Earth Terminal Capacity 3 S x 1mm2 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Ix 4mm2 Multi-strand Earth Terminal Capacity 5 Froduct Class 1 Must be earthed (ref BS7671 415.2.1) Ambient Operating Temperature Recommended Location Internal Use Only Maximum Installation Altitude EuroFix Additional Notes Can be used in both EIA 568A and EIA 568B wirling schedules CFX is a Registered Trade Mark No 2398667 Hartland CFX is a Registered Trade Mark No 2398667 Hartland CFX is a Registered Testign under Reference Nos. R21 = 3023446 SS2 = 3023445 All products listed conform to current British or European standard and the product information is correct at the time of going to press. BEN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing guarantee an exact colour match and shadings of European standard and match and the product match and shadings of	Dimensions (Nominal)	Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm		
Switched Poles N/A IP Rating IP2XD Contact Gap Minimum N/A Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed (ref BS7671 415.2.1) Ambient Operating Temperature 5 to 40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m EuroFix Additional Notes Can be used in both EIA 568A and EIA 568B wirring schedules CFX is a Registered Trade Mark No 2398667 Hartland CFX is a Registered Design under Reference Nos. R21 = 3023446 SS2 = 3023445 All products listed conform to current British or European standard and the product information is correct at the time of going to press. BS EN ISO 9001 : 2015 Quality Management System. Due to manufacturing processes we cannot the limitations of reproduction and printing guarantee an exact colour match and shadings of Correct as at 16 October 2018 12-41 Earth Terminal Capacity 1	Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips		
IP Rating	Minimum Wall Box Depth	35mm		
Contact Gap Minimum N/A Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed (ref BS7671 415.2.1) Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m EuroFix Additional Notes Can be used in both EIA 568A and EIA 568B wirring schedules CFX is a Registered Trade Mark No 2398667 Hartland CFX is a Registered Design under Reference Nos. R21 = 3023446 SS2 = 3023445 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. Due to manufacturing processes we cannot the limitations of reproduction and printing guarantee an exact colour match and shadings of Correct as at 16 October 2018 12-81 guarantee an exact colour match and shadings of Correct as at 16 October 2018 12-81	Switched Poles	N/A		
Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed (ref BS7671 415.2.1) Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m EuroFix Additional Notes Can be used in both EIA 568A and EIA 568B wirring schedules Patents and Trademarks CFX is a Registered Trade Mark No 2398667 Hartland CFX is a Registered Design under Reference Nos. R21 = 3023446 SSZ = 3023445 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing guarantee an exact colour match and shadings of Correct as at 16 October 2018 12:41	IP Rating	IP2XD		
Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Product Class 1 Ambient Operating Temperature As 2000m Recommended Location Internal Use Only Maximum Installation Altitude EuroFix Additional Notes Can be used in both EIA 568A and EIA 568B wiring schedules CFX is a Registered Trade Mark No 2398667 Hartland CFX is a Registered Design under Reference Nos. R21 = 3023446 All products listed conform to current British or European standard and the product information is correct at the time of going to press. Blustrations and diagrams are reproduced within the limitations of reproduction and printing guarantee an exact colour match and shadings of Earth Terminal Capacity 3 3 x 2.5mm2 1 x 4mm2 Multi-strand 1 x 6mm2 Product Class 1 Car be used in both EIA 568B wiring schedules CFX is a Registered Trade Mark No 2398667 Hartland CFX is a Registered Design under Reference Nos. R21 = 3023446 BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. Correct as at 16 October 2018 12:41 Earth Terminal Capacity 3 2 x 4 mm2 All accessories are manufacturing processes we cannot guarantee an exact colour match and shadings of Earth Terminal Capacity 4 Earth Terminal Capacity 5 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Earth Terminal Capacity 5 Earth Terminal Capacity 5 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Earth Terminal Cap	Contact Gap Minimum	N/A		
Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Product Class 1 Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude EuroFix Additional Notes Can be used in both EIA 568A and EIA 568B wirring schedules CFX is a Registered Trade Mark No 2398667 Hartland CFX is a Registered Design under Reference Nos. R21 = 3023446 SS2 = 3023445 All products listed conform to current British or European standard and the product information is correct at the time of going to press. Bllustrations and diagrams are reproduced within the limitations of reproduction and printing guarantee an exact colour match and shadings of E8 Correct as at 16 October 2018 12:41 Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 16 October 2018 12:41 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 4mm2 Multi-strand 2 x 4mm2 Multi-strand Earth Terminal Capacity 4 1 x 4mm2 Multi-strand 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 4mm2 Earth Terminal Capacity 5 1 x 4mm2 Earth Terminal Capacity 5 1 x 4mm2 Earth Terminal Capacity 5 Earth Terminal Capaci	Earth Terminal Capacity 1	5 x 1mm2		
Earth Terminal Capacity 4 Earth Terminal Capacity 5 Product Class 1 Ambient Operating Temperature Fecommended Location Must be earthed (ref BS7671 415.2.1) Ambient Operating Temperature Fecommended Location Internal Use Only Maximum Installation Altitude EuroFix Additional Notes Can be used in both EIA 568A and EIA 568B wiriing schedules CFX is a Registered Trade Mark No 2398667 Hartland CFX is a Registered Design under Reference Nos. R21 = 3023446 SS2 = 3023445 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All products listed conform to current British or European standard and the product information is correct at the time of going to press. Bllustrations and diagrams are reproduced within the limitations of reproduction and printing Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 16 October 2018 12:41 Earth Terminal Capacity 5 It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Correct as at 16 October 2018 12:41 Earth Terminal Capacity 5 It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Correct as at 16 October 2018 12:41	Earth Terminal Capacity 2	4 x 1.5mm2		
Earth Terminal Capacity 5 Product Class 1 Must be earthed (ref BS7671 415.2.1) Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m EuroFix Additional Notes Can be used in both EIA 568A and EIA 568B wiring schedules CFX is a Registered Trade Mark No 2398667 Hartland CFX is a Registered Design under Reference Nos. R21 = 3023446 SS2 = 3023445 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. BS EN ISO 9001 : 2015 Quality Management System. Due to manufacturing processes we cannot freefore, we reserve the right to alter designs and dimensions without prior notice. Correct as at 16 October 2018 12:41 Eaguarantee an exact colour match and shadings of	Earth Terminal Capacity 3	3 x 2.5mm2		
Product Class 1 Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m EuroFix Additional Notes Can be used in both EIA 568A and EIA 568B wiriing schedules CFX is a Registered Trade Mark No 2398667 Hartland CFX is a Registered Design under Reference Nos. R21 = 3023446 SS2 = 3023445 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. But to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 16 October 2018 12:41 East of the Hart System of the Company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.	Earth Terminal Capacity 4	1 x 4mm2 Multi-strand		
Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m EuroFix Additional Notes Can be used in both EIA 568A and EIA 568B wiriing schedules CFX is a Registered Trade Mark No 2398667 Hartland CFX is a Registered Design under Reference Nos. R21 = 3023446 SS2 = 3023445 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All products listed conform to current British or European standard and the product information is correct at the time of going to press. Illustrations and diagrams are reproduced within the limitations of reproduction and printing Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 16 October 2018 12:41	Earth Terminal Capacity 5	1 x 6mm2		
Recommended Location Internal Use Only Maximum Installation Altitude 2000m EuroFix Additional Notes Can be used in both EIA 568A and EIA 568B wiriing schedules CFX is a Registered Trade Mark No 2398667 Hartland CFX is a Registered Design under Reference Nos. R21 = 3023446 SS2 = 3023445 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All products listed conform to current British or European standard and the product information is correct at the time of going to press. Illustrations and diagrams are reproduced within the limitations of reproduction and printing Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 16 October 2018 12:41 E8	Product Class 1	Must be earthed (ref BS7671 415.2.1)	Must be earthed (ref BS7671 415.2.1)	
Maximum Installation Altitude EuroFix Additional Notes Can be used in both EIA 568A and EIA 568B wiriing schedules CFX is a Registered Trade Mark No 2398667 Hartland CFX is a Registered Design under Reference Nos. R21 = 3023446	Ambient Operating Temperature	-5° to +40°C		
EuroFix Additional Notes Can be used in both EIA 568A and EIA 568B wiriing schedules CFX is a Registered Trade Mark No 2398667 Hartland CFX is a Registered Design under Reference Nos. R21 = 3023446 SS2 = 3023445 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 16 October 2018 12:41	Recommended Location	Internal Use Only		
Patents and Trademarks CFX is a Registered Trade Mark No 2398667 Hartland CFX is a Registered Design under Reference Nos. R21 = 3023446 SS2 = 3023445 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing Therefore, we reserve the right to alter designs and dimensions without prior notice. Correct as at 16 October 2018 12:41 E8	Maximum Installation Altitude	2000m		
Patents and Trademarks Hartland CFX is a Registered Design under Reference Nos. R21 = 3023446 SS2 = 3023445 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 16 October 2018 12:41 E8	EuroFix Additional Notes	Can be used in both EIA 568A and EIA 568B wiriing schedules		
European standard and the product information is correct at the time of going to press. BS EN ISO 9001 : 2015 Quality Management System. BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. Illustrations and diagrams are reproduced within the limitations of reproduction and printing guarantee an exact colour match and shadings of	Patents and Trademarks	Hartland CFX is a Registered Design under Reference Nos.		
the limitations of reproduction and printing guarantee an exact colour match and shadings of E8	European standard and the product information is		as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.	
R Hamilton & Co. Ltd. Unit 10 Carrick Rusiness Centre 4-5 Ronville Road. Riskington Rristol. RS/15N7	the limitations of reproduction and printing	guarantee an exact colour match and shadings of	Correct as at 16 October 2018 12:41 PM E&OE	

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84









