

SL

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

7G24R22SS-W

Item Image Wiring Dimensions Harmitton Warthung of Primary Range Insert Type 2 gang 10AX 2 Way Rocker Plate Finish Hartland 62 Safin Stainless Steel Insert Type 1 Safin Stainless Steel EANY 3 Barcodo Safin Stainless Steel EANY 3 Barcodo Safin Stainless Steel Luckers Tsi University Tsi University Tsi University Tsi University Tsi Box Fixing - 80.3mm Winthum Wall Box Depth Songe - Height - 87.4mm Wolth - 87.4mm Depth - 4.65mm Fixing Hole Certies Box Fixing - 80.3mm Minimum Wall Box Depth Single Current Rating 10AX Current Rating 10AX 10 Amp Inductive Massir Fixing - 10.2mm Massir Fixing - 10.2mm Terminal Capacity 1 Terminal Capacity 1 Terminal Capacity 1 Terminal Capacity 3 1 x 4 mm 2 Terminal Capacity 3 1 x 4 mm 2 Earth Terminal Capacity 4 1 x 4 mm 2 Earth Terminal Capacity 5 Earth Terminal Capacity 6 Earth Terminal Capacity 5 Earth Terminal Capacity 6 Earth Terminal Capacity 1 Earth Terminal Capacity 1 Earth Terminal Capacity 1 Earth Terminal Capacity 5 Earth Terminal Capacity 1 Earth	7G24R22SS-W Hartland G2 Satin Stainless Steel 2 gang 10AX 2 Way Rocker Satin Stainless Steel/White				
Primary Range	Item Image	Wiring	Dimensions		
Insert Type		Abarative 2 way sentaining Loop In Long Old James San	R22 2 Way Rocker		
Plate Finish	Primary Range	Hartland G2			
Satin Stainless Steel/White	Insert Type	2 gang 10AX 2 Way Rocker			
EAN13 Barcode 5051164002190 Commodity Code 85383010 Luckins TSI 407520727 Dimensions (Nominal) Single: Helight = 87.4mm Width = 87.4mm Depth = 4.65mm Fixing Hole Centres Box Fixing = 60.3mm Minimum Wall Box Depth 25mm Switched Poles Single Current Rating 10AX Voltage 120/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5 x mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 1 x 2.5mm2 Terminal Capacity 4 1 x 4mm2 Multi-strand Terminal Capacity 1 5 x 1 mm2 Earth Terminal Capacity 4 1 x 4 mm2 Multi-strand Earth Terminal Capacity 5 1 x 2.5mm2 Earth Terminal Capacity 4 1 x 4 mm2 Multi-strand Earth Terminal Capacity 4 1 x 4 mm2 Multi-strand Earth Terminal Capacity 4 1 x 4 mm2 Multi-strand Earth Terminal Capacity 4 1 x 4 mm2 Multi-strand Earth Terminal Capacity 4 1 x 4 mm2 Multi-strand Earth Terminal Capacity 5 1 x 6 mm2 Earth Terminal Capacity 4 1 x 4 mm2 Multi-strand Earth Terminal Capacity 5 1 x 6 mm2 Earth Terminal Capacity 5 1 x 6 mm2 Earth Terminal Capacity 6 1 x 6 mm2 Earth Terminal Capacity 7 5 x 1 mm2 Earth Terminal Capacity 6 1 x 6 mm2 Earth Terminal Capacity 7 5 x 1 mm2 Earth Terminal Capacity 6 1 x 6 mm2 Earth Terminal Capacity 7 5 x 6 mm2 Earth Terminal Capacity 6 1 x 6 mm2 Earth Terminal Capacity 7 5 x 6 mm2 Earth Terminal Capacity 8 1 x 6 mm2 Earth Terminal Capacity 9 1 x 6 mm2 Earth Terminal Ca	Plate Finish				
Commodity Code	Insert Colour	Satin Stainless Steel/White			
Luckins TSI	EAN13 Barcode	5051164002190			
Dimensions (Nominal) Single: Height = 87.4mm Width = 87.4mm Depth = 4.65mm	Commodity Code				
Fixing Hole Centres	Luckins TSI	407520727			
Minimum Wall Box Depth 25mm Switched Poles Single Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 1 x 2.5mm2 Terminal Capacity 4 1 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m	Dimensions (Nominal)	Single: Height = 87.4mm Width = 87.4mm Depth = 4.65mm			
Switched Poles Single Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 1 x 2.5mm2 Terminal Capacity 4 1 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Restrict Capacity 5 1 x 6mm2 Restrict Capacity 6 1 x 6mm2 Restric	Fixing Hole Centres				
Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 1 x 2.5mm2 Terminal Capacity 4 1 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Forduct Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m	Minimum Wall Box Depth	25mm			
Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 1 x 2.5mm2 Terminal Capacity 4 1 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m	Switched Poles	Single			
Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 1 x 2.5mm2 Terminal Capacity 4 1 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature -5" to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m	Current Rating	10AX			
Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 1 x 2.5mm2 Terminal Capacity 4 1 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m	Voltage	220/250V AC			
IP Rating	Maximum Load	10 Amp inductive			
Contact Gap Minimum 3mm Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 1 x 2.5mm2 Terminal Capacity 4 1 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Forduct Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m	Mains Frequency	50Hz			
Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 1 x 2.5mm2 Terminal Capacity 4 1 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m	IP Rating	IP2XD			
Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 1 x 2.5mm2 Terminal Capacity 4 1 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m	Contact Gap Minimum	3mm			
Terminal Capacity 3 Terminal Capacity 4 1 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude	Terminal Capacity 1	5 x 1mm2			
Terminal Capacity 4 1 x 4mm2 Multi-strand 1 x 6mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Ambient Operating Temperature 75° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 1 x 4mm2 Multi-strand Internal Use Only Maximum Installation Altitude	Terminal Capacity 2	4 x 1.5mm2			
Terminal Capacity 5 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Tx 4mm2 Multi-strand Earth Terminal Capacity 5 Tx 6mm2 Product Class 1 Ambient Operating Temperature Ambient Operating Temperature For to +40°C Recommended Location Maximum Installation Altitude Internal Use Only Maximum Installation Altitude	Terminal Capacity 3	1 x 2.5mm2			
Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m	Terminal Capacity 4	1 x 4mm2 Multi-strand			
Earth Terminal Capacity 2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Ambient Operating Temperature Recommended Location Maximum Installation Altitude 4 x 1.5mm2 1 x 4mm2 Multi-strand 1 x 6mm2 Must be earthed -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude	Terminal Capacity 5	1 x 6mm2			
Earth Terminal Capacity 3 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Ambient Operating Temperature Recommended Location Maximum Installation Altitude 3 x 2.5mm2 1 x 6mm2 Must be earthed -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude	Earth Terminal Capacity 1	5 x 1mm2			
Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m	Earth Terminal Capacity 2	4 x 1.5mm2			
Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m	Earth Terminal Capacity 3	3 x 2.5mm2			
Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m	· · ·	1 x 4mm2 Multi-strand			
Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m	Earth Terminal Capacity 5	1 x 6mm2			
Recommended Location Internal Use Only Maximum Installation Altitude 2000m		Must be earthed			
Maximum Installation Altitude 2000m	Ambient Operating Temperature	-5° to +40°C			
	Recommended Location	·			
	Maximum Installation Altitude	2000m			
Standard/Approval BS EN 60669-1	Standard/Approval	BS EN 60669-1			



SL

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio				
7G24R22SS-W Hartland G2 Satin Stainless Steel 2 gang 10AX 2 Way Rocker Satin Stainless Steel/White				
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.		
Illustrations and diagrams are reproduced within the limitations of reproduction and printing	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of	Correct as at 14 August 2019 04:04 PM E&OE		

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84









