

SL

## making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

## 7G29R22AB-B

| Primary Range  | 7G29R22AB-B  Hartland G2 Antique Brass 2 gang 10AX 2 Way Rocker Antique Brass/Black |   |                     |  |  |
|--|---|---|---------------------|--|--|
| Primary Range  |   |   |                     |  |  |
| Insert Type  |   | Abernativa 2 way swatzing                             | R22<br>2 Way Rocker |  |  |
| Plate Finish   | Primary Range   | Hartland G2   |                     |  |  |
| Insert Colour  | Insert Type   | 2 gang 10AX 2 Way Rocker                              |                     |  |  |
| EAN13 Barcode 5051164003210 Commodity Code 885383010 Luckins TSI 407519275 Dimensions (Nominal) Single: Height = 87.4mm Width = 87.4mm Depth = 4.65mm Fixing Hole Centres Box Fixing = 60.3mm Minimum Wall Box Depth 25mm Switched Poles Single Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5 x 1mm2 Terminal Capacity 3 1 x 2.5mm2 Terminal Capacity 3 1 x 4mm2 Multi-strand Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 3 1 x 6mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 6 1 x 4mm2 Earth Terminal Capacity 6 1 x 6mm2 Earth Terminal Capacity 6 1 x 4mm2 Earth Terminal Capacity 7 5 x 1mm2 Earth Terminal Capacity 8 3 x 2.5mm2 Earth Terminal Capacity 9 1 x 4mm2 Multi-strand Earth Terminal Capacity 6 1 x 6mm2 Earth Terminal Capacity 7 5 x 1 x 6mm2 Earth Terminal Capacity 8 1 x 6mm2 Earth Terminal Capacity 9 1 x 6mm2 Ear | Plate Finish  | Hartland G2 Antique Brass                             |                     |  |  |
| Commodity Code   | Insert Colour   | Antique Brass/Black                                   |                     |  |  |
| Luckins TSI         407519275           Dimensions (Nominal)         Single: Height = 87.4mm Width = 87.4mm Depth = 4.65mm           Fixing Hole Centres         Box Fixing = 60.3mm           Minimum Wall Box Depth         25mm           Switched Poles         Single           Current Rating         10AX           Voltage         220/250V AC           Maximum Load         10 Amp inductive           Mains Frequency         50Hz           IP Rating         IP2XD           Contact Gap Minimum         3mm           Terminal Capacity 1         5 x 1mm2           Terminal Capacity 2         4 x 1.5mm2           Terminal Capacity 3         1 x 2.5mm2           Terminal Capacity 4         1 x 4mm2 Multi-strand           Terminal Capacity 5         1 x 6mm2           Earth Terminal Capacity 2         4 x 1.5mm2           Earth Terminal Capacity 3         3 x 2.5mm2           Earth Terminal Capacity 4         1 x 4mm2 Multi-strand           Earth Terminal Capacity 5         1 x 6mm2           Earth Terminal Capacity 4         1 x 4mm2 Multi-strand           Earth Terminal Capacity 5         1 x 6mm2           Earth Terminal Capacity 4         1 x 4mm2 Multi-strand           Earth Terminal Capacity 4  | EAN13 Barcode   | 5051164003210   |                     |  |  |
| Dimensions (Nominal)         Single: Height = 87.4mm Width = 87.4mm Depth = 4.65mm           Fixing Hole Centres         Box Fixing = 60.3mm           Minimum Wall Box Depth         25mm           Switched Poles         Single           Current Rating         10AX           Voltage         220/250V AC           Maximum Load         10 Amp inductive           Mains Frequency         50Hz           IP Rating         IP2XD           Contact Gap Minimum         3mm           Terminal Capacity 1         5 x 1mm2           Terminal Capacity 2         4 x 1.5mm2           Terminal Capacity 3         1 x 2.5mm2           Terminal Capacity 4         1 x 4mm2 Multi-strand           Terminal Capacity 5         1 x 6mm2           Earth Terminal Capacity 1         5 x 1mm2           Earth Terminal Capacity 3         3 x 2.5mm2           Earth Terminal Capacity 3         3 x 2.5mm2           Earth Terminal Capacity 4         1 x 4mm2 Multi-strand           Earth Terminal Capacity 5         1 x 6mm2           Product Class 1         Must be earthed           Ambient Operating Temperature         -5° to +40°C           Recommended Location         Internal Use Only  | Commodity Code  | 85363010  |                     |  |  |
| Fixing Hole Centres         Box Fixing = 60.3mm           Minimum Wall Box Depth         25mm           Switched Poles         Single           Current Rating         10AX           Voltage         220/250V AC           Maximum Load         10 Amp inductive           Mains Frequency         50Hz           IP Rating         IP2XD           Contact Gap Minimum         3mm           Terminal Capacity 1         5 x 1mm2           Terminal Capacity 2         4 x 1.5mm2           Terminal Capacity 3         1 x 2.5mm2           Terminal Capacity 4         1 x 4mm2 Multi-strand           Terminal Capacity 5         1 x 6mm2           Earth Terminal Capacity 1         5 x 1mm2           Earth Terminal Capacity 3         3 x 2.5mm2           Earth Terminal Capacity 3         3 x 2.5mm2           Earth Terminal Capacity 4         1 x 4mm2 Multi-strand           Earth Terminal Capacity 5         1 x 6mm2           Product Class 1         Must be earthed           Auximum Installation Altitude         2000m   | Luckins TSI   | 407519275   |                     |  |  |
| Minimum Wall Box Depth         25mm           Switched Poles         Single           Current Rating         10AX           Voltage         220/250V AC           Maximum Load         10 Amp inductive           Mains Frequency         50Hz           IP Rating         IP2XD           Contact Gap Minimum         3mm           Terminal Capacity 1         5 x 1mm2           Terminal Capacity 2         4 x 1.5mm2           Terminal Capacity 3         1 x 2.5mm2           Terminal Capacity 4         1 x 4mm2 Multi-strand           Terminal Capacity 5         1 x 6mm2           Earth Terminal Capacity 1         5 x 1mm2           Earth Terminal Capacity 2         4 x 1.5mm2           Earth Terminal Capacity 3         3 x 2.5mm2           Earth Terminal Capacity 4         1 x 4mm2 Multi-strand           Earth Terminal Capacity 5         1 x 6mm2           Forduct Class 1         Must be earthed           Ambient Operating Temperature         -5° to +40°C           Recommended Location         Internal Use Only           Maximum Installation Altitude         2000m   | Dimensions (Nominal)  | Single: Height = 87.4mm Width = 87.4mm Depth = 4.65mm |                     |  |  |
| Switched Poles         Single           Current Rating         10AX           Voltage         220/250V AC           Maximum Load         10 Amp inductive           Mains Frequency         50Hz           IP Rating         IPZXD           Contact Gap Minimum         3mm           Terminal Capacity 1         5 x 1mm2           Terminal Capacity 2         4 x 1.5mm2           Terminal Capacity 3         1 x 2.5mm2           Terminal Capacity 4         1 x 4mm2 Multi-strand           Terminal Capacity 5         1 x 6mm2           Earth Terminal Capacity 1         5 x 1mm2           Earth Terminal Capacity 2         4 x 1.5mm2           Earth Terminal Capacity 3         3 x 2.5mm2           Earth Terminal Capacity 4         1 x 4mm2 Multi-strand           Earth Terminal Capacity 5         1 x 6mm2           Earth Terminal Capacity 3         3 x 2.5mm2           Earth Terminal Capacity 5         1 x 6mm2           Earth Terminal Capacity 6         1 x 6mm2           Earth Terminal Capacity 7         1 x 6mm2           Earth Terminal Capacity 8         1 x 6mm2           Earth Terminal Capacity 9         1 x 6mm2           Earth Terminal Capacity 9         1 x 6mm2           <  | Fixing Hole Centres   | Box Fixing = 60.3mm                                   |                     |  |  |
| Current Rating         10AX           Voltage         220/250V AC           Maximum Load         10 Amp inductive           Mains Frequency         50Hz           IP Rating         IP2XD           Contact Gap Minimum         3mm           Terminal Capacity 1         5 x 1mm2           Terminal Capacity 2         4 x 1.5mm2           Terminal Capacity 3         1 x 2.5mm2           Terminal Capacity 4         1 x 4mm2 Multi-strand           Terminal Capacity 5         1 x 6mm2           Earth Terminal Capacity 1         5 x 1mm2           Earth Terminal Capacity 2         4 x 1.5mm2           Earth Terminal Capacity 3         3 x 2.5mm2           Earth Terminal Capacity 4         1 x 4mm2 Multi-strand           Earth Terminal Capacity 5         1 x 6mm2           Forduct Class 1         Must be earthed           Ambient Operating Temperature         -5 to +40°C           Recommended Location         Internal Use Only           Maximum Installation Altitude         2000m  | Minimum Wall Box Depth  | 25mm  |                     |  |  |
| Voltage         220/250V AC           Maximum Load         10 Amp inductive           Mains Frequency         50Hz           IP Rating         IP2XD           Contact Gap Minimum         3mm           Terminal Capacity 1         5 x 1mm2           Terminal Capacity 2         4 x 1.5mm2           Terminal Capacity 3         1 x 2.5mm2           Terminal Capacity 4         1 x 4mm2 Multi-strand           Terminal Capacity 5         1 x 6mm2           Earth Terminal Capacity 1         5 x 1mm2           Earth Terminal Capacity 2         4 x 1.5mm2           Earth Terminal Capacity 3         3 x 2.5mm2           Earth Terminal Capacity 4         1 x 4mm2 Multi-strand           Earth Terminal Capacity 5         1 x 6mm2           Product Class 1         Must be earthed           Ambient Operating Temperature         -5° to +40°C           Recommended Location         Internal Use Only           Maximum Installation Altitude         2000m   | Switched Poles  | Single  |                     |  |  |
| Maximum Load         10 Amp inductive           Mains Frequency         50Hz           IP Rating         IP2XD           Contact Gap Minimum         3mm           Terminal Capacity 1         5 x 1mm2           Terminal Capacity 2         4 x 1.5mm2           Terminal Capacity 3         1 x 2.5mm2           Terminal Capacity 4         1 x 4mm2 Multi-strand           Terminal Capacity 5         1 x 6mm2           Earth Terminal Capacity 1         5 x 1mm2           Earth Terminal Capacity 2         4 x 1.5mm2           Earth Terminal Capacity 3         3 x 2.5mm2           Earth Terminal Capacity 4         1 x 4mm2 Multi-strand           Earth Terminal Capacity 5         1 x 6mm2           Product Class 1         Must be earthed           Ambient Operating Temperature         -5° to +40°C           Recommended Location         Internal Use Only           Maximum Installation Altitude         2000m   | Current Rating  | 10AX  |                     |  |  |
| Mains Frequency         50Hz           IP Rating         IP2XD           Contact Gap Minimum         3mm           Terminal Capacity 1         5 x 1mm2           Terminal Capacity 2         4 x 1.5mm2           Terminal Capacity 3         1 x 2.5mm2           Terminal Capacity 4         1 x 4mm2 Multi-strand           Terminal Capacity 5         1 x 6mm2           Earth Terminal Capacity 1         5 x 1mm2           Earth Terminal Capacity 2         4 x 1.5mm2           Earth Terminal Capacity 3         3 x 2.5mm2           Earth Terminal Capacity 4         1 x 4mm2 Multi-strand           Earth Terminal Capacity 5         1 x 6mm2           Product Class 1         Must be earthed           Ambient Operating Temperature         -5° to +40°C           Recommended Location         Internal Use Only           Maximum Installation Altitude         2000m   | Voltage   | 220/250V AC   |                     |  |  |
| IP Rating  | Maximum Load  | 10 Amp inductive                                      |                     |  |  |
| Contact Gap Minimum  Terminal Capacity 1  5 x 1mm2  Terminal Capacity 2  4 x 1.5mm2  Terminal Capacity 3  1 x 2.5mm2  Terminal Capacity 4  1 x 4mm2 Multi-strand  Terminal Capacity 5  1 x 6mm2  Earth Terminal Capacity 1  5 x 1mm2  Earth Terminal Capacity 2  4 x 1.5mm2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 4  1 x 4mm2 Multi-strand  Earth Terminal Capacity 5  1 x 6mm2  Product Class 1  Must be earthed  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  | Mains Frequency   |   |                     |  |  |
| Terminal Capacity 1         5 x 1mm2           Terminal Capacity 2         4 x 1.5mm2           Terminal Capacity 3         1 x 2.5mm2           Terminal Capacity 4         1 x 4mm2 Multi-strand           Terminal Capacity 5         1 x 6mm2           Earth Terminal Capacity 1         5 x 1mm2           Earth Terminal Capacity 2         4 x 1.5mm2           Earth Terminal Capacity 3         3 x 2.5mm2           Earth Terminal Capacity 4         1 x 4mm2 Multi-strand           Earth Terminal Capacity 5         1 x 6mm2           Product Class 1         Must be earthed           Ambient Operating Temperature         -5° to +40°C           Recommended Location         Internal Use Only           Maximum Installation Altitude         2000m  | IP Rating   | IP2XD   |                     |  |  |
| Terminal Capacity 2  Terminal Capacity 3  Terminal Capacity 4  Terminal Capacity 4  Terminal Capacity 5  Earth Terminal Capacity 1  Earth Terminal Capacity 2  Earth Terminal Capacity 2  Earth Terminal Capacity 3  Earth Terminal Capacity 3  Earth Terminal Capacity 4  Earth Terminal Capacity 4  Earth Terminal Capacity 4  Earth Terminal Capacity 5  Earth Terminal Capacity 5  Earth Terminal Capacity 6  Earth Terminal Capacity 7  Earth Terminal Capacity 8  Earth Terminal Capacity 9  Earth Terminal Capacity 9  Earth Terminal Capacity 5  I x 6mm2  Product Class 1  Must be earthed  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude   | Contact Gap Minimum   | 3mm   |                     |  |  |
| Terminal Capacity 3  1 x 2.5mm2  Terminal Capacity 4  1 x 4mm2 Multi-strand  Terminal Capacity 5  1 x 6mm2  Earth Terminal Capacity 1  Earth Terminal Capacity 2  4 x 1.5mm2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 4  1 x 4mm2 Multi-strand  Earth Terminal Capacity 5  1 x 6mm2  Product Class 1  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude   |   | 5 x 1mm2  |                     |  |  |
| Terminal Capacity 4  1 x 4mm2 Multi-strand  1 x 6mm2  Earth Terminal Capacity 1  5 x 1mm2  Earth Terminal Capacity 2  4 x 1.5mm2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 4  1 x 4mm2 Multi-strand  Earth Terminal Capacity 5  1 x 6mm2  Product Class 1  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude   |   |   |                     |  |  |
| Terminal Capacity 5  Earth Terminal Capacity 1  Earth Terminal Capacity 2  Earth Terminal Capacity 2  Earth Terminal Capacity 3  Earth Terminal Capacity 3  Earth Terminal Capacity 4  Earth Terminal Capacity 4  Earth Terminal Capacity 5  1 x 6mm2  Product Class 1  Must be earthed  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude   |   | 1 x 2.5mm2  |                     |  |  |
| Earth Terminal Capacity 1 5 x 1mm2  Earth Terminal Capacity 2 4 x 1.5mm2  Earth Terminal Capacity 3 3 x 2.5mm2  Earth Terminal Capacity 4 1 x 4mm2 Multi-strand  Earth Terminal Capacity 5 1 x 6mm2  Product Class 1 Must be earthed  Ambient Operating Temperature -5° to +40°C  Recommended Location Internal Use Only  Maximum Installation Altitude 2000m  | Terminal Capacity 4   |   |                     |  |  |
| Earth Terminal Capacity 2  Earth Terminal Capacity 3  Earth Terminal Capacity 4  I x 4mm2 Multi-strand  Earth Terminal Capacity 5  I x 6mm2  Product Class 1  Ambient Operating Temperature  Recommended Location  Internal Use Only  Maximum Installation Altitude  4 x 1.5mm2  1 x 4mm2 Multi-strand  1 x 6mm2  Must be earthed  -5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m   | Terminal Capacity 5   | 1 x 6mm2  |                     |  |  |
| Earth Terminal Capacity 3  Earth Terminal Capacity 4  1 x 4mm2 Multi-strand  Earth Terminal Capacity 5  1 x 6mm2  Product Class 1  Ambient Operating Temperature  Ambient Operating Temperature  Recommended Location  Internal Use Only  Maximum Installation Altitude  3 x 2.5mm2  1 x 4mm2 Multi-strand  1 x 6mm2  Must be earthed  -5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  | 1 1   |   |                     |  |  |
| Earth Terminal Capacity 4  Earth Terminal Capacity 5  1 x 6mm2  Product Class 1  Ambient Operating Temperature  Recommended Location  Internal Use Only  Maximum Installation Altitude  1 x 4mm2 Multi-strand  1 x 6mm2  Must be earthed  -5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m  | Earth Terminal Capacity 2   | 4 x 1.5mm2  |                     |  |  |
| Earth Terminal Capacity 5         1 x 6mm2           Product Class 1         Must be earthed           Ambient Operating Temperature         -5° to +40°C           Recommended Location         Internal Use Only           Maximum Installation Altitude         2000m   |   |   |                     |  |  |
| Product Class 1 Must be earthed  Ambient Operating Temperature -5° to +40°C  Recommended Location Internal Use Only  Maximum Installation Altitude 2000m   |   | 1 x 4mm2 Multi-strand                                 |                     |  |  |
| Ambient Operating Temperature -5° to +40°C  Recommended Location Internal Use Only  Maximum Installation Altitude 2000m  |   |   |                     |  |  |
| Recommended Location     Internal Use Only       Maximum Installation Altitude     2000m   |   | Must be earthed                                       |                     |  |  |
| Maximum Installation Altitude 2000m  | Ambient Operating Temperature   | -5° to +40°C  |                     |  |  |
|  | Recommended Location  |   |                     |  |  |
| Standard/Approval BS EN 60669-1  | Maximum Installation Altitude   | 2000m   |                     |  |  |
|  | Standard/Approval   | BS EN 60669-1   |                     |  |  |



SL

making connections beautifully

| Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio   |  |  |  |  |
|---|--|--|--|--|
| <u>7G29R22AB-B</u>  |  |  |  |  |
| Hartland G2 Antique Brass 2 gang 10AX 2 Way Rocker Antique Brass/Black  |  |  |  |  |
| Patents and Trademarks  | Hartland G2 is a Registered Trade Mark No UK00003388376  |  |  |  |
| All products listed conform to current British or<br>European standard and the product information is<br>correct at the time of going to press. | All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.        | It is the policy of the company to improve products<br>as part of our development programme.<br>Therefore, we reserve the right to alter designs<br>and dimensions without prior notice. |  |  |
| Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding                       | Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes | Correct as at 14 August 2019 04:05 PM<br>E&OE  |  |  |

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84









