




7G29TPBL-B

Hartland G2 Antique Brass 1 gang 10A Triple Pole Rocker Black/Black

| Item Image | Wiring | Dimensions |
|---|---|---|
|  |  |  |
| Primary Range | Hartland G2 | |
| Insert Type | 1 gang 10A Triple Pole Rocker | |
| Plate Finish | Hartland G2 Antique Brass | |
| Insert Colour | Black/Black | |
| EAN13 Barcode | 5051164003425 | |
| Commodity Code | 85363010 | |
| Luckins TSI | 407519398 | |
| Dimensions (Nominal) | Single: Height = 87.4mm Width = 87.4mm Depth = 4.65mm | |
| Fixing Hole Centres | Box Fixing = 60.3mm | |
| Minimum Wall Box Depth | 25mm | |
| Switched Poles | Triple | |
| Current Rating | 10A | |
| Voltage | 220/250V AC | |
| Maximum Load | 10 Amp resistive | |
| Mains Frequency | 50Hz | |
| IP Rating | IP2XD | |
| Contact Gap Minimum | 3mm | |
| Terminal Capacity 1 | 5 x 1mm ² | |
| Terminal Capacity 2 | 4 x 1.5mm ² | |
| Terminal Capacity 3 | 1 x 2.5mm ² | |
| Terminal Capacity 4 | 1 x 4mm ² Multi-strand | |
| Terminal Capacity 5 | 1 x 6mm ² | |
| Earth Terminal Capacity 1 | 5 x 1mm ² | |
| Earth Terminal Capacity 2 | 4 x 1.5mm ² | |
| Earth Terminal Capacity 3 | 3 x 2.5mm ² | |
| Earth Terminal Capacity 4 | 1 x 4mm ² Multi-strand | |
| Earth Terminal Capacity 5 | 1 x 6mm ² | |
| Product Class 1 | Must be earthed | |
| Ambient Operating Temperature | -5° to +40°C | |
| Recommended Location | Internal Use Only | |
| Maximum Installation Altitude | 2000m | |
| Standard/Approval | BS EN 60669-1 | |

7G29TPBL-B

Hartland G2 Antique Brass 1 gang 10A Triple Pole Rocker Black/Black

| | | | | | |
|---|--|---|---|---|--|
| Patents and Trademarks | | | Hartland G2 is a Registered Trade Mark No UK00003388376 | | |
| All products listed conform to current British or European standard and the product information is correct at the time of going to press. | | All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. | | It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. | |
| Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. | | Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes. | | Correct as at 14 August 2019 04:05 PM E&OE | |

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414

E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB

Registered in London No. 941624 VAT Registration No. 222 6607 84



CERT. No. FM11238