SL

making connections beautifully

| Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio | | |
|---|---|--|
| 7G2MBEURO2 | | |
| Hartland G2 EuroFix Matt Black Single Plate complete with 2 EuroFix Apertures 50x50mm and Grid | | |
| Triantana G2 Euror ix Matt Black Gingle Frate complete with 2 Euror ix Apertures 30x30mm and Gna | | |
| Item Image | Wiring | Dimensions |
| | | Hemilton HARTLAND G2 EURO2 Single plate with 2 x EuroFix cutout |
| | | 57.A 50.0 TITLES |
| Primary Range | EuroFix | |
| Insert Type | 2 Gang EuroFix 50x50mm Apertured Plate with Grid | |
| Plate Finish | Hartland G2 EuroFix Matt Black | |
| Insert Colour | No Insert Colour | |
| EAN13 Barcode | 5051164004354 | |
| Commodity Code | 73269098 | |
| Luckins TSI | 407516883 | |
| Dimensions (Nominal) | Single: Height = 87.4mm Width = 87.4mm Depth = 4.65mm | |
| Fixing Hole Centres | Box Fixing = 60.3mm | |
| Minimum Wall Box Depth | As Per Inserts | |
| Switched Poles | N/A | |
| IP Rating | N/A | |
| Contact Gap Minimum | N/A | |
| Earth Terminal Capacity 1 | 5 x 1mm2 | |
| Earth Terminal Capacity 2 | 4x1.5mm2 | |
| Earth Terminal Capacity 3 | 3 x 2.5mm2 | |
| Earth Terminal Capacity 4 | 1 x 4mm2 Multi-strand | |
| Earth Terminal Capacity 5 | 1 x 6mm2 | |
| Product Class 1 | Face plate must be earthed | |
| Recommended Location | Internal Use Only | |
| Maximum Installation Altitude | 2000m | |
| Standard/Approval | N/A | |
| Additional Notes | es See EuroFix for a full range of inserts. Plates must be Earthed via the Earth Tag. | |
| atents and Trademarks EuroFix is a Registered Trade Mark No. 2560270 | | |
| All products listed conform to current British or European standard and the product information is correct at the time of going to press. | All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. | It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. |
| Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. | Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes. | Correct as at 14 August 2019 04:03 PM E&OE |

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84











