SL

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

7G2MBTVSATB

Primary Range Hartland G2 Insert Type 2 gang Non-isolated TV+Satellite Zin/Zout Hartland G2 Mon-isolated TV+Satellite Zin/Zout Hartland G2 Matt Black Insert Colour Black EAN13 Barcode 5051164004651 Commodity Code 85366910 Luckins TS1 407517785 Dimensions (Nominal) Single: Height = 87.4mm Width = 87.4mm Depth = 4.65mm Fixing Hole Centres Box Fixing = 60.3mm Minimum Wall Box Depth 35mm Switched Poles N/A IP Rating IP 2XD Contact Gap Minimum NA Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed (ref BS7671 415.2.1) Ambient Operating Temperature	Hartland G2 Matt Black 2 gang Non-Isolated TV+Satellite 2in/2out Black			
Primary Range	Item Image	Wiring	Dimensions	
Primary Range Hartland G2 Insert Type 2 gang Non-Isolated TV+Satellite 2in/Zout Plate Finish Hartland G2 Matt Black Insert Colour Black EAN13 Barcode 5051164004651 Commodity Code 85366910 Luckins TSI 407517785 Dimensions (Nominal) Single: Height = 87.4mm Width = 87.4mm Depth = 4.65mm Fixing Hole Centres Box Fixing = 60.3mm Minimum Wall Box Depth 35mm Minimum Wall Box Depth 35mm Switched Poles N/A IP Rating IP2XD Contact Gap Minimum N/A Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed (ref BS7671415.2.1)		Single	HARTLAND G2 TVSAT Non-Isolated TV + Satellite 2in/2out	
Insert Type		Under Cable	87.4 50.0	
Plate Finish Hartland G2 Matt Black Insert Colour Black EAN13 Barcode 5051164004651 Commodity Code 85366910 Luckins TSI 407517785 Dimensions (Nominal) Single: Height = 87.4mm Width = 87.4mm Depth = 4.65mm Fixing Hole Centres Box Fixing = 60.3mm Minimum Wall Box Depth 35mm Switched Poles N/A IP Rating IP2XD Contact Gap Minimum N/A Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed (ref BS7671 415.2.1)	Primary Range	Hartland G2		
Insert Colour	Insert Type	2 gang Non-Isolated TV+Satellite 2in/2out		
EAN13 Barcode 5051164004651 Commodity Code 85366910 Luckins TSI 407517785 Dimensions (Nominal) Single: Height = 87.4mm Width = 87.4mm Depth = 4.65mm Fixing Hole Centres Box Fixing = 60.3mm Minimum Wall Box Depth 35mm Switched Poles N/A IP Rating IP2XD Contact Gap Minimum N/A Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed (ref BS7671 415.2.1)	Plate Finish	Hartland G2 Matt Black		
Commodity Code 85366910 Luckins TSI 407517785 Dimensions (Nominal) Single: Height = 87.4mm Width = 87.4mm Depth = 4.65mm Fixing Hole Centres Box Fixing = 60.3mm Minimum Wall Box Depth 35mm Switched Poles N/A IP Rating IP2XD Contact Gap Minimum N/A Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed (ref BS7671 415.2.1)	Insert Colour	Black		
Luckins TSI 407517785 Dimensions (Nominal) Single: Height = 87.4mm Width = 87.4mm Depth = 4.65mm Fixing Hole Centres Box Fixing = 60.3mm Minimum Wall Box Depth 35mm Switched Poles N/A IP Rating IP2XD Contact Gap Minimum N/A Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed (ref BS7671 415.2.1)	EAN13 Barcode	5051164004651		
Dimensions (Nominal) Single: Height = 87.4mm Width = 87.4mm Depth = 4.65mm Fixing Hole Centres Box Fixing = 60.3mm Minimum Wall Box Depth 35mm Switched Poles N/A IP Rating IP2XD Contact Gap Minimum N/A Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed (ref BS7671 415.2.1)	Commodity Code	85366910		
Fixing Hole Centres Box Fixing = 60.3mm Minimum Wall Box Depth 35mm Switched Poles N/A IP Rating IP2XD Contact Gap Minimum N/A Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed (ref BS7671 415.2.1)	Luckins TSI	407517785		
Minimum Wall Box Depth 35mm Switched Poles N/A IP Rating IP2XD Contact Gap Minimum N/A Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed (ref BS7671 415.2.1)	Dimensions (Nominal)	Single: Height = 87.4mm Width = 87.4mm Depth = 4.65mm		
Switched Poles N/A IP Rating IP2XD Contact Gap Minimum N/A Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed (ref BS7671 415.2.1)	Fixing Hole Centres	Box Fixing = 60.3mm		
IP Rating IP2XD Contact Gap Minimum N/A Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed (ref BS7671 415.2.1)	Minimum Wall Box Depth	35mm		
Contact Gap Minimum N/A Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed (ref BS7671 415.2.1)	Switched Poles	N/A		
Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed (ref BS7671 415.2.1)	IP Rating	IP2XD		
Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Product Class 1 4 x 1.5mm2 1 x 4mm2 Multi-strand 1 x 4mm2 Multi-strand Must be earthed (ref BS7671 415.2.1)	Contact Gap Minimum	N/A		
Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed (ref BS7671 415.2.1)	Earth Terminal Capacity 1	5 x 1mm2		
Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed (ref BS7671 415.2.1)	Earth Terminal Capacity 2	4 x 1.5mm2		
Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed (ref BS7671 415.2.1)	Earth Terminal Capacity 3	3 x 2.5mm2		
Product Class 1 Must be earthed (ref BS7671 415.2.1)	Earth Terminal Capacity 4	1 x 4mm2 Multi-strand		
	Earth Terminal Capacity 5			
Ambient Operating Temperature -5° to +40°C	Product Class 1	Must be earthed (ref BS7671 415.2.1)		
	Ambient Operating Temperature			
Recommended Location Internal Use Only	Recommended Location	Internal Use Only		
Maximum Installation Altitude 2000m				
Standard/Approval BS 5733	Standard/Approval	BS 5733		
Patents and Trademarks Hartland G2 is a Registered Trade Mark No UK00003388376	Patents and Trademarks	Hartland G2 is a Registered Trade Mark No UK00003388376		
All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice.	European standard and the product information is		Therefore, we reserve the right to alter designs	
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes. Correct as at 14 August 2019 of certain finishes.	the limitations of reproduction and printing	guarantee an exact colour match and shadings of	Correct as at 14 August 2019 04:06 PM E&OE	

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84











