Hamilton

making connections beautifully

| | Wiring Accessories • Circuit Protection • Sn | nart Lighting Control & Multi-room Audio |
|--|---|--|
| | 7G2MW2J45-C6W | |
| Hartland G | 2 Matt White 2 gang RJ45 CAT 6 Outlet - Unsl | hielded White |
| Thankand Oz Mak White Z gang 1040 CAT 0 Outlet - Unshielded White | | |
| Item Image | Wiring | Dimensions |
| | RJ45 CAT5e Rew View | |
| Primary Range | Hartland G2 | |
| Insert Type | 2 gang RJ45 CAT 5E Outlet - Unshielded | |
| Plate Finish | Hartland G2 Matt White | |
| Insert Colour | White | |
| EAN13 Barcode | 5051164004729 | |
| Commodity Code | 85176990 | |
| Luckins TSI | 407517808 | |
| Dimensions (Nominal) | Single: Height = 87.4mm Width = 87.4mm Depth = 4.65mm | |
| Fixing Hole Centres | Box Fixing = 60.3mm | |
| Minimum Wall Box Depth | 35mm | |
| Switched Poles | N/A | |
| IP Rating | IP2XD | |
| Contact Gap Minimum | N/A | |
| Earth Terminal Capacity 1 | 5 x 1mm2 | |
| Earth Terminal Capacity 2 | 4 x 1.5mm2 | |
| Earth Terminal Capacity 3 | 3 x 2.5mm2 | |
| Earth Terminal Capacity 4 | 1 x 4mm2 Multi-strand | |
| Earth Terminal Capacity 5 | 1 x 6mm2 | |
| Product Class 1 | Must be earthed (ref BS7671 415.2.1) | |
| Ambient Operating Temperature | -5° to +40°C | |
| Recommended Location | Internal Use Only | |
| Maximum Installation Altitude | 2000m | |
| Standard/Approval | N/A | |
| EuroFix Additional Notes | Can be used in both EIA 568A and EIA 568B wiriing schedules | |
| Patents and Trademarks | Hartland G2 is a Registered Trade Mark No UK00003388376 | |
| All products listed conform to current British or European standard and the product information is correct at the time of going to press. | All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. | It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. |
| Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. | Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes. | Correct as at 14 August 2019 04:06 Pt E&O |
| R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville T: +44 (0)1747 860088 F: +44 (0)1179 710414 Registered E: info@hamilton-litestat.com www.hamilton-litestat.com Registered | Road, Brislington, Bristol, BS4 5NZ Office 1 Rushmills, Bedford Road, Northampton NN4 7YB in London No. 941624 VAT Registration No. 222 6607 84 | Listed in Strimble product PLSPIus CER. No. 7011238 |

SL