Hamilton

making connections beautifully

SL

	Wiring Accessories • Circuit Protection • Sr	nare Ebrang Control of Falls Footh Falls
Hartland CFX Connaught Bronze Non-I	<u>7HBCDSAT+B</u> solated TV+FM+SAT1+SAT2 Quadplexer 2in	/4out +TVF+TCS (DAB Compatible) Black
Item Image	Wiring	Dimensions
	Cable Clamp Screw Cable Clamp Screw Clamp Screw Cable Clamp Screw Clamp Screw	HEIRILAD CEX DATA Data Dadpiezer Zin/Aout + TVF + TCS
Primary Range	Hartland CFX	
Insert Type	Non-Isolated TV+FM+SAT1+SAT2 Quadplexer 2in/4out +TVF+TCS (DAB Compatible)	
Plate Finish	Hartland CFX Connaught Bronze	
Insert Colour	Black	
EAN13 Barcode	5017504012885	
	Double: Height = 86.0mm Width = 145.0mm Depth = 5.0mm	
Dimensions (Nominal)	Box Fixing = 120.6mm Grid Fixing = CFX Clips	
Fixing Hole Centres		
Minimum Wall Box Depth	35mm N/A	
Switched Poles		
IP Rating		
Contact Gap Minimum	N/A	
Earth Terminal Capacity 1	5 x 1mm2	
Earth Terminal Capacity 2	4 x 1.5mm2	
Earth Terminal Capacity 3	3 x 2.5mm2	
Earth Terminal Capacity 4	1 x 4mm2 Multi-strand	
Earth Terminal Capacity 5	1 x 6mm2	
Product Class 1	Must be earthed (ref BS7671 415.2.1)	
Ambient Operating Temperature	-5° to +40°C	
Recommended Location	Internal Use Only	
Maximum Installation Altitude	2000m	
EuroFix Additional Notes	Quadplexer for use with combined TV FM and Satellite Signals (DAB compatible) plus Telephone Slave and Female TV Socket	
Frequencies 1	TV=5-68 MHz 125-860 MHz	
Frequencies 2	FM=88-108 MHz	
Frequencies 3	SAT DC=950-2200 MHz	
Frequencies 4	TV DC=5-2200 MHz	
Patents and Trademarks	CFX is a Registered Trade Mark No 2398667 Hartland CFX is a Registered Design under Reference Nos. R21 = 3023446 SS2 = 3023445	
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 16 October 2018 12:41 PM E&OE
R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville T: +44 (0)1747 860088 F: +44 (0)1179 710414 Registered E: info@hamilton-litestat.com www.hamilton-litestat.com	Road, Brislington, Bristol, BS4 5NZ Office 1 Rushmills, Bedford Road, Northampton NN4 7YB in London No. 941624 VAT Registration No. 222 6607 84	Tiba product selector Instruction (CERTING MALE)