

SL

making connections beautifully

| Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio                  |  |   |  |
|--|--|---|--|
| 7HBCSHSB   |  |   |  |
| Hartland CFX Connaught Bronze Shaver Dual Voltage Unswitched Socket (Vertically Mounted) Black       |  |   |  |
| Transand of A Confidugition Divise Shaver Dual Voltage of Switched Socket (Vertically Mounted) Diack |  |   |  |
| Item Image   | Wiring   | Dimensions  |  |
|  | Nontral Exact Earth  | HARTLAND CFX SHS Shaver Dual Voltage Unswitched Socket (Vertical Mounted)  145.0  145.0 |  |
| Primary Range  | Hartland CFX   |   |  |
| Insert Type  | Shaver Dual Voltage Unswitched Socket (Vertically Mounted)             |   |  |
| Plate Finish   | Hartland CFX Vertical Connaught Bronze                                 |   |  |
| Insert Colour  | Black  |   |  |
| EAN13 Barcode  | 5017504013257  |   |  |
| Dimensions (Nominal)   | Double: Height = 145.0mm Width = 86.0mm Depth = 5.0mm                  |   |  |
| Fixing Hole Centres  | Box Fixing = 120.6mm Grid Fixing = CFX Clips                           |   |  |
| Minimum Wall Box Depth   | 47mm   |   |  |
| Switched Poles   | None   |   |  |
| Current Rating   | 20VA   |   |  |
| Voltage  | 220/250V AC  |   |  |
| Maximum Load   | 200/250V input; 115/230V 20VA output                                   |   |  |
| Mains Frequency  | 50Hz   |   |  |
| IP Rating  | IP2XD  |   |  |
| Contact Gap Minimum  | None   |   |  |
| Terminal Capacity 1  | 5 x 1mm2   |   |  |
| Terminal Capacity 2  | 4 x 1.5mm2   |   |  |
| Terminal Capacity 3  | 3 x 2.5mm2   |   |  |
| Terminal Capacity 4  | 2 x 4mm2 Multi-strand  |   |  |
| Terminal Capacity 5  | 1 x 6mm2   |   |  |
| Earth Terminal Capacity 1  | 9 x 1mm2   |   |  |
| Earth Terminal Capacity 2  | 6 x 1.5mm2   |   |  |
| Earth Terminal Capacity 3  | 4 x 2.5mm2   |   |  |
| Earth Terminal Capacity 4  | 2 x 4mm2 Multi-strand  |   |  |
| Earth Terminal Capacity 5  | 1 x 6mm2   |   |  |
| Product Class 1  | Must be earthed  |   |  |
| Ambient Operating Temperature  | -5° to +40°C   |   |  |
| Recommended Location   | Internal Use Only  |   |  |
| Maximum Installation Altitude  | 2000m  |   |  |
| Standard/Approval  | BS EN 61558-2-5 - BS 4573  |   |  |
| Additional Notes   | ional Notes Must be mounted vertically. Shuttered :Yes. Box Depth 47mm |   |  |
|  |  |   |  |



SL

making connections beautifully

| Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio   |  |  |  |  |
|---|--|--|--|--|
| 7HBCSHSB  |  |  |  |  |
| Hartland CFX Connaught Bronze Shaver Dual Voltage Unswitched Socket (Vertically Mounted) Black  |  |  |  |  |
| Patents and Trademarks  | CFX is a Registered Trade Mark No 2398667 Hartland CFX is a Registered Design under Reference Nos. R21 = 3023446 SS2 = 3023445 |  |  |  |
| All products listed conform to current British or<br>European standard and the product information is<br>correct at the time of going to press. | All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.                          | It is the policy of the company to improve products<br>as part of our development programme.<br>Therefore, we reserve the right to alter designs<br>and dimensions without prior notice. |  |  |
| Illustrations and diagrams are reproduced within the limitations of reproduction and printing   | Due to manufacturing processes we cannot guarantee an exact colour match and shadings of                                       | Correct as at 16 October 2018 12:41 PM<br>E&OE   |  |  |

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84











